

## SAFETY DATA SHEET

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

**SDS code** : 8118933

AN006GF/20KG

**UFI** : CP78-60XK-700E-KG9C

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses					
Industrial use					
	Uses advised against				
Consumer use					

Product use : Electrostatic coating for use in industrial plants

#### 1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited

Stoneygate Lane,

Felling, Gateshead. NE10 0JY United Kingdom

e-mail address of person : responsible for this SDS

ou ranguom

: sdsfellinguk@akzonobel.com

**National contact** 

01 8092566 or 01 8379964

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : +44 (0)344 892 0111

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Repr. 1B, H360F

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-20241/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

#### **SECTION 2: Hazards identification**

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :





Signal word : Danger

**Hazard statements** : H360F - May damage fertility.

H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

or hearing protection.

P273 - Avoid release to the environment.

**Response** : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

**Disposal**: P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

**Hazardous ingredients** : 4,4'-isopropylidenediphenol

Supplemental label

elements

: Contains 4,4'-isopropylidenediphenol. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: May cause endocrine disruption.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Date of issue/Date of revision : 10-7-2025 Version : 4

Date of previous issue : 14-2-2024 2/17 AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
4,4'-isopropylidenediphenol	REACH #: 01-2119457856-23 EC: 201-245-8 CAS: 80-05-7	<1	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 10	[1] [2] [3]
2-methylimidazole	REACH #: 01-2119980041-46 EC: 211-765-7 CAS: 693-98-1	<0.3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Carc. 2, H351 Repr. 1B, H360Df	ATE [Oral] = 500 mg/kg	[1]
2-Naphthalenol, 1-[ (2-methyl-1H-imidazol-1-yl) methyl]-	REACH #: 01-0000017450-78 CAS: 185554-99-8	≤0.3	Aquatic Acute 1, H400 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

- [1] Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-20243/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

#### **SECTION 4: First aid measures**

Ingestion

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being

discharged to any waterway, sewer or drain.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

Date of issue/Date of revision : 10-7-2025 Version : 4

Date of previous issue : 14-2-2024 4/17 AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### SECTION 5: Firefighting measures

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### 6.3 Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision : 10-7-2025 Version : 4

**AkzoNobel** Date of previous issue :14-2-2024 5/17

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### **SECTION 7: Handling and storage**

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### **Seveso Directive - Reporting thresholds**

#### **Danger criteria**

	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
4,4'-isopropylidenediphenol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 2 mg/m³ 8 hours. Form: inhalable dust

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-20246/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Type	Exposure	Value	Population	Effects
4,4'-isopropylidenediphenol	DNEL	Short term Dermal	24 μg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	24 μg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	53 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	53 μg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	66 µg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	66 µg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	1 mg/m³	General population	Local
	DNEL	Long term Inhalation	1 mg/m³	General population	Local
	DNEL	Short term Inhalation	1 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	1 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	2 mg/m³	Workers	Local
	DNEL	Long term Inhalation	2 mg/m³	Workers	Local
	DNEL	Short term Inhalation	2 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	2 mg/m³	Workers	Systemic
2-methylimidazole	DNEL	Long term Oral	0.02 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.04 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.3 mg/m <sup>3</sup>	Workers	Systemic

### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
4,4'-isopropylidenediphenol	Marine water Fresh water sediment	0.023 mg/l 0.019 mg/l 1.2 mg/kg dwt 0.24 mg/kg dwt	Sensitivity Distribution Sensitivity Distribution Assessment Factors Assessment Factors

### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-20247/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### **SECTION 8: Exposure controls/personal protection**

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

## Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton R or Nitrile, thickness R on the contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness R on the contact is expected.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

## Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Version: 4

 Date of issue/Date of revision
 : 10-7-2025
 Vers

 Date of previous issue
 : 14-2-2024
 8/17

AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Solid. Colour : Black. : Odourless. Odour Odour threshold : Not available. Melting point/freezing point : Not available. Boiling point, initial boiling : Not applicable.

point, and boiling range

**Flammability** Lower and upper explosion

limit

: Not available. : 20 - 70 g/m3

Flash point : Not applicable.

: 450 to 600°C (842 to 1112°F) **Auto-ignition temperature** 

**Decomposition temperature** : Not available.

Hq : Not applicable. [DIN EN 1262]

: Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] **Viscosity** 

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies)

Media	Result
cold water	Not soluble [OECD (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure : Not available.

Relative density : 1.2 to 1.9 [ISO 8130-2/-3]

Vapour density : Not applicable.

Particle characteristics

: Not available. Median particle size

Percentage of particles with aerodynamic diameter ≤ 10

μm

: 0

#### 9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

**Fundamental burning velocity** : Not applicable. **SADT** : Not available. Heat of combustion : Not available.

**Aerosol product** 

Type of aerosol : Not applicable.

Date of issue/Date of revision : 10-7-2025 Version: 4

**AkzoNobel** Date of previous issue :14-2-2024 9/17

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-isopropylidenediphenol	LD50 Dermal	Rabbit	3 mL/kg	-
	LD50 Oral	Rat	3250 mg/kg	-
2-methylimidazole	LD50 Intraperitoneal	Mouse	480 mg/kg	-
	LD50 Oral	Mouse	1400 mg/kg	-

**Conclusion/Summary**: Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2-methylimidazole	500	N/A	N/A	N/A	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-isopropylidenediphenol	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
				ug	
	Skin - Mild irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	

**Conclusion/Summary** 

: Not available.

**Sensitisation** 

**Conclusion/Summary** 

: Not available.

**Mutagenicity** 

**Conclusion/Summary** 

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-202410/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### **SECTION 11: Toxicological information**

Conclusion/Summary : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-isopropylidenediphenol	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

Potential acute health effects

**Eve contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eve contact** : No specific data.

Inhalation : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

Date of issue/Date of revision : 10-7-2025 Version: 4

**AkzoNobel** Date of previous issue :14-2-2024 11/17

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### **SECTION 11: Toxicological information**

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

No additional information.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
4,4'-isopropylidenediphenol	Acute EC50 1000 μg/l Marine water Acute LC50 50.4 μg/l Marine water Acute LC50 4600 μg/l Fresh water Chronic NOEC 0.1 mg/l Fresh water	Algae - Skeletonema costatum Crustaceans - Artemia sinica Fish - Pimephales promelas Crustaceans - Asellus aquaticus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 48 hours 96 hours 21 days
2-methylimidazole	Acute LC50 286000 μg/l Fresh water	Fish - Pimephales promelas	96 hours

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
4,4'-isopropylidenediphenol 2-Naphthalenol, 1-[ (2-methyl-1H-imidazol-1-yl)	-		Readily Not readily
methyl]-			

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4,4'-isopropylidenediphenol	3.4	20 to 67	low
2-methylimidazole	0.24	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Date of issue/Date of revision	: 10-7-2025	Version : 4	
Date of previous issue	: 14-2-2024	12/17	AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

### **SECTION 12: Ecological information**

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal**: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations**: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 02 01	waste coating powders	

#### **Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

**Disposal considerations**: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

**Special precautions**: This material and its container must be disposed of in a safe way. Care should be

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

Date of issue/Date of revision: 10-7-2025Version: 4Date of previous issue: 14-2-202413/17AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bisphenol A)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bisphenol A)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bisphenol A)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Marine Pollutant(s): bisphenol A	Yes.

#### **Additional information**

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L

or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2

and 4.1.1.4 to 4.1.1.8. Tunnel code (-)

**IMDG** : Emergency schedules F-A, S-F

> This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2

and 4.1.1.4 to 4.1.1.8.

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L **IATA** 

or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1,

5.0.2.6.1.1 and 5.0.2.8.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO

instruments

: Not applicable.

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

Date of issue/Date of revision : 10-7-2025 Version: 4 **AkzoNobel** Date of previous issue :14-2-2024 14/17

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## **SECTION 15: Regulatory information**

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Toxic to reproduction	bisphenol A 2-methylimidazole	Recommended Candidate	ED/01/2018 D(2020) 4578-DC	10/1/2019 6/25/2020
Endocrine disrupting properties for human health	bisphenol A	Recommended	ED/01/2018	10/1/2019
Endocrine disrupting properties for environment	bisphenol A	Recommended	ED/01/2018	10/1/2019

Annex XVII - Restrictions :

: Restricted to professional users.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### **Other EU regulations**

VOC : Not applicable.VOC for Ready-for-Use : Not applicable.

**Mixture** 

Industrial emissions : Listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Listed

(integrated pollution prevention and control) -

Water

### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Persistent Organic Pollutants**

Not listed.

#### **Seveso Directive**

This product is controlled under the Seveso Directive.

#### **Danger criteria**

Category
Γ2

E2

#### **National regulations**

#### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

Date of issue/Date of revision : 10-7-2025 Version : 4

Date of previous issue : 14-2-2024 15/17 AkzoNobel

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

## SECTION 15: Regulatory information

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. acronyms

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Repr. 1B, H360F	Calculation method
Aquatic Chronic 2, H411	Calculation method

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Carc. 2 Eye Dam. 1 Repr. 1B Skin Corr. 1C Skin Sens. 1	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 REPRODUCTIVE TOXICITY - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -
	Category 3

Date of printing : 10-7-2025 Date of issue/ Date of : 10-7-2025

revision

Date of issue/Date of revision : 10-7-2025 Version: 4 **AkzoNobel** Date of previous issue : 14-2-2024 16/17

AN006GF BLACK GLOSS 90-12-9922-0 Interpon A1242

#### **SECTION 16: Other information**

Date of previous issue : 14-2-2024

Version : 4 Unique ID :

#### Notice to reader

#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 10-7-2025 Version : 4

Date of previous issue : 14-2-2024 17/17 AkzoNobel