

SAFETY DATA SHEET

PA100QF 20-1015 INT 200 INTERPON 200 SKY WHITE

Section 1. Identification **GHS** product identifier : PA100QF 20-1015 INT 200 INTERPON 200 SKY WHITE SDS code : 8121258 PA100QF/25KG Relevant identified uses of the substance or mixture and uses advised against Identified uses Industrial use Uses advised against All other uses Product use : Electrostatic coating for use in industrial plants Supplier's details Akzo Nobel Coatings Inc. 150 Columbia Street Reading, PA 19601 USA 1-610-372-3600 **Emergency telephone** : CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls number (with hours of accepted) operation) Domestic Poison Control Center Customer Service +1 (800) 854-6813 Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Classification of the** : COMBUSTIBLE DUSTS **CARCINOGENICITY - Category 2** substance or mixture **TOXIC TO REPRODUCTION - Category 2 GHS label elements** Hazard pictograms



Signal word Hazard statements	 Warning Suspected of causing cancer. Suspected of damaging fertility May form combustible dust con 		
Precautionary statements			
Prevention	: Obtain special instructions before eye or face protection.	re use. Wear protective gloves,	protective clothing and
Response	: IF exposed or concerned: Get r	nedical advice or attention.	
Storage	: Not applicable.		
Date of issue/Date of revision	: 12/13/2022	Version : 1	
Date of previous issue	: No previous validation	1/11	AkzoNobel

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
titanium dioxide	≥25 - ≤50	13463-67-7
Limestone	≤5	1317-65-3
Kaolin	≤3	1332-58-7
propylidynetrimethanol	≤1	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: Exposure to airborne concent	rations above statutory or recor	nmended exposure limits
	may cause irritation of the eye		
Inhalation	: Exposure to airborne concent may cause irritation of the nos		nmended exposure limits
Skin contact	: No known significant effects of	r critical hazards.	
Ingestion	: No known significant effects of	r critical hazards.	
Date of issue/Date of revision	: 12/13/2022	Version : 1	
Date of previous issue	: No previous validation	2/11	AkzoNobel

Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and

Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	1			
Protective measures	ol ha or w ac ve m ec co pi di ec	ut on appropriate personal protective otain special instructions before use. andle until all safety precautions have on skin or clothing. Do not ingest. A hen handling and avoid all possible s occumulation. Use only with adequate entilation is inadequate. Keep in the ade from a compatible material, kept quipment and lighting should be prote oming into contact with hot surfaces, recautionary measures against electro ssipate static electricity during transfe quipment before transferring material an be hazardous. Do not reuse contact	Avoid exposure during pregna been read and understood. D Avoid breathing dust. Avoid the ources of ignition (spark or flan ventilation. Wear appropriate original container or an approve tightly closed when not in use. ected to appropriate standards sparks or other ignition sources ostatic discharges. To avoid fin er by grounding and bonding co . Empty containers retain prod	ncy. Do not bo not get in eyes e creation of dust ne). Prevent dust respirator when ed alternative . Electrical to prevent dust s. Take re or explosion, ontainers and
Advice on general occupational hygiene	ha di ei	ating, drinking and smoking should be andled, stored and processed. Work inking and smoking. Remove contar ntering eating areas. See also Sectio easures.	ers should wash hands and fac ninated clothing and protective	ce before eating, equipment before
Conditions for safe storage, including any incompatibilities	S aı lo co oj uı	tore in accordance with local regulation tore in original container protected from rea, away from incompatible materials cked up. Eliminate all ignition source ontainer tightly closed and sealed unti- bened must be carefully resealed and nabeled containers. Use appropriate ontamination. See Section 10 for inco	om direct sunlight in a dry, cool s (see Section 10) and food an es. Separate from oxidizing ma il ready for use. Containers tha I kept upright to prevent leakag containment to avoid environm	and well-ventilated d drink. Store aterials. Keep at have been je. Do not store in nental
Date of issue/Date of revision	:	12/13/2022	Version :1	
Date of previous issue	:	No previous validation	4/11	AkzoNobel

Section 7. Handling and storage

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits	
titanium dioxide Limestone Kaolin propylidynetrimethanol		OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2022). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles None. None. None.	
	Lles entruith adaguate ventil	ation. If your operations generate dust fumae, gene war	
Appropriate engineering controls	or mist, use process enclosur to keep worker exposure to a limits. The engineering contro	ation. If user operations generate dust, fumes, gas, vap res, local exhaust ventilation or other engineering contro irborne contaminants below any recommended or statut ols also need to keep gas, vapor or dust concentrations its. Use explosion-proof ventilation equipment.	ols tory
Environmental exposure controls	they comply with the requirem	work process equipment should be checked to ensure nents of environmental protection legislation. In some or engineering modifications to the process equipment missions to acceptable levels.	[
Individual protection measure	<u>95</u>		
Hygiene measures	eating, smoking and using the Appropriate techniques shoul	ace thoroughly after handling chemical products, before e lavatory and at the end of the working period. d be used to remove potentially contaminated clothing. before reusing. Ensure that eyewash stations and safet estation location.	
Eye/face protection	assessment indicates this is r gases or dusts. If contact is p the assessment indicates a h	th an approved standard should be used when a risk necessary to avoid exposure to liquid splashes, mists, possible, the following protection should be worn, unless igher degree of protection: safety glasses with side- ns cause high dust concentrations to be produced, use	3
Skin protection			
Hand protection	worn at all times when handlin necessary. Considering the p during use that the gloves are noted that the time to breakth glove manufacturers. In the c	Is gloves complying with an approved standard should bing chemical products if a risk assessment indicates this barameters specified by the glove manufacturer, check e still retaining their protective properties. It should be rough for any glove material may be different for differe case of mixtures, consisting of several substances, the cannot be accurately estimated.	s is
Body protection		nt for the body should be selected based on the task bei ved and should be approved by a specialist before	ing
Other skin protection		additional skin protection measures should be selected ormed and the risks involved and should be approved by product.	
Respiratory protection	appropriate standard or certifi	ential for exposure, select a respirator that meets the cation. Respirators must be used according to a n to ensure proper fitting, training, and other important	
Date of issue/Date of revision	: 12/13/2022	Version :1	
Date of previous issue	: No previous validation	5/11 AkzoNot	bel

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Solid. [Powder.]
Color	:	White.
Odor	:	Odorless.
Odor threshold	:	Not available.
рН	:	Not applicable. [DIN EN 1262]
Melting point/freezing point	:	Not available.
Boiling point, initial boiling point, and boiling range	:	Not available.
Flash point	:	Closed cup: Not applicable. [Pensky-Martens]
Flash point Flammability		Closed cup: Not applicable. [Pensky-Martens] Not available.
· · · · · · · · · · · · · · · · · · ·	:	
Flammability Lower and upper explosion	:	Not available.
Flammability Lower and upper explosion limit/flammability limit	:	Not available. 20 - 70 g/m3
Flammability Lower and upper explosion limit/flammability limit Vapor pressure	::	Not available. 20 - 70 g/m3 Not available.

,		
Media		Result
cold water		Not soluble [OESO (TG 105)]
Partition coefficient: n- octanol/water	: Not	applicable.
Auto-ignition temperature	: 450) to 600°C (842 to 1112°F)
Decomposition temperature	: Not	available.
Minimum ignition energy (mJ)	: 5 to	o 20
Viscosity		ematic (room temperature): Not applicable. [DIN EN ISO 3219] ematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]
Particle characteristics		
Median particle size	: Not	available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to	: No specific test data related to reactivity available for this product or its ingredients.		
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of sto	orage and use, hazardous reaction	ons will not occur.	
Conditions to avoid	(spark or flame). Take precau avoid fire or explosion, dissipa	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.		
Incompatible materials	: Reactive or incompatible with oxidizing materials	the following materials:		
Date of issue/Date of revision	: 12/13/2022	Version : 1		
Date of previous issue	: No previous validation	6/11	AkzoNobel	

Section 10. Stability and reactivity

Hazardous decomposition
products: Under normal conditions of storage and use, hazardous decomposition products should
not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral LD50 Oral		13700 mg/kg 14000 mg/kg	-
	LD50 Oral		14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision	: 12/13/2022	Version : 1	
Date of previous issue	: No previous validation	7/11	AkzoNobel

Section 11. Toxicological information

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
Date of issue/Date of revision	: 12/13/2022	Version : 1	
Date of previous issue	: No previous validation	8/11	AkzoNobe

Section 12. Ecological information

	0		
		dubia - Neonate	
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	<1	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Date of issue/Date of revisi	ion : 12/13/2022	Version : 1	
Date of previous issue	: No previous validation	9/11	AkzoNobel

Section 14. Transport information

Section 14. Transport information			
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations	: United States inventory	Not determined.
	(TSCA 8b):	

State regulations

Massachusetts	 The following components are listed: TITANIUM DIOXIDE; CALCIUM CARBONATE; KAOLIN DUST
New York	: None of the components are listed.
New Jersey	 The following components are listed: TITANIUM DIOXIDE; CALCIUM CARBONATE; KAOLIN
Pennsylvania	: The following components are listed: TITANIUM OXIDE; LIMESTONE; KAOLIN

California Prop. 65

WARNING: Cancer - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
titanium dioxide	-	-	Cancer
crystalline silica, respirable powder	-	-	Cancer
crystalline silica	-	-	Cancer

Inventory list

Canada

: All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS	On basis of test data
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

<u>History</u>

Date of printing

: 6 February 2023



Section 16. Other information

Date of issue/ Date of revision	: 13 December 2022
Date of previous issue	: No previous validation
Version	: 1
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

