

## **SAFETY DATA SHEET**

AN211QF 10-7011 INTERPON 100 BLACK

## **Section 1. Identification**

GHS product identifier SDS code

 : AN211QF 10-7011 INTERPON 100 BLACK
 : 8121660 AN211QF/20KG

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Industrial use	Industrial use		
	Uses advised against		
All other uses			
Product use	: Electrostatic coating for use in industrial plants		
Supplier's details			
Akzo Nobel Coatings 150 Columbia Street Reading, PA 19601 L			
1-610-372-3600			
Emergency telephone number (with hours of operation)	<ul> <li>CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)</li> <li>Domestic Poison Control Center Customer Service +1 (800) 854-6813</li> </ul>		
Section 2. Hazards	s identification		
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).		
Classification of the substance or mixture	: COMBUSTIBLE DUSTS CARCINOGENICITY - Category 1A		
<u>GHS label elements</u> Hazard pictograms	:		
Signal word	: Danger		
Hazard statements	: May cause cancer. May form combustible dust concentrations in air.		
Precautionary statements			
Prevention	: Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection.		
Response	: IF exposed or concerned: Get medical advice or attention.		
Storage	: Not applicable.		

## Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
earbon black, respirable powder	≤3	1333-86-4
Crystalline Silica as quartz not respirable,>10µm	≤0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	nmediately flush eyes with plenty of water, occasionally lifting the upper and lo velids. Check for and remove any contact lenses. Continue to rinse for at lea inutes. Get medical attention.	
Inhalation	emove victim to fresh air and keep at rest in a position comfortable for breath of breathing, if breathing is irregular or if respiratory arrest occurs, provide arti- espiration or oxygen by trained personnel. It may be dangerous to the person d to give mouth-to-mouth resuscitation. Get medical attention. If unconsciou recovery position and get medical attention immediately. Maintain an open a bosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation ecomposition products in a fire, symptoms may be delayed. The exposed per bed to be kept under medical surveillance for 48 hours.	ficial providing s, place irway. on of
Skin contact	ush contaminated skin with plenty of water. Remove contaminated clothing a noes. Wash contaminated clothing thoroughly with water before removing it, o oves. Continue to rinse for at least 10 minutes. Get medical attention. Wash efore reuse. Clean shoes thoroughly before reuse.	or wear
Ingestion	Ash out mouth with water. Remove dentures if any. If material has been swand the exposed person is conscious, give small quantities of water to drink. Supposed person feels sick as vomiting may be dangerous. Do not induce vominaless directed to do so by medical personnel. If vomiting occurs, the head shout performs that vomit does not enter the lungs. Get medical attention. Never gravity by mouth to an unconscious person. If unconscious, place in recovery and get medical attention immediately. Maintain an open airway. Loosen tight uch as a collar, tie, belt or waistband.	top if the ting ould be give y position

#### Most important symptoms/effects, acute and delayed

# Potential acute health effectsEye contact: Exposure to airborne concentrations above statutory or recommended exposure limits<br/>may cause irritation of the eyes.Inhalation: Exposure to airborne concentrations above statutory or recommended exposure limits<br/>may cause irritation of the nose, throat and lungs.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Date of previous issue	: 2/6/2023	2/11	AkzoNobel

## Section 4. First aid measures

#### Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li></ul>
Specific treatments	The exposed person may need to be kept under medical surveillance for 48 hours. <li>No specific treatment.</li>
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

#### Section 5. Fire-fighting measures **Extinguishing media** Suitable extinguishing : Use dry chemical powder. media Unsuitable extinguishing : Avoid high pressure media which could cause the formation of a potentially explosible media dust-air mixture. Specific hazards arising : May form explosible dust-air mixture if dispersed. from the chemical Hazardous thermal : Decomposition products may include the following materials: decomposition products carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. : Fire-fighters should wear appropriate protective equipment and self-contained breathing Special protective apparatus (SCBA) with a full face-piece operated in positive pressure mode. equipment for fire-fighters

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
--------------------------------	--

Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Date of previous issue	: 2/6/2023	3/11	AkzoNobel

## Section 6. Accidental release measures

For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for co	ntainment and cleaning up		
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.	
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.	

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Farbon black, respirable powder	ACGIH TLV (United States, 1/2022). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Refers to Appendix A Carcinogens. TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen See Appendix C - Supplemental Exposure Limits TWA: 3.5 mg/m <sup>3</sup> 10 hours. NIOSH REL (United States, 10/2020). Notes: Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs) See Appendix A - NIOSH Potential Occupational Carcinogen See Appendix C - Supplemental Exposure Limits TWA: 0.1 mg of PAHs/cm <sup>3</sup> 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m <sup>3</sup> 8 hours. OSHA PEL 1989 (United States, 3/1989).
Crystalline Silica as quartz not respirable,>10µm	<ul> <li>TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>OSHA PEL Z3 (United States, 6/2016).</li> <li>TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable</li> <li>TWA: 10 mg/m<sup>3</sup> / (%SiO2+2) 8 hours. Form: Respirable</li> <li>OSHA PEL (United States, 5/2018).</li> <li>TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>OSHA PEL 1989 (United States, 3/1989).</li> <li>Notes: as quartz</li> <li>TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hours. Form: Respirable dust</li> <li>ACGIH TLV (United States, 3/2018). Notes: Respirable fraction; see Appendix C, paragraph C.</li> <li>TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> <li>NIOSH REL (United States, 10/2016).</li> <li>Notes: See Appendix A - NIOSH Potential Occupational Carcinogen</li> <li>TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</li> </ul>

## Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.



## Section 8. Exposure controls/personal protection

	the second se
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use

# **Section 9. Physical and chemical properties and safety characteristics**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>			
Physical state	: Solid. [Powder.]		
Color	: Black.		
Odor	: Odorless.		
Odor threshold	: Not available.		
рН	: Not applicable. [DIN EN 1262]		
Melting point/freezing point	: Not available.		
Boiling point, initial boiling point, and boiling range	: Not available.		
Flash point	: Closed cup: Not applicable. [Pen	isky-Martens]	
Flammability	: Not available.		
Lower and upper explosion limit/flammability limit	: 20 - 70 g/m3		
Vapor pressure	: Not available.		
Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Date of previous issue	: 2/6/2023	6/11	AkzoNobel

# Section 9. Physical and chemical properties and safety characteristics

onaraotoriotioo			
Relative vapor density	: Not applicable.		
Relative density	: 1.2 to 1.9 [ISO 8130-2/-3]		
Solubility(ies)	:		
Media	Result		
cold water	Not soluble [OESO (TG 105)]		
Partition coefficient: n- octanol/water	: Not applicable.		
Auto-ignition temperature	: 450 to 600°C (842 to 1112°F)		
Decomposition temperature	: Not available.		
Minimum ignition energy (mJ)	: 5 to 20		
Viscosity	: Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]		
Particle characteristics			
Median particle size	: Not available.		
Section 10. Stabil	ity and reactivity		
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
Chemical stability	: The product is stable.		
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust		
	accumulation.		
Incompatible materials			

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
carbon black, respirable powder	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Date of previous issue	: 2/6/2023	7/11	AkzoNobel

## Section 11. Toxicological information

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
carbon black, respirable powder	-	2B	-
Crystalline Silica as quartz not respirable,>10µm	-	1	Known to be a human carcinogen.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

#### Information on the likely : Not available. routes of exposure

#### Potential acute health effects

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Date of previous issue	: 2/6/2023	8/11	AkzoNobel
Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Potential delayed effects	: Not available.		
Potential immediate effects	: Not available.		
<u>Long term exposure</u>			
Potential delayed effects	: Not available.		
Potential immediate effects	: Not available.		
<u>Short term exposure</u>			

## Section 11. Toxicological information

#### Potential chronic health effects

#### Not available.

General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

<u>Acute toxicity estimates</u> N/A

## Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
øarbon black, respirable powder	Acute EC50 37.563 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 61.547 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### <u>Mobility in soil</u>

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



## Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group Environmental hazards		- No.	- No.

# **Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

## Section 15. Regulatory information

-	
U.S. Federal regulations	: United States inventory Not determined. (TSCA 8b):
	<b>United States inventory (TSCA 8b):</b> This is a new product solely for research and development use. It contains chemicals which are not listed on the U.S. EPA TSCA Inventory and cannot be distributed by itself or as a part of another product for commercial purposes. It is to be used only by/ under the direct supervision of a technically qualified individual. This material's chemical, physical, and toxicological properties have not been fully investigated. Its handling or use may be hazardous. Caution must be exercised through the use of protective equipment and handling procedures to minimize exposure.
State regulations	
Massachusetts	: The following components are listed: BARIUM SULFATE; CARBON BLACK
New York	: None of the components are listed.
New Jersey	<ul> <li>The following components are listed: BARIUM SULFATE; CYANIDE compounds; CARBON BLACK</li> </ul>
Pennsylvania	<ul> <li>The following components are listed: BARIUM SULFATE; CYANIDE COMPOUNDS; CARBON BLACK</li> </ul>

#### California Prop. 65

**WARNING**: Cancer - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
zarbon black, respirable powder	-	-	Cancer
Crystalline Silica as quartz not respirable,>10µm	-	-	Cancer
styrene	Yes.	-	Cancer
Crystalline Silica, respirable part in whole product, <a></a>	-	-	Cancer
ethylbenzene	Yes.	-	Cancer

#### Inventory list

Date of issue/Date of revision	: 3/23/2023	Version : 2.01	
Date of previous issue	: 2/6/2023	10/11	AkzoNobel

## Section 15. Regulatory information

Canada

: Not determined.

### Section 16. Other information

#### Procedure used to derive the classification

	Classification	Justification	
COMBUSTIBLE DUSTS CARCINOGENICITY - Category 1A		On basis of test data Calculation method	
History			
Date of printing	: 23 March 2023		
Date of issue/ Date of revision	: 23 March 2023		
Date of previous issue	: 6 February 2023		
Version	: 2.01		
Unique ID	:		
Key to abbreviations			

IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Indicates information that has changed from previously issued version.

#### Notice to reader

#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

