

SAFETY DATA SHEET

QZ100Q INTERPON A4741 LOW GLOSS CLEAR

Section 1. Identification GHS product identifier : QZ100Q INTERPON A4741 LOW GLOSS CLEAR SDS code : 8145925 QZ100Q/20KG

Relevant identified uses of the substance or mixture and uses advised against

| | Identifie | d uses | |
|--|---|---|------------------------|
| Industrial use | | | |
| | Uses advis | ed against | |
| All other uses | | | |
| Product use | : Electrostatic coating for use | in industrial plants | |
| Supplier's details | | | |
| Akzo Nobel Coatii 150 Columbia Stro Reading, PA 1960 | eet | | |
| 1-610-372-3600 | | | |
| Emergency telephone number (with hours of operation) | accepted) | 9300 (Inside the US) +1 (703) 527-3887(Outside the enter Customer Service +1 (800 | |
| Section 2. Hazar | ds identification | | |
| OSHA/HCS status | : This material is considered (29 CFR 1910.1200). | hazardous by the OSHA Hazard | Communication Standard |
| Classification of the substance or mixture | : COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - C SERIOUS EYE DAMAGE - SKIN SENSITIZATION - Ca GERM CELL MUTAGENIC SPECIFIC TARGET ORGA | Category 1 tegory 1 | OSURE) - Category 2 |
| GHS label elements | | | |
| Hazard pictograms | | | |
| Signal word | : Danger | | |
| Hazard statements | : Harmful if swallowed. May cause an allergic skin r Causes serious eye damag May cause genetic defects. May cause damage to organ May form combustible dust | e. ns through prolonged or repeate | d exposure. |
| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 | |
| Date of previous issue | : 12/15/2022 | 1/11 | AkzoNobe |

Section 2. Hazards identification

| Precautionary statements | | |
|-------------------------------------|---|--|
| Prevention | : | Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. |
| Response | : | IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. |
| Storage | : | Not applicable. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | : | Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation. |
| Hazards not otherwise classified | : | None known. |
| | | |

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

| Ingredient name | % | CAS number |
|--|-----|------------|
| 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione | <10 | 2451-62-9 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| Description of necessary first | aid measures |
|--------------------------------|---|
| Eye contact | : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. |
| Inhalation | : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |



Section 4. First aid measures

| Ingestion | : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
|-----------|---|
| | |

Most important symptoms/effects, acute and delayed

| Most important symptoms/e | effects, acute and delayed |
|---------------------------------|---|
| Potential acute health effect | <u>cts</u> |
| Eye contact | : Causes serious eye damage. |
| Inhalation | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. |
| Skin contact | : May cause an allergic skin reaction. |
| Ingestion | : Harmful if swallowed. |
| <u>Over-exposure signs/symp</u> | <u>otoms</u> |
| Eye contact | : Adverse symptoms may include the following: pain watering redness |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | : Adverse symptoms may include the following: pain or irritation redness blistering may occur |
| Ingestion | : Adverse symptoms may include the following: stomach pains |
| Indication of immediate med | dical attention and special treatment needed, if necessary |
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use dry chemical powder. |
| Unsuitable extinguishing media | : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. |
| Specific hazards arising from the chemical | : May form explosible dust-air mixture if dispersed. |

| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 12/15/2022 | 3/11 | AkzoNobel |

Section 5. Fire-fighting measures

| | | 0 |
|---|---|---|
| Hazardous thermal decomposition products | | Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides |
| Special protective actions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
| | | |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

emergency personnel".

| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
|--------------------------------|---|
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- |

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

| Small spill | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. |
|-------------|--|
| Large spill | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| | history of skin sensitization this product is used. Aver handle until all safety pre- or on skin or clothing. De when handling and avoid accumulation. Use only ventilation is inadequate. made from a compatible equipment and lighting s coming into contact with precautionary measures | nal protective equipment (see Section 8). Persons with a on problems should not be employed in any process in which oid exposure - obtain special instructions before use. Do not cautions have been read and understood. Do not get in eyes o not breathe dust. Do not ingest. Avoid the creation of dust all possible sources of ignition (spark or flame). Prevent dust with adequate ventilation. Wear appropriate respirator when Keep in the original container or an approved alternative material, kept tightly closed when not in use. Electrical hould be protected to appropriate standards to prevent dust hot surfaces, sparks or other ignition sources. Take against electrostatic discharges. To avoid fire or explosion, during transfer by grounding and bonding containers and |
|--|--|---|
|--|--|---|

| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 |
|--------------------------------|--------------|----------------|
| Date of previous issue | : 12/15/2022 | 4/11 |



Section 7. Handling and storage

| | equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

:12/15/2022

Control parameters

Date of previous issue

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|--|
| 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione | ACGIH TLV (United States, 1/2022). [1,3,5-Triglycidyl-s-triazinetrione] TWA: 0.05 mg/m ³ 8 hours. |

| Appropriate engineering controls | or mist, use proce to keep worker e> limits. The engine | equate ventilation. If user operations generate dust, fumes, gas, vapor ess enclosures, local exhaust ventilation or other engineering controls (posure to airborne contaminants below any recommended or statutor eering controls also need to keep gas, vapor or dust concentrations explosive limits. Use explosion-proof ventilation equipment. |
|----------------------------------|--|--|
| Environmental exposure controls | they comply with cases, fume scru | entilation or work process equipment should be checked to ensure the requirements of environmental protection legislation. In some bbers, filters or engineering modifications to the process equipment to reduce emissions to acceptable levels. |
| Individual protection meas | ures | |
| Hygiene measures | eating, smoking a Appropriate techr Contaminated wo contaminated clo | earms and face thoroughly after handling chemical products, before and using the lavatory and at the end of the working period. hiques should be used to remove potentially contaminated clothing. ork clothing should not be allowed out of the workplace. Wash thing before reusing. Ensure that eyewash stations and safety e to the workstation location. |
| Eye/face protection | assessment indic gases or dusts. I the assessment in | omplying with an approved standard should be used when a risk ates this is necessary to avoid exposure to liquid splashes, mists, f contact is possible, the following protection should be worn, unless ndicates a higher degree of protection: chemical splash goggles and/ inhalation hazards exist, a full-face respirator may be required instead. |
| Skin protection | | |
| Hand protection | worn at all times v necessary. Cons during use that th noted that the tim glove manufactur | nt, impervious gloves complying with an approved standard should be when handling chemical products if a risk assessment indicates this is idering the parameters specified by the glove manufacturer, check e gloves are still retaining their protective properties. It should be e to breakthrough for any glove material may be different for different ers. In the case of mixtures, consisting of several substances, the the gloves cannot be accurately estimated. |
| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 |

5/11

AkzoNobel

Section 8. Exposure controls/personal protection

| protective equipment for the body should be selected based on the task being d and the risks involved and should be approved by a specialist before this product. ate footwear and any additional skin protection measures should be selected the task being performed and the risks involved and should be approved by a before handling this product. |
|--|
| the task being performed and the risks involved and should be approved by a |
| |
| the hazard and potential for exposure, select a respirator that meets the te standard or certification. Respirators must be used according to a y protection program to ensure proper fitting, training, and other important of use. |
| |

characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

| Physical state | : Solid. [Powder.] |
|---|--|
| Color | : 🖉 olorless. |
| Odor | : Odorless. |
| Odor threshold | : Not available. |
| рН | : Not applicable. [DIN EN 1262] |
| Melting point/freezing point | : Not available. |
| Boiling point, initial boiling point, and boiling range | : Not available. |
| Flash point | : Closed cup: Not applicable. [Pensky-Martens] |
| Flammability | : Not available. |
| Lower and upper explosion limit/flammability limit | : 20 - 70 g/m3 |
| Vapor pressure | : Not available. |
| Relative vapor density | : Not applicable. |
| Relative density | : 1.2 to 1.9 [ISO 8130-2/-3] |
| Solubility(ies) | : |
| | |

| | Media | | Result |
|----|---|--------|--|
| | cold water | | Not soluble [OESO (TG 105)] |
| | artition coefficient: n- ctanol/water | : No | t applicable. |
| Α | uto-ignition temperature | : 450 | 0 to 600°C (842 to 1112°F) |
| D | ecomposition temperature | : No | t available. |
| | inimum ignition energy nJ) | : 5 to | o 20 |
| Vi | scosity | | nematic (room temperature): Not applicable. [DIN EN ISO 3219] nematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219] |
| | article characteristics ledian particle size | : No | t available. |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|---------|-----------------------|----------|
| 1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione | LC50 Inhalation Dusts and mists | Mouse | 2000 mg/m³ | 4 hours |
| , | LC50 Inhalation Dusts and mists | Rat | 650 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 188 mg/kg | - |
| | LD50 Oral | Rat | 222 mg/kg | - |
| | LD50 Oral | Rat | 138 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|------------------------|---------|-------|----------|-------------|
| 1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione | Eyes - Severe irritant | Rabbit | - | 100 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 12/15/2022 | 7/11 | AkzoNobel |

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs |
|--|------------|-------------------|---------------|
| 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione | Category 2 | - | - |

Aspiration hazard

Not available.

| Information on the likely | : Not available. |
|---------------------------|------------------|
|---------------------------|------------------|

routes of exposure

Potential acute health effects

- Eye contact : Causes serious eye damage. Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact : May cause an allergic skin reaction.
- Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | : Adverse symptoms may include the following: pain watering redness |
|--------------|--|
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | : Adverse symptoms may include the following: pain or irritation redness blistering may occur |
| Ingestion | : Adverse symptoms may include the following: stomach pains |

Delayed and immediate effects and also chronic effects from short and long term exposure

| Short term exposure | |
|--------------------------------|---|
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health eff | ects |
| Not available. | |
| General | : May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : May cause genetic defects. |
| Reproductive toxicity | : No known significant effects or critical hazards. |
| | |

Numerical measures of toxicity

Acute toxicity estimates

| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 12/15/2022 | 8/11 | AkzoNobel |

Section 11. Toxicological information

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/ I) |
|---|------------------|-------------------|--------------------------------|----------------------------------|---|
| 5/QZ100Q/USA INT A4741 LOW GLOSS CLR/74 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H, 5H)-trione | 1313.8 100 | N/A N/A | N/A N/A | N/A N/A | 6.6 0.5 |

Section 12. Ecological information

<u>Toxicity</u>

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|-----|-----------|
| 1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione | -0.8 | - | low |

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

| Dianasal mathada | . The generation of waste should be availed as minimized wherever passible. Dispessel |
|------------------|--|
| Disposal methods | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains |
| | and sewers. |

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.



Section 14. Transport information

| | DOT Classification | IMDG | IATA |
|-------------------------------|--------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

| Section 15. Regu | latory information | | |
|--------------------------|---|--|--|
| U.S. Federal regulations | : United States inventory (TSCA 8b): | All components are active or exempted. | |

| State regulations | |
|----------------------------|---|
| Massachusetts | : None of the components are listed. |
| New York | : None of the components are listed. |
| New Jersey | : The following components are listed: 1,3,5-TRIGLYCIDYL-s-TRIAZINETRIONE |
| Pennsylvania | : None of the components are listed. |
| <u>California Prop. 65</u> | |

Inventory list

Canada

: At least one component is not listed.

Section 16. Other information

Procedure used to derive the classification

| Classification | Justification |
|---|---|
| COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 | On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method |
| <u>History</u> | |
| Date of printing : 7 February 2023 | |

| Date of issue/Date of revision | : 2/7/2023 | Version : 1.02 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 12/15/2022 | 10/11 | AkzoNobel |

Section 16. Other information

| Date of issue/ Date of revision | : 7 February 2023 |
|---------------------------------|--|
| Date of previous issue | : 15 December 2022 |
| Version | : 1.02 |
| Unique ID | : |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations |

✓ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

