

SAFETY DATA SHEET

JF070QF INT 600 RAL 2012 SALMON ORANGE U1578-1

Section 1. Identification **GHS** product identifier : JF070QF INT 600 RAL 2012 SALMON ORANGE U1578-1 SDS code : 8208548 JF070QF/25KG Relevant identified uses of the substance or mixture and uses advised against Identified uses Industrial use Uses advised against All other uses Product use : Electrostatic coating for use in industrial plants Supplier's details Akzo Nobel Coatings Inc. 150 Columbia Street Reading, PA 19601 USA 1-610-372-3600 **Emergency telephone** : CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls number (with hours of accepted) operation) Domestic Poison Control Center Customer Service +1 (800) 854-6813 Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Classification of the** : COMBUSTIBLE DUSTS substance or mixture ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 **GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2** SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 **GHS** label elements Hazard pictograms 2 Signal word : Danger

: 2/7/2023 : 12/15/2022



Section 2. Hazards identification

Hazard statements	 Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. May cause genetic defects. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May form combustible dust concentrations in air.
Precautionary statements	
Prevention	: Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
titanium dioxide	≥10 - ≤25	13463-67-7
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	≤8.5	2451-62-9
propylidynetrimethanol	≤0.3	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures			
Eye contact	eyes with plenty of wate	nmediately. Call a poison center or p er, occasionally lifting the upper and k ses. Continue to rinse for at least 10 tly by a physician.	ower eyelids. Check for and
Inhalation	fresh air and keep at re fumes are still present, breathing apparatus. If occurs, provide artificia dangerous to the perso unconscious, place in re an open airway. Loose inhalation of decompos	nmediately. Call a poison center or p st in a position comfortable for breath the rescuer should wear an appropria not breathing, if breathing is irregular l respiration or oxygen by trained person providing aid to give mouth-to-mout ecovery position and get medical attent n tight clothing such as a collar, tie, b ition products in a fire, symptoms makept under medical surveillance for 4	ing. If it is suspected that ate mask or self-contained r or if respiratory arrest sonnel. It may be th resuscitation. If ntion immediately. Maintain elt or waistband. In case of y be delayed. The exposed
Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	2/12	AkzoNobel

Section 4. First aid measures

Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	3/12	AkzoNo



Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

-	_
Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	<u>tive e</u>	quipment and emergency procedu	res	
For non-emergency personnel	Ev en No ve	o action shall be taken involving any p vacuate surrounding areas. Keep unn itering. Do not touch or walk through o flares, smoking or flames in hazard intilation. Wear appropriate respirator opropriate personal protective equipme	ecessary and unprotect spilled material. Shut o area. Do not breathe du when ventilation is inac	ed personnel from ff all ignition sources. ust. Provide adequate
For emergency responders	Se	specialized clothing is required to dea ection 8 on suitable and unsuitable ma nergency personnel".		
Environmental precautions	an	void dispersal of spilled material and ro nd sewers. Inform the relevant authori ollution (sewers, waterways, soil or air)	ities if the product has c	
Methods and materials for co	ntain	<u>ment and cleaning up</u>		
Small spill	Av HE de	ove containers from spill area. Use sp void dust generation. Do not dry swee EPA filter and place in a closed, labele ssignated, labeled waste container. D ontractor.	p. Vacuum dust with e ed waste container. Pla	quipment fitted with a ce spilled material in a
Large spill	Ap or eq Av wa	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		
Date of issue/Date of revision	::	2/7/2023	Version : 1.01	
Date of previous issue	:	12/15/2022	4/12	AkzoNobel

Section 7. Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
titanium dioxide	OSHA PEL (United States, 5/2018).	
	TWA: 15 mg/m ³ 8 hours. Form: Total dust	
	OSHA PEL 1989 (United States, 3/1989).	
	TWA: 10 mg/m ³ 8 hours. Form: Total dust	
	ACGIH TLV (United States, 1/2022).	
	TWA: 2.5 mg/m ³ 8 hours. Form: respirable	
	fraction, finescale particles	
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	ACGIH TLV (United States, 1/2022).	
	[1,3,5-Triglycidyl-s-triazinetrione]	
	TWA: 0.05 mg/m ³ 8 hours.	
propylidynetrimethanol	None.	

Appropriate engineering controls	or mist, use process er to keep worker exposu limits. The engineering	e ventilation. If user operations general inclosures, local exhaust ventilation or o re to airborne contaminants below any g controls also need to keep gas, vapo ive limits. Use explosion-proof ventila	other engineering controls recommended or statutory r or dust concentrations
Environmental exposure controls	 Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. 		
Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	5/12	AkzoNobel

Section 8. Exposure controls/personal protection

	the second se
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>

Physical state	:	Solid. [Powder.]
Color	:	Orange.
Odor	:	Odorless.
Odor threshold	:	Not available.
рН	:	Not applicable. [DIN EN 1262]
Melting point/freezing point	:	Not available.
Boiling point, initial boiling	:	Not available.
point, and boiling range		
Flash point	:	Closed cup: Not applicable. [Pensky-Martens]
Flash point Flammability		Closed cup: Not applicable. [Pensky-Martens] Not available.
	:	
Flammability	:	Not available.
Flammability Lower and upper explosion	:	Not available.
Flammability Lower and upper explosion limit/flammability limit	:	Not available. 20 - 70 g/m3
Flammability Lower and upper explosion limit/flammability limit Vapor pressure	::	Not available. 20 - 70 g/m3 Not available.
Flammability Lower and upper explosion limit/flammability limit Vapor pressure Relative vapor density	::	Not available. 20 - 70 g/m3 Not available. Not applicable.

Section 9. Physical and chemical properties and safety characteristics

Media		Result		
cold water	Not soluble [OESO (TG 105)]			
Partition coefficient: n- octanol/water	: Not applicable.			
Auto-ignition temperature	: 450	to 600°C (842 to 1112°F)		
Decomposition temperature	e : Not available.			
Minimum ignition energy (mJ)	: 5 to 20			
Viscosity	 Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219] 			
Particle characteristics				
Median particle size	: Not	available.		
Section 10. Stabili	ty ar	nd reactivity		

Reactivity : No specific test data related to reactivity available for this product or its ingredients. **Chemical stability** : The product is stable. Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur. reactions Conditions to avoid : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation. Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products should products not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	LC50 Inhalation Dusts and mists	Mouse	2000 mg/m ³	4 hours
,	LC50 Inhalation Dusts and mists	Rat	650 mg/m³	4 hours
	LD50 Oral	Rat	188 mg/kg	-
	LD50 Oral	Rat	222 mg/kg	-
	LD50 Oral	Rat	138 mg/kg	-
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	7/12	AkzoNobel

Section 11. Toxicological information

	0				
Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	Eyes - Severe irritant	Rabbit	-	100 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione	Category 2	-	-

Aspiration hazard

Not available.

Information on the likely	: Not available.
routes of exposure	

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	8/12	AkzoNobel

Section 11. Toxicological information

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: May cause genetic defects.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
₱5/JF070QF/USA RAL2012 ORANGE U1578-1/BA 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	1657.7 100	N/A N/A	N/A N/A	N/A N/A	8.3 0.5

Section 12. Ecological information

Toxicity



Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H,	-0.8	-	low
5H)-trione propylidynetrimethanol	-0.47	<1	low

<u>Mobility in soil</u>

Soil/water partition : Not coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group		-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations : United States inventory All components (TSCA 8b):

All components are active or exempted.

State regulations

Massachusetts	: The following components are listed: TITANIUM DIOXIDE; BARIUM SULFATE
New York	: None of the components are listed.
New Jersey	: The following components are listed: TITANIUM DIOXIDE; 1,3,5-TRIGLYCIDYL-s- TRIAZINETRIONE; BARIUM SULFATE

Pennsylvania

: The following components are listed: TITANIUM OXIDE; BARIUM SULFATE

California Prop. 65

WARNING: Cancer - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
titanium dioxide	-	-	Cancer
crystalline silica	-	-	Cancer
crystalline silica, respirable powder	-	-	Cancer

Inventory list

Canada

: At least one component is not listed.

Date of issue/Date of revision	: 2/7/2023	Version : 1.01	
Date of previous issue	: 12/15/2022	11/12	AkzoNobel

Section 16. Other information

Procedure used to derive the classification

	Classification	Justification
		On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method
SPECIFIC TARGET ORGAN TO	DXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
<u>History</u>		
Date of printing	: 7 February 2023	
Date of issue/ Date of revision	: 7 February 2023	
Date of previous issue	: 15 December 2022	
Version	: 1.01	
Unique ID	:	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	

✓ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

