

# SAFETY DATA SHEET

FL635F/25KG Interpon 700 GREY 7035 Gloss

# **SECTION 1: Identification of the substance/mixture and of the company/** undertaking

Product name
SDS code

: FL635F/25KG Interpon 700 GREY 7035 Gloss : 8000938

FL635F/25KG

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Industrial use		
	Uses advised against	
All other uses		

Product use

: Electrostatic coating for use in industrial plants

# 1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. NE10 0JY United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS <u>National contact</u> 01 8092566 or 01 8379964 1.4 Emergency telephone number National advisory body/Poison Centre

Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111
Hours of operation	:

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Product definition : Mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	1/14	AkzoNobel

# **SECTION 2: Hazards identification**

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Safety data sheet available on request. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requiren	nen	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form combustible dust concentrations in air.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤15	Carc. 2, H351 (inhalation)	-	[1] [*]
2-ethyl-N,N-bis (2-ethylhexyl)hexylamine	EC: 217-461-0 CAS: 1860-26-0	≤0.3	Repr. 2, H361 STOT RE 2, H373 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	2/14	AkzoNobel

FL635F/25KG Interpon 700 GREY 7035 Gloss

# **SECTION 3: Composition/information on ingredients**

Substance classified with a health or environmental hazard

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

### **Over-exposure signs/symptoms**

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	3/14	AkzoNobel

# **SECTION 5: Firefighting measures**

0		0
5.2 Special hazards arising f	ron	n the substance or mixture
Hazards from the substance or mixture	:	May form explosible dust-air mixture if dispersed.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### **Occupational exposure limits**

Product/ingredie	nt name	Exposure limit values				
Manium dioxide		<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable TWA: 10 mg/m <sup>3</sup> 8 hours. Form: total inhalable				
Recommended monitoring procedures	atmosphere or b of the ventilation protective equip the following: E the assessment limit values and atmospheres - 0 of exposure to o (Workplace atm for the measure	n or other control measures and ment. Reference should be ma uropean Standard EN 689 (Wor of exposure by inhalation to che measurement strategy) Europe Guide for the application and use chemical and biological agents) nospheres - General requiremen ment of chemical agents) Refe	uired to determine the effectiveness for the necessity to use respiratory de to monitoring standards, such as kplace atmospheres - Guidance for emical agents for comparison with ean Standard EN 14042 (Workplace e of procedures for the assessment European Standard EN 482 ts for the performance of procedures			
Date of issue/Date of revision	: 18-5-2023	Version	: 3.01			
Date of previous issue	: 20-2-2023	5/14	AkzoNobel			

# **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-ethyl-N,N-bis(2-ethylhexyl) hexylamine	DNEL	Long term Oral	0.03 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.06 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.07 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.13 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.23 mg/m <sup>3</sup>	Workers	Systemic

# PNECs

No PNECs available

8.2 Exposure controls				
Appropriate engineering controls		vapour or mist, use process engineering controls to keep recommended or statutory li	tilation. If user operations ger enclosures, local exhaust ver worker exposure to airborne mits. The engineering contro ns below any lower explosive l	ntilation or other contaminants below any is also need to keep gas,
Individual protection measu	ires			
Hygiene measures		before eating, smoking and Appropriate techniques sho	face thoroughly after handling using the lavatory and at the e uld be used to remove potenti g before reusing. Ensure that the workstation location.	end of the working period. ally contaminated clothing.
Eye/face protection		assessment indicates this is gases or dusts. If contact is unless the assessment indic	vith an approved standard sho necessary to avoid exposure possible, the following protec cates a higher degree of prote inditions cause high dust conc	to liquid splashes, mists, tion should be worn, ction: safety glasses with
Skin protection				
Hand protection			ous gloves complying with an a andling chemical products if a	
		time >30 minutes according Nitrile, thickness ≥ 0.12 mm	glove with protection class of to EN374) is recommended. regularly and if there is any sig	Recommended gloves:
		The performance or effectiv chemical damage and poor	eness of the glove may be rec maintenance.	luced by physical/
			e final choice of type of glove ate and takes into account the s risk assessment.	
Body protection			ent for the body should be sele ks involved and should be app	
		protective clothing to ensure	ective clothing. Care should be that inflammation and irritation vith the powder are avoided.	
Date of issue/Date of revision		: 18-5-2023	Version : 3.01	
Date of previous issue		: 20-2-2023	6/14	AkzoNobel

# **SECTION 8: Exposure controls/personal protection**

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

# 9.1 Information on basic physical and chemical properties

Media		Result
Solubility(ies)	:	
Viscosity		Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
рН		Not applicable. [DIN EN 1262]
Decomposition temperature	-	Not available.
Auto-ignition temperature	:	450 to 600°C (842 to 1112°F)
Flash point	:	Closed cup: Not applicable. [Pensky-Martens]
Lower and upper explosion limit	:	20 - 70 g/m3
Flammability	-	Not available.
Initial boiling point and boiling range	:	Not available.
Melting point/freezing point	:	Not available.
Odour threshold	:	Not available.
Odour	:	Odourless.
Colour	:	Grey.
Physical state	:	Solid. [Powder.]
<u>Appearance</u>		

INIEUIA		Result			
cold water		Not soluble [OESO (TG 105)]			
Partition coefficient: n-octanol/ water	/:	Not applicable.			
Vapour pressure	: 1	Not available.			
Relative density	: '	1.2 to 1.9 [ISO 8130-2/-3]			
Vapour density	: 1	Not applicable.			
Particle characteristics					
Median particle size	: 1	Not available.			
Percentage of particles with aerodynamic diameter ≤ 10 μm	: (	<b>7</b>			
.2 Other information					
Minimum ignition energy (mJ)	: {	5 to 20			
ate of issue/Date of revision	:18-	-5-2023	Version	: 3.01	
ate of previous issue	:20-	-2-2023	7/14		AkzoNobel

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.		
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

# **SECTION 11: Toxicological information**

11.1 Information on hazard	classes as defined in Regulation (EC) No 1272/2008			
Acute toxicity				
<b>Conclusion/Summary</b>	: Not available.			
Acute toxicity estimates				
N/A				
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
Sensitisation				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
<b>Carcinogenicity</b>				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<b>Teratogenicity</b>				
Conclusion/Summary	: Not available.			

Specific target organ toxicity (single exposure)

Not available.

# Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-ethyl-N,N-bis(2-ethylhexyl)hexylamine	Category 2	-	-

# Aspiration hazard

Not available.

Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	8/14	AkzoNobel

# **SECTION 11: Toxicological information**

SECTION 11: Toxicological information				
Information on likely routes of exposure	available.			
Potential acute health effects				
Eye contact	osure to airborne concentrations above statutory s may cause irritation of the eyes.	or recommended exposure		
Inhalation	osure to airborne concentrations above statutory s may cause irritation of the nose, throat and lung			
Skin contact	nown significant effects or critical hazards.			
Ingestion	nown significant effects or critical hazards.			
	nemical and toxicological characteristics			
Eye contact	erse symptoms may include the following: tion ess			
Inhalation	erse symptoms may include the following: iratory tract irritation jhing			
Skin contact	pecific data.			
Ingestion	pecific data.			
Delayed and immediate offer	ll as abranic offects from about and long town			
Short term exposure	ell as chronic effects from short and long-terr	<u>Texposure</u>		
Potential immediate effects	available.			
Potential delayed effects	available.			
Long term exposure				
Potential immediate effects	available.			
Potential delayed effects	available.			
Potential chronic health effe				
Not available.				
Conclusion/Summary	available.			
General	eated or prolonged inhalation of dust may lead to	chronic respiratory irritation.		
Carcinogenicity	nown significant effects or critical hazards.			
Mutagenicity	nown significant effects or critical hazards.			
Reproductive toxicity	nown significant effects or critical hazards.			

# 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

No additional information.



FL635F/25KG Interpon 700 GREY 7035 Gloss

# **SECTION 12: Ecological information**

## 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
<b>ti</b> tanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-ethyl-N,N-bis(2-ethylhexyl) hexylamine	10.131	-	high

## 12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	10/14	AkzoNobel

# **SECTION 12: Ecological information**

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 02 01	waste coating powders	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.	
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
Date of issue/Date of revi Date of previous issue	ision : 18-5-2023 : 20-2-2023	Version : 3.0 11/14	AkzoNobel

# **SECTION 14: Transport information**

14.5	No.	No.	No.
Environmental hazards			

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# 14.7 Maritime transport in: Not applicable.bulk according to IMOinstruments

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# UK (GB) /REACH

### Annex XIV - List of substances subject to authorisation

### Annex XIV

None of the components are listed.

### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.			
Other EU regulations				
VOC	: Not applicable.			
VOC for Ready-for-Use Mixture	: Not applicable.			
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Ozone depleting substances (1005/2009/EU) Not listed.				
Prior Informed Consent (PIC) (649/2012/EU) Not listed.				
Persistent Organic Pollutants				

Not listed.

# Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations



FL635F/25KG Interpon 700 GREY 7035 Gloss

SECTION 15: Regulatory information			
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.		
International regulations	<u>S</u>		
Chemical Weapon Conv	rention List Schedules I, II & III Chemicals		
Not listed.			
Montreal Protocol			
Not listed.			
Stockholm Convention	on Persistent Organic Pollutants		
Rotterdam Convention	on Prior Informed Consent (PIC)		
Not listed.			
UNECE Aarhus Protoco	I on POPs and Heavy Metals		
Not listed.			
15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried out.		
SECTION 16: Othe	er information		
Indicates information the second s	nat has changed from previously issued version.		
Abbroviations and	• ATE - Acute Taxicity Estimate		

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
2	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

# Full text of abbreviated H statements

H351

Date of previous issue

Suspected of causing cancer.

# Full text of classifications [CLP/GHS]

🖉arc. 2		CARCINOGENICITY - Category 2	
Date of printing	: 19 May 2023		
Date of issue/ Date of revision	: 18 May 2023		
Date of previous issue	: 20 February 20	023	
Version	: 3.01		
Unique ID	:		
Date of issue/Date of revision	: 18-5-2023	Version : 3.01	
Date of previous issue	: 20-2-2023	13/14	AkzoNobel

FL635F/25KG Interpon 700 GREY 7035 Gloss

# **SECTION 16: Other information**

## Notice to reader

### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

