

SAFETY DATA SHEET

EL180E/25KG RAL 7035 Hybrid

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: EL180E/25KG RAL 7035 Hybrid
SDS code	: 8007212
	EL180E/25KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Industrial use			
Uses advised against			
All other uses			
Product use : Electrostatic coating for use in industrial plants			

1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane,
Felling,
Gateshead.
NE10 0JY
United Kingdom
e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS
National contact
01 8092566 or 01 8379964
1.4 Emergency telephone number
National advisory body/Poison Centre

Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111
Hours of operation	:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

1.4

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	1/15	AkzoNobel

SECTION 2: Hazards identification

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Hazardous ingredients	:	benzene-1,2,4-tricarboxylic acid 1,2-anhydride
Supplemental label elements	:	Contains benzene-1,2,4-tricarboxylic acid 1,2-anhydride. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirements		<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form combustible dust concentrations in air. May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
tranium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥20 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	EC: 209-008-0 CAS: 552-30-7 Index: 607-097-00-4	<1	Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full text of the H statements declared above.	-	[1] [2]

Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	2/15	AkzoNobel

EL180E/25KG RAL 7035 Hybrid

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

Substance classified with a health or environmental hazard

[2] Substance of equivalent concern

The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for If not breathing, if breathing is irregular or if respiratory arrest occurs, pra artificial respiration or oxygen by trained personnel. It may be dangerou person providing aid to give mouth-to-mouth resuscitation. Get medical adverse health effects persist or are severe. If unconscious, place in re position and get medical attention immediately. Maintain an open airwat tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains benzene-1,2,4-tricarboxylic acid 1,2-anhydride. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may irritation redness	include the following:	
Inhalation	: Adverse symptoms may respiratory tract irritation coughing		
Skin contact	: No specific data.		
Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	3/15	AkzoNobel

EL180E/25KG RAL 7035 Hybrid

SECTION 4: First aid	measures				
Ingestion	: No specific data.				
4.3 Indication of any immedia	4.3 Indication of any immediate medical attention and special treatment needed				
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large				
Specific treatments	quantities have been ingested or inhaled.No specific treatment.				
SECTION 5: Firefight					
5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical powder.				
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.				
5.2 Special hazards arising fi	rom the substance or mixture				
Hazards from the substance or mixture	: May form explosible dust-air mixture if dispersed.				
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides				
5.3 Advice for firefighters					
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.				
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.				
SECTION 6: Acciden	tal release measures				
6.1 Personal precautions, pre	otective equipment and emergency procedures				
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				

- **For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- **6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	4/15	AkzoNobel

SECTION 6: Accidental release measures

Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)Recommendations: Not available.Industrial sector specific: Not available.solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits



SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
titanium dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 4 mg/m ³ 8 hours. Form: respirable
	TWA: 10 mg/m ³ 8 hours. Form: total inhalable
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser.
	STEL: 0.12 mg/m ³ 15 minutes.
	TWA: 0.04 mg/m ³ 8 hours.

procedures in this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	DNEL	Long term Oral	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4.4 mg/m ³	General population	Systemic
	DNEL	Short term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	8.8 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	17.5 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	35 mg/m³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering	: Use only with adequate ventilation. If user operations generate dust, fumes, gas,
controls	vapour or mist, use process enclosures, local exhaust ventilation or other
	engineering controls to keep worker exposure to airborne contaminants below any
	recommended or statutory limits. The engineering controls also need to keep gas,
	vapour or dust concentrations below any lower explosive limits. Use explosion-
	proof ventilation equipment

Individual protection measures

Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	6/15	AkzoNobel

SECTION 8: Exposur	e controls/personal protection
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Date of previous issue	: 30-1-2023	7/15	AkzoNobel
Date of issue/Date of revision	: 5-9-2023	Version : 2	
Flammability	: Not available.		
Melting point/freezing point	: Not available.		
Odour threshold	: Not available.		
Odour	: Odourless.		
Colour	: Grey.		
Physical state	: Solid. [Powder.]		
<u>Appearance</u>			

SECTION 9: Physical ar	nd	chemical properties
Lower and upper explosion limit	:	20 - 70 g/m3
Auto-ignition temperature	:	450 to 600°C (842 to 1112°F)
Decomposition temperature	:	Not available.
рН	:	Not applicable. [DIN EN 1262]
Viscosity	:	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
Solubility(ies)	:	
Media		Result
cold water		Not soluble [OESO (TG 105)]
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	:	Not available.
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]
Vapour density	:	Not applicable.
Particle characteristics		
Median particle size	:	Not available.
Percentage of particles with aerodynamic diameter ≤ 10 μm	:	

9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	LD50 Oral	Mouse	1900 mg/kg	-
	LD50 Oral	Rabbit	5600 mg/kg	-
Conclusion/Summary	: Not available.			
Acute toxicity estimates				
N/A				
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
<u>Sensitisation</u>				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
<u>Carcinogenicity</u>				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<u>Teratogenicity</u>				
Conclusion/Summary	: Not available.			
Specific target organ toxicity	<u>′ (single exposure)</u>			

Product/ingredient name Category Route of exposure Target organs benzene-1,2,4-tricarboxylic acid 1,2-anhydride Category 3 Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following:
	irritation
	redness

EL180E/25KG RAL 7035 Hybrid

SECTION 11: Toxico	SECTION 11: Toxicological information			
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing			
Skin contact	: No specific data.			
Ingestion	: No specific data.			
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure			
<u>Short term exposure</u>				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Long term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health eff	Potential chronic health effects			
Not available.				
Conclusion/Summary	: Not available.			
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.			
Carcinogenicity	: No known significant effects or critical hazards.			
Mutagenicity	: No known significant effects or critical hazards.			
Reproductive toxicity	: No known significant effects or critical hazards.			
-	-			

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	10/15	AkzoNobel

SECTION 12: Ecological information

	dubia - Neonate	
Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex -	48 hours
Ŭ	Neonate	
Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex -	48 hours
	Neonate	
Acute LC50 >1000000 µg/l Marine	Fish - Fundulus heteroclitus	96 hours
water		
Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
enzene-1,2,4-tricarboxylic acid 1,2-anhydride	0.06	-	low

1:	2.4	Мо	bility	'n	soil	
----	-----	----	--------	----	------	--

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>			
Methods of disposal	Disposal of this produc with the requirements any regional local auth products via a licensed	te should be avoided or minimised wh ct, solutions and any by-products shou of environmental protection and waste pority requirements. Dispose of surplu- d waste disposal contractor. Waste sh unless fully compliant with the require	Id at all times comply e disposal legislation and s and non-recyclable nould not be disposed of
Hazardous waste		owledge of the supplier, this product is lefined by EU Directive 2008/98/EC.	not regarded as
Disposal considerations	If this product is mixed longer apply and the a	Irains or watercourses. to all federal, state and local applicable I with other wastes, the original waste ppropriate code should be assigned. I, contact your local waste authority.	
Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	11/15	AkzoNobel

SECTION 13: Disposal considerations

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation		
EWC 08 02 01	waste coating powders		
Packaging			
Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.			
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. 		
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

Section 14. Transport information

	ADR/RID IMDG IATA				
14.1 UN number	Not regulated.	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	-	-		
14.3 Transport hazard class(es)	-	-	-		
14.4 Packing group	-	-	-		
14.5 Environmental hazards	No.	No.	No.		

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Date of issue/Date of revision	: 5-9-2023
Date of previous issue	: 30-1-2023



EL180E/25KG RAL 7035 Hybrid

SECTION 15: Regulatory information

Intrinsic property	Ingredient name			Date of revision
Substance of equivalent concern for human health	benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Candidate	ED/61/2018	6/27/2018
Endocrine disrupting properties for human health	benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Recommended	ED/71/2019	4/14/2021

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market

and use of certain dangerous substances, mixturos and articlos

mixtures and articles		
Other EU regulations		
VOC	:	Not applicable.
VOC for Ready-for-Use Mixture	:	Not applicable.
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Industrial emissions (integrated pollution	:	Not listed

prevention and control) -Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.



SECTION 15: Regulatory information

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

₩317 H318 H334	May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Full text of classifications [CLP/GHS]

Øarc. 2 Eye Dam. 1 Resp. Sens. 1 Skin Sens. 1 STOT SE 3		CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 RESPIRATORY SENSITISATION - Category 1 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 5-9-2023	

Date of issue/ Date of revision	: 5-9-2023
Date of previous issue	: 30-1-2023
Version	: 2
Unique ID	:

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are

Date of issue/Date of revision	: 5-9-2023	Version : 2	
Date of previous issue	: 30-1-2023	14/15	AkzoNobel

EL180E/25KG RAL 7035 Hybrid

SECTION 16: Other information

subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

