

# SAFETY DATA SHEET

SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### **1.1 Product identifier**

Product	name
SDS cod	e

 SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN
 8010104 SL181E/25KG

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Industrial use		
Uses advised against		
All other uses		
Broductuco	<ul> <li>Electroatatic conting for use in industrial planta</li> </ul>	

Product use

: Electrostatic coating for use in industrial plants

### 1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. NE10 0JY United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS <u>National contact</u> 01 8092566 or 01 8379964 1.4 Emergency telephone number <u>National advisory body/Poison Centre</u> Telephone number : ±44 (0)344 892 0111

l elephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111
Hours of operation	:

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	1/13	AkzoNobel

SECTION 2: Hazards identification				
2.2 Label elements	2.2 Label elements			
Signal word	:	No signal word.		
Hazard statements	:	No known significant effects or critical hazards.		
Precautionary statements				
Prevention	:	Not applicable.		
Response	:	Not applicable.		
Storage	:	Not applicable.		
Disposal	:	Not applicable.		
Supplemental label elements	:	Safety data sheet available on request. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.		
Special packaging requirem	en	<u>its</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.		
Tactile warning of danger	:	Not applicable.		
2.3 Other hazards				
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do not result in classification	:	May form combustible dust concentrations in air.		

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

: Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact		with plenty of water, occasionally liftin I remove any contact lenses. Get med	
Inhalation	Get medical attention in	n air and keep at rest in a position com f symptoms occur. In case of inhalatic otoms may be delayed. The exposed   rveillance for 48 hours.	on of decomposition
Skin contact		in with plenty of water. Remove conta tention if symptoms occur.	minated clothing and
Ingestion	person is conscious, gi	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.	
Protection of first-aiders	: No action shall be take	n involving any personal risk or withou	t suitable training.
Date of issue/Date of revision	: 14-4-2023	Version : 3	a. a a
Date of previous issue	: 30-1-2023	2/13	AkzoNobel

## **SECTION 4: First aid measures**

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

### **Over-exposure signs/symptoms**

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media				
Suitable extinguishing media	:	Use dry chemical powder		
Unsuitable extinguishing media	:	Avoid high pressure medi explosible dust-air mixture	a which could cause the formatic e.	on of a potentially
5.2 Special hazards arising fr	on	the substance or mixtu	re	
Hazards from the substance or mixture	:	May form explosible dust-	air mixture if dispersed.	
Hazardous combustion products	:	Decomposition products r carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides	nay include the following materia	ls:
5.3 Advice for firefighters				
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.		
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		
Date of issue/Date of revision		: 14-4-2023	Version : 3	
Date of previous issue		: 30-1-2023	3/13	AkzoNobel

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	otective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.		
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
6.3 Methods and material for containment and cleaning up			
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.		
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information		

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	4/13	AkzoNobe

# **SECTION 7: Handling and storage**

7.3 Specific end use(s)		
Recommendations	:	Not available.
Industrial sector specific	:	Not available.
solutions		

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

No exposure limit value known.

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

No DNELs/DMELs available.

### PNECs

No PNECs available

8.2 Exposure controls				
Appropriate engineering controls		Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
Individual protection meas	<u>sures</u>			
Hygiene measures		before eating, smoking Appropriate techniques Wash contaminated clo	and using the lavatory and should be used to remove	handling chemical products, I at the end of the working period. Potentially contaminated clothing. ure that eyewash stations and on.
Eye/face protection		Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.		
Skin protection				
Hand protection				with an approved standard should ucts if a risk assessment indicates
Date of issue/Date of revision		: 14-4-2023	Version : 3	3
Date of previous issue		: 30-1-2023	5/13	AkzoNobel

# **SECTION 8: Exposure controls/personal protection**

	For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Solid. [Powder.]
Colour	: Grey.
Odour	: Odourless.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: 20 - 70 g/m3
Flash point	: Closed cup: Not applicable. [Pensky-Martens]
Auto-ignition temperature	: 450 to 600°C (842 to 1112°F)
Decomposition temperature	: Not available.
рН	: Not applicable. [DIN EN 1262]
Viscosity	: Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
Solubility(ies)	:



SECTION 9: Physical and chemical properties			
Media		Result	
cold water		Not soluble [OESO (TG 105)]	
Partition coefficient: n-octar water	nol/ :	Not applicable.	
Vapour pressure	:	Not available.	
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]	
Vapour density	:	Not applicable.	
Particle characteristics			
Median particle size	:	Not available.	
9.2 Other information			
Minimum ignition energy (m	J) :	5 to 20	
SECTION 10: Stability and reactivity			
10.1 Reactivity	: No	specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The	product is stable.	
10.3 Possibility of hazardous reactions	: Unc	ler normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	(spa To a bon	oid the creation of dust when handling and avoid all possible sources of ignition ark or flame). Take precautionary measures against electrostatic discharges. avoid fire or explosion, dissipate static electricity during transfer by earthing and iding containers and equipment before transferring material. Prevent dust umulation.	
10.5 Incompatible materials		active or incompatible with the following materials: lising materials	
10.6 Hazardous decomposition products		ler normal conditions of storage and use, hazardous decomposition products uld not be produced.	

# **SECTION 11: Toxicological information**

11.1 Information on hazard	classes as defined in Regula	tion (EC) No 1272/2008	
Acute toxicity			
<b>Conclusion/Summary</b>	: Not available.		
Acute toxicity estimates			
N/A			
Irritation/Corrosion			
<b>Conclusion/Summary</b>	: Not available.		
<u>Sensitisation</u>			
<b>Conclusion/Summary</b>	: Not available.		
<u>Mutagenicity</u>			
<b>Conclusion/Summary</b>	: Not available.		
<b>Carcinogenicity</b>			
<b>Conclusion/Summary</b>	: Not available.		
Reproductive toxicity			
Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	7/13	AkzoNobel

SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN

Date of issue/Date of revision	: 14-4-2023	Version : 3	AkzoNobol
Reproductive toxicity	: No known significant ef	ffects or critical hazards.	
Mutagenicity	: No known significant ef	ffects or critical hazards.	
Carcinogenicity	: No known significant el	fects or critical hazards.	
General	: Repeated or prolonged	inhalation of dust may lead to chron	ic respiratory irritation.
<b>Conclusion/Summary</b>	: Not available.		
Not available.			
Potential chronic health effe	<u>ects</u>		
Potential delayed effects	: Not available.		
Potential immediate effects	: Not available.		
Long term exposure			
effects Potential delayed effects	: Not available.		
Short term exposure Potential immediate	: Not available.		
Delayed and immediate effect	<u>cts as well as chronic effe</u>	cts from short and long-term expo	<u>osure</u>
Ingestion	: No specific data.		
Skin contact	: No specific data.		
Inhalation	: Adverse symptoms ma respiratory tract irritatio coughing		
Eye contact	: Adverse symptoms ma irritation redness	y include the following:	
Symptoms related to the phy	/sical, chemical and toxic	ological characteristics	
Ingestion	: No known significant ef	nects of critical nazards.	
Skin contact	: No known significant ef		
Inhalation	limits may cause irritati	oncentrations above statutory or reco on of the nose, throat and lungs.	ommended exposure
Eye contact	: Exposure to airborne co limits may cause irritati	oncentrations above statutory or reco on of the eyes.	ommended exposure
Potential acute health effects	_		
Information on likely routes of exposure			
Aspiration hazard Not available.			
<u>Specific target organ toxicit</u> Not available.	<u>ty (repeated exposure)</u>		
Specific target organ toxicit Not available.	<u>ty (single exposure)</u>		
Conclusion/Summary	: Not available.		
<b>Teratogenicity</b>			
Conclusion/Summary	: Not available.		
<b>SECTION 11: Toxico</b>	logical information	า	
	SL181E/25KG Interpon D1036 (7	70) DARK ADMIRALTY GREY SATIN	



SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN

# **SECTION 11: Toxicological information**

### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible.
	Disposal of this product, solutions and any by-products should at all times comply
	with the requirements of environmental protection and waste disposal legislation and
	any regional local authority requirements. Dispose of surplus and non-recyclable
	products via a licensed waste disposal contractor. Waste should not be disposed of
	untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	9/13	AkzoNobel

SECTION 13: Disposal considerations			
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.		
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.		

### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders
Packaging	
Methods of dispos	<b>:</b> The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considera	ations: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	<ul> <li>This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.</li> </ul>

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ	
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	
14.2 UN proper shipping name	-	-	-	
14.3 Transport hazard class(es)	-	-	-	
14.4 Packing group	-	-	-	
14.5 Environmental hazards	No.	No.	No.	

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in** : Not applicable. bulk according to IMO instruments



	SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN
SECTION 15: Regula	itory information
5.1 Safety, health and envir <u>UK (GB) /REACH</u>	onmental regulations/legislation specific for the substance or mixture
Annex XIV - List of substa	nces subject to authorisation
Annex XIV	
None of the components a	are listed.
Substances of very high	concern
None of the components a	are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: Not applicable.
VOC for Ready-for-Use Mixture	: Not applicable.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) -	: Not listed
Water	
Ozone depleting substance	<u>:es (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (P Not listed.	<u>'IC) (649/2012/EU)</u>
Persistent Organic Polluta	ants
Not listed.	—
<u>Seveso Directive</u>	
	d under the Seveso Directive.
National regulations	
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations	
Chemical Weapon Convent	tion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol Not listed.	
Stockholm Convention on I Not listed.	Persistent Organic Pollutants
	Prior Informed Consent (PIC)
Nate of issue/Date of revision	
I I I I I I I I I I I I I I I I I I I	• 14-4-2023 Version : 3

Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	11/13	AkzoNobel

SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN

### SECTION 15: Regulatory information

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

# 15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information** 

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
acronyms	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

### Full text of abbreviated H statements

Not applicable.

#### Full text of classifications [CLP/GHS]

Not applicable.

Date of printing	: 14 April 2023
Date of issue/ Date of revision	: 14 April 2023
Date of previous issue	: 30 January 2023
Version	: 3
Unique ID	:
Nation to used on	

### Notice to reader

### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Date of issue/Date of revision	: 14-4-2023	Version : 3	
Date of previous issue	: 30-1-2023	12/13	AkzoNobel

SL181E/25KG Interpon D1036 (70) DARK ADMIRALTY GREY SATIN

**SECTION 16: Other information** 

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

