

SAFETY DATA SHEET

AJ402QF 12-5004 INTERPON 100 LAGOON BLUE U1556-1

Section 1. Identification Product identifier : AJ402QF 12-5004 INTERPON 100 LAGOON BLUE U1556-1 SDS code : 8121237 AJ402QF/25KG Relevant identified uses of the substance or mixture and uses advised against **Recommended use** Industrial use **Restrictions on use** All other uses Product use : Electrostatic coating for use in industrial plants Supplier's details Akzo Nobel Coatings Inc. Akzo Nobel Coatings Ltd. 150 Columbia Street 110 Woodbine Downs Blvd. Reading, PA 19601 USA Unit #4 Etobicoke. Ontario Canada M9W 5S6 1-610-372-3600 : CHEMTREC +1 (800) 424-9300 (Inside the US) **Emergency telephone** CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls number (with hours of accepted) operation) Domestic Poison Control Center Customer Service +1 (800) 854-6813 24 hours

Section 2. Hazard identification

Classification of the substance or mixture	: COMBUSTIBLE DUSTS SKIN IRRITATION - Cate EYE IRRITATION - Cate CARCINOGENICITY - Ca	gory 2 gory 2A ategory 2	
<u>GHS label elements</u> Hazard pictograms	TOXIC TO REPRODUCT	ION - Calegory 2	
Signal word	: Warning		
Hazard statements	: Causes skin irritation. Causes serious eye irritat Suspected of causing car Suspected of damaging for May form combustible du	ncer. ertility or the unborn child.	
Precautionary statements			
Prevention		s before use. Wear protective glove n. Wash hands thoroughly after hand	
Date of issue/Date of revision	: 2/6/2023	Version : 1.01	
Date of previous issue	: 12/13/2022	1/12	AkzoNobel

Section 2. Hazard identification

Response	: IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	% (w/w)	CAS number
titanium dioxide	≥10 - ≤30	13463-67-7
methylenedisalicylic acid	≥10 - ≤30	27496-82-8
trichloro(N,N-dimethyloctylamine)boron	≥0.1 - ≤1	34762-90-8
propylidynetrimethanol	≥0.1 - ≤1	77-99-6

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary fir	<u>rst aid measures</u>		
Eye contact		ith plenty of water, occasionally lif move any contact lenses. Contin ention.	
Inhalation	If not breathing, if breathi artificial respiration or oxy person providing aid to gi unconscious, place in reo Maintain an open airway. waistband. In case of inh	ir and keep at rest in a position co ng is irregular or if respiratory arre gen by trained personnel. It may ve mouth-to-mouth resuscitation. covery position and get medical att Loosen tight clothing such as a c alation of decomposition products d person may need to be kept und	est occurs, provide be dangerous to the Get medical attention. If cention immediately. collar, tie, belt or a in a fire, symptoms may
Skin contact	shoes. Continue to rinse	with plenty of water. Remove con for at least 10 minutes. Get medi ean shoes thoroughly before reus	ical attention. Wash
Ingestion	swallowed and the expose drink. Stop if the expose induce vomiting unless d the head should be kept attention. Never give any place in recovery position	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Date of issue/Date of revision	: 2/6/2023	Version : 1.01	
Date of previous issue	: 12/13/2022	2/12	AkzoNobel

Section 4. First-aid measures

Most important symptoms/effects, acute and delayed

Most important symptoms/effects, acute and delayed		
Potential acute health effe		
Eye contact	Causes serious eye irritation.	
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.	
Skin contact	Causes skin irritation.	
Ingestion	No known significant effects or critical hazards.	
<u>Over-exposure signs/symp</u>	<u>ns</u>	
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	No specific treatment.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media			
Suitable extinguishing media	: Use dry chemical powder.		
Unsuitable extinguishing media	: Avoid high pressure media explosible dust-air mixture.	which could cause the formation of	a potentially
Specific hazards arising from the chemical	: May form explosible dust-a	ir mixture if dispersed.	
Hazardous thermal decomposition products	: Decomposition products m carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides	ay include the following materials:	
Date of issue/Date of revision	: 2/6/2023	Version : 1.01	
Date of previous issue	: 12/13/2022	3/12	AkzoNobel

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other	Protective measures	Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers
--	---------------------	--



Section 7. Handling and storage

Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
titanium dioxide	 CA British Columbia Provincial (Canada, 3/2022). TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 6/2021). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). Skin sensitizer. 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. Form: total dust CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. 	

Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before
eating, smoking and using the lavatory and at the end of the working period.
Appropriate techniques should be used to remove potentially contaminated clothing.
Wash contaminated clothing before reusing. Ensure that eyewash stations and
safety showers are close to the workstation location.

Date of issue/Date of revision	: 2/6/2023	Version : 1.01	
Date of previous issue	: 12/13/2022	5/12	AkzoNobel

Section 8. Exposure controls/personal protection

Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance					
Physical state	: So	lid. [Powder.]			
Color	: Blu				
Odor		orless.			
Odor threshold	: No	t available.			
рН	: No	t applicable. [DIN EN	1262]		
Melting point/freezing point		t available.			
Boiling point, initial boiling point, and boiling range	: No	t available.			
Flash point	: Clo	sed cup: Not applica	ole. [Pensky-Martens]]	
Flammability	: No	t available.			
Lower and upper explosion limit/flammability limit	: 20 - 70 g/m3				
Vapor pressure	: Not available.				
Relative vapor density	: No	: Not applicable.			
Relative density	: 1.2	to 1.9 [ISO 8130-2/-3	3]		
Solubility(ies)	:				
Media		Result			
cold water		Not soluble [OESO	(TG 105)]		
Partition coefficient: n- octanol/water	: No	t applicable.			
Auto-ignition temperature	: 45	0 to 600°C (842 to 11	12°F)		
Date of issue/Date of revision	:	2/6/2023	Versi	on : 1.01	
Date of previous issue	:	12/13/2022	6/12		AkzoNobel

Section 9. Physical and chemical properties and safety characteristics

Decomposition temperature	:	Not available.
Minimum ignition energy (mJ)	:	5 to 20
Viscosity	:	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]
Particle characteristics		
Median particle size	:	Not available.

Section 10. Stability and reactivity		
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.	
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methylenedisalicylic acid	LD50 Oral	Guinea pig	1750 mg/kg	-
	LD50 Oral	Rat	2500 mg/kg	-
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	IARC	NTP	ACGIH
titanium dioxide	2B	-	A4

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Date of issue/Date of revision	: 2/6/2023	Version : 1.01
Date of previous issue	: 12/13/2022	8/12



Section 11. Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

To	cic	ity
_		_

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
trichloro(N,N- dimethyloctylamine)boron propylidynetrimethanol	5.77 -0.47	- <1	high Iow
Date of issue/Date of revision Date of previous issue	: 2/6/2023 : 12/13/2022	Vers 9/12	ion : 1.01 AkzoNobel

Section 12. Ecological information

Mobility in soil

Soil/water partition	: Not a
coefficient (Koc)	

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and
	liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments



Section 15. Regulatory information

Canadian lists	
Canadian NPRI	: The following components are listed: copper (and its compounds)
CEPA Toxic substances	: None of the components are listed.
Inventory list	
Canada	 At least one component is not listed in DSL but all such components are listed in NDSL.
United States	: All components are active or exempted.

Section 16. Other information

History Date of printing : 6 February 2023	
Date of printing : 6 February 2023	
Date of issue/ Date of : 6 February 2023 revision	
Date of previous issue : 13 December 2022	
Version : 1.01	
Unique ID :	
Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of C HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS - Category 1	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision	: 2/6/2023	Version : 1.01	
Date of previous issue	: 12/13/2022	11/12	AkzoNobel

Section 16. Other information

