

SAFETY DATA SHEET

AL106QF 10-7098 INTERPON 100 GRAY U1555-1

Section 1. Identification **GHS** product identifier : AL106QF 10-7098 INTERPON 100 GRAY U1555-1 SDS code : 8121282 AL106QF/25KG Relevant identified uses of the substance or mixture and uses advised against Identified uses Industrial use Uses advised against All other uses Product use : Electrostatic coating for use in industrial plants Supplier's details Akzo Nobel Coatings Inc. 150 Columbia Street Reading, PA 19601 USA 1-610-372-3600 **Emergency telephone** : CHEMTREC +1 (800) 424-9300 (Inside the US) number (with hours of CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls operation) accepted) Domestic Poison Control Center Customer Service +1 (800) 854-6813 Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Classification of the : COMBUSTIBLE DUSTS substance or mixture **CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 GHS** label elements Hazard pictograms Signal word : Warning : Suspected of causing cancer. Hazard statements Suspected of damaging fertility or the unborn child. May form combustible dust concentrations in air. **Precautionary statements** Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Response : IF exposed or concerned: Get medical advice or attention.

 Storage
 Not applicable.

 Date of issue/Date of revision
 : 3/22/2023
 Version
 : 2

 Date of previous issue
 : 11/23/2022
 1/12
 AkzoNobel

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
Manium dioxide	≥10 - ≤25	13463-67-7
manganese ferrite black spinel	≤3	68186-94-7
propylidynetrimethanol	≤0.3	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	 Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. 		
Inhalation	: Exposure to airborne cor may cause irritation of the	ncentrations above statutory or recom e nose, throat and lungs.	mended exposure limits
Skin contact	: No known significant effe	ects or critical hazards.	
Ingestion	: No known significant effe	ects or critical hazards.	
Date of issue/Date of revision	: 3/22/2023	Version : 2	
Date of previous issue	: 11/23/2022	2/12	AkzoNobel

Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. For non-emergency personnel Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel". **Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Methods and materials for containment and cleaning up Small spill : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed

 waste disposal contractor.
 Large spill
 Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	obtain special in handle until all s or on skin or clo when handling a accumulation. U ventilation is ina made from a con equipment and I coming into com precautionary m dissipate static e equipment befor	structions before use. Avoid exp afety precautions have been rea- thing. Do not ingest. Avoid brea- nd avoid all possible sources of lse only with adequate ventilatio dequate. Keep in the original co- mpatible material, kept tightly clo- ghting should be protected to ap act with hot surfaces, sparks or easures against electrostatic dis- electricity during transfer by grou	propriate standards to prevent dust
Advice on general occupational hygiene	handled, stored drinking and sm	and processed. Workers should	ed in areas where this material is I wash hands and face before eating, othing and protective equipment before ditional information on hygiene
Conditions for safe storage, including any incompatibilities	Store in original area, away from locked up. Elim container tightly opened must be unlabeled conta	container protected from direct s incompatible materials (see Sec nate all ignition sources. Separ- closed and sealed until ready fo carefully resealed and kept upri ners. Use appropriate containm	e in a segregated and approved area. sunlight in a dry, cool and well-ventilated ction 10) and food and drink. Store ate from oxidizing materials. Keep r use. Containers that have been ght to prevent leakage. Do not store in ient to avoid environmental materials before handling or use.
Date of issue/Date of revision	: 3/22/2023	Version	
Date of previous issue	: 11/23/2022	4/12	AkzoNobel

Section 7. Handling and storage

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
i ifanium dioxide	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2022). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles
manganese ferrite black spinel propylidynetrimethanol	None.
 Appropriate engineering controls Use only with adequate ventilation. If user operations generate dust, function or mist, use process enclosures, local exhaust ventilation or other engineer to keep worker exposure to airborne contaminants below any recommend limits. The engineering controls also need to keep gas, vapor or dust combelow any lower explosive limits. Use explosion-proof ventilation equipment 	

: Emissions from ventilation or work process equipment should be checked to ensure **Environmental exposure** they comply with the requirements of environmental protection legislation. In some controls cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	eating, smoking and usir Appropriate techniques s Wash contaminated clot	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	assessment indicates thi gases or dusts. If contac the assessment indicates	ig with an approved standard should s is necessary to avoid exposure to l at is possible, the following protection s a higher degree of protection: safe ditions cause high dust concentration	liquid splashes, mists, n should be worn, unless ety glasses with side-	
Skin protection				
Hand protection	worn at all times when ha necessary. Considering during use that the glove noted that the time to bre glove manufacturers. In	ervious gloves complying with an app andling chemical products if a risk as the parameters specified by the glov s are still retaining their protective pr eakthrough for any glove material ma the case of mixtures, consisting of s ves cannot be accurately estimated.	sessment indicates this is ve manufacturer, check operties. It should be ay be different for different everal substances, the	
Body protection		oment for the body should be selecte involved and should be approved by		
Other skin protection	based on the task being	propriate footwear and any additional skin protection measures should be selected sed on the task being performed and the risks involved and should be approved by a ecialist before handling this product.		
Respiratory protection	appropriate standard or o	l potential for exposure, select a resp certification. Respirators must be us ogram to ensure proper fitting, trainin	ed according to a	
Date of issue/Date of revision	: 3/22/2023	Version : 2		
Date of previous issue	: 11/23/2022	5/12	AkzoNobel	

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Solid. [Powder.]		
Color	:	Gray.		
Odor	:	Odorless.		
Odor threshold	:	Not available.		
рН	:	Not applicable. [DIN EN 1262]		
Melting point/freezing point	:	Not available.		
Flammability	:	Not available.		
Lower and upper explosion limit	:	20 - 70 g/m3		
Vapor pressure	:	Not available.		
Relative vapor density	:	Not applicable.		
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]		
Solubility(ies)	:			
Media		Result		
cold water		Not soluble [OESO (TG 105)]		
Partition coefficient: n- octanol/water	:	Not applicable.		
Auto-ignition temperature	:	450 to 600°C (842 to 1112°F)		
Decomposition temperature	:	Not available.		
Minimum ignition energy (mJ)	:	5 to 20		
Viscosity	:	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]		
Particle characteristics Median particle size	:	Not available.		

Section 10. Stability and reactivity

Date of previous issue	: 11/23/2022	6/12	AkzoNobel	
Date of issue/Date of revision	: 3/22/2023	Version : 2		
Hazardous decomposition products	: Under normal conditions not be produced.	of storage and use, hazardous de	composition products should	
Incompatible materials	: Reactive or incompatible oxidizing materials	e with the following materials:		
Conditions to avoid	(spark or flame). Take p avoid fire or explosion, d	st when handling and avoid all pose precautionary measures against ele lissipate static electricity during trai equipment before transferring mate	ectrostatic discharges. To nsfer by grounding and	
Possibility of hazardous reactions	: Under normal conditions	Under normal conditions of storage and use, hazardous reactions will not occur.		
Chemical stability	: The product is stable.			
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral LD50 Oral LD50 Oral LD50 Oral	Mouse Rat	13700 mg/kg 14000 mg/kg 14100 mg/kg 14000 mg/kg	- - -

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Reproductive toxicity

Not available.

<u>Teratogenicity</u>

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely	:	Not available.
routes of exposure		

Potential acute health effects

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: irritation
	redness



Section 11. Toxicological information

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effect	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Т	oxi	С	ity
_			

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
Date of issue/Date of revision	: 3/22/2023	Version : 2	
Date of previous issue	: 11/23/2022	8/12	AkzoNobe

Section 12. Ecological information

	<u> </u>		
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia - Neonate	
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex -	48 hours
		Neonate	
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex -	48 hours
		Neonate	
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	<1	low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	UN3077	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (benzothiazole- 2-thiol)	-	-
Transport hazard class(es)	9	-	-
Date of issue/Date of revisi	ion : 3/22/2023	Version : 2	
Date of previous issue	: 11/23/2022	9/12	AkzoNobel

Section 14. Transport information

Packing group		-	-	
Environmental hazards	No.	No.	No.	
Additional information	<u>n</u>			
DOT Classification	solely to the pre subject to repor greater than, or	esence of one or more US rtable quantity requirement equal to, the product repo	kg. The classification of the product is due DOT-listed 'Hazardous substances' that its and only applies to shipments of packa ortable quantity. Package sizes less than ated as hazardous materials.	t are ages
Special precautions f	upright and sec		ays transport in closed containers that are transporting the product know what to do	

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations	: United States inventory (TSCA 8b):	All components are active or exempted.
	()	

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ	: Not applicable.
-------------	-------------------

SARA 311/312

Classification	: COMBUSTIBLE DUSTS
	CARCINOGENICITY - Category 2
	TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

Name	%	Classification
ffanium dioxide propylidynetrimethanol		CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

<u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting requirements	manganese ferrite black spinel	68186-94-7	≤3
Supplier notification	manganese ferrite black spinel	68186-94-7	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: The following components are listed: TITANIUM DIOXIDE
New York	: None of the components are listed.
New Jersey	: The following components are listed: TITANIUM DIOXIDE; CYANIDE compounds

Date of issue/Date of revision	: 3/22/2023	Version : 2	
Date of previous issue	: 11/23/2022	10/12	AkzoNobel

Section 15. Regulatory information

Pennsylvania

: The following components are listed: TITANIUM OXIDE; CYANIDE COMPOUNDS; MANGANESE COMPOUNDS

California Prop. 65

WARNING: Cancer - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
ii tanium dioxide	-	-	Cancer
2-methylimidazole	-	-	Cancer
benzothiazole-2-thiol	-	-	Cancer

Inventory list

Canada

: All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

	Classification	Justification
COMBUSTIBLE DUSTS CARCINOGENICITY - Cate TOXIC TO REPRODUCTIC		On basis of test data Calculation method Calculation method
History		
Date of printing	: 7/3/2023	
Date of issue/ Date of revision	: 3/22/2023	
Date of previous issue	: 11/23/2022	
Version	: 2	
Unique ID	:	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classific IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Good LogPow = logarithm of the octanol/water partition MARPOL = International Convention for the Prev as modified by the Protocol of 1978. ("Marpol" = N/A = Not available SGG = Segregation Group UN = United Nations	ls n coefficient vention of Pollution From Ships, 1973

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Date of issue/Date of revision	: 3/22/2023	Version : 2	
Date of previous issue	: 11/23/2022	11/12	AkzoNobel

AL106QF 10-7098 INTERPON 100 GRAY U1555-1

Section 16. Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

