

SAFETY DATA SHEET

HNF35QF AN137QF 17-7005 ECB-1363A BLACK 2701

Section 1. Identification **GHS** product identifier : HNF35QF AN137QF 17-7005 ECB-1363A BLACK 2701 SDS code : 8123804 HNF35QF/25KG Relevant identified uses of the substance or mixture and uses advised against Identified uses Powder coating. Industrial use Uses advised against All other uses Product use : Electrostatic coating for use in industrial plants Supplier's details Akzo Nobel Coatings Inc. 150 Columbia Street Reading, PA 19601 USA 1-610-372-3600 : CHEMTREC +1 (800) 424-9300 (Inside the US) **Emergency telephone** number (with hours of CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls operation) accepted) Domestic Poison Control Center Customer Service +1 (800) 854-6813 Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Classification of the : COMBUSTIBLE DUSTS substance or mixture CARCINOGENICITY - Category 1A **GHS** label elements Hazard pictograms Signal word : Danger **Hazard statements** : May cause cancer. May form combustible dust concentrations in air. **Precautionary statements** Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. : IF exposed or concerned: Get medical advice or attention. Response Storage : Not applicable.

Section 2. Hazards identification

| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
|-------------------------------------|---|
| Supplemental label elements | : Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed

Potential acute health effects

| Eye contact | Exposure to airborne c may cause irritation of | concentrations above statutory or recom the eves. | mended exposure limits |
|--------------------------------|---|---|------------------------|
| Inhalation | : Exposure to airborne o | concentrations above statutory or recom the nose, throat and lungs. | mended exposure limits |
| Skin contact | : No known significant e | ffects or critical hazards. | |
| Ingestion | : No known significant e | ffects or critical hazards. | |
| Over-exposure signs/syn | <u>nptoms</u> | | |
| Eye contact | : Adverse symptoms ma irritation redness | ay include the following: | |
| Inhalation | : Adverse symptoms ma respiratory tract irritation coughing | , . | |
| Date of issue/Date of revision | : 1/27/2023 | Version : 1 | |
| Date of previous issue | : No previous validation | 2/10 | AkzoNobel |
| | | | |

Section 4. First aid measures

| Skin contact | : No specific data. |
|--------------|---------------------|
| Ingestion | : No specific data. |

Indication of immediate medical attention and special treatment needed, if necessary

| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | |
|---|---|--|
| Specific treatments Protection of first-aiders | No specific treatment. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. | |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|--|
| Suitable extinguishing media | : Use dry chemical powder. |
| Unsuitable extinguishing media | : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. |
| Specific hazards arising from the chemical | : May form explosible dust-air mixture if dispersed. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel | action shall be taken involving any personal risk or without suitable training. acuate surrounding areas. Keep unnecessary and unprotected personnel from ering. Do not touch or walk through spilled material. Shut off all ignition sour flares, smoking or flames in hazard area. Avoid breathing dust. Provide ade tilation. Wear appropriate respirator when ventilation is inadequate. Put on propriate personal protective equipment. | ces. |
|--------------------------------|---|------|
| For emergency responders | becialized clothing is required to deal with the spillage, take note of any inforn ction 8 on suitable and unsuitable materials. See also the information in "For ergency personnel". | |
| Environmental precautions | oid dispersal of spilled material and runoff and contact with soil, waterways, dr I sewers. Inform the relevant authorities if the product has caused environme ution (sewers, waterways, soil or air). | |

Methods and materials for containment and cleaning up

| Date of issue/Date of revision | : 1/27/2023 | Version : 1 | |
|--------------------------------|--------------------------|-------------|-----------|
| Date of previous issue | : No previous validation | 3/10 | AkzoNobel |

Section 6. Accidental release measures

| Small spill | Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. |
|-------------|--|
| Large spill | Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | | Exposure limits | Exposure limits | |
|--|--------------------------|---|-----------------|--|
| crystalline silica Crystalline silica OSHA PEL Z3 (Un TWA: 250 mppcf, Respirable TWA: 10 mg/m³ / Respirable OSHA PEL (United TWA: 50 μg/m³ 8 dust OSHA PEL 1989 (U Notes: as quartz TWA: 0.1 mg/m³, Respirable dust | | ed States, 6/2016). (%SiO2+5) 8 hours. Form: %SiO2+2) 8 hours. Form: States, 5/2018). ours. Form: Respirable nited States, 3/1989). as quartz) 8 hours. Form: | | |
| Date of issue/Date of revision | : 1/27/2023 | Version : 1 | | |
| Date of previous issue | : No previous validation | 4/10 AkzoNobe | | |

Section 8. Exposure controls/personal protection

| Section 8. Exposure controls/personal protection | | |
|--|--|--|
| | ACGIH TLV (United States, 3/2018). Notes: Respirable fraction; see Appendix C, paragraph C. TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen TWA: 0.05 mg/m ³ 10 hours. Form: respirable dust | |
| Limestone | None. | |
| Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. | | |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | |
| Individual protection measu | Ires | |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | |
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles. | |
| Skin protection | | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. | |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. | |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. | |



Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

| Physical state | : | Solid. [Powder.] |
|--|---|--|
| Color | : | Black. |
| Odor | : | Odorless. |
| Odor threshold | : | Not available. |
| рН | : | Not applicable. |
| Melting point/freezing point | : | Not available. |
| Boiling point, initial boiling point, and boiling range | : | Not available. |
| Flash point | : | Closed cup: Not applicable. |
| Flammability | : | Not available. |
| Lower and upper explosion limit/flammability limit | : | Not available. |
| Vapor pressure | : | |
| Relative vapor density | : | |
| Relative density | : | 1.2 to 1.9 [ISO 8130-2/-3] |
| Solubility(ies) | : | |
| Not available. | | |
| Partition coefficient: n- octanol/water | : | Not available. |
| Auto-ignition temperature | : | 450 to 600°C (842 to 1112°F) |
| Decomposition temperature | : | Not available. |
| Minimum ignition energy (mJ) | : | 5 to 20 |
| Viscosity | : | Kinematic (room temperature): Not applicable. Kinematic (40°C (104°F)): Not applicable. |
| Particle characteristics | | |
| Median particle size | : | |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |

Section 10. Stability and reactivity

Hazardous decomposition
products: Under normal conditions of storage and use, hazardous decomposition products should
not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|---------------------------------|
| crystalline silica | - | 1 | Known to be a human carcinogen. |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

| Information on the likely | : Not available. |
|---------------------------|------------------|
| routes of exposure | |

Potential acute health effects

| Eye contact | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. |
|--------------|--|
| Inhalation | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion | : No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | : Adverse symptoms may inclu irritation redness | de the following: | |
|--------------------------------|--|-------------------|-----------|
| Inhalation | : Adverse symptoms may inclu respiratory tract irritation coughing | de the following: | |
| Date of issue/Date of revision | : 1/27/2023 | Version : 1 | |
| Date of previous issue | : No previous validation | 7/10 | AkzoNobel |

Section 11. Toxicological information

| Skin contact | : No specific data. |
|--------------|---------------------|
| Ingestion | : No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

| Short term exposure | | |
|--------------------------------|-----|--|
| Potential immediate effects | : | Not available. |
| Potential delayed effects | : | Not available. |
| Long term exposure | | |
| Potential immediate effects | : | Not available. |
| Potential delayed effects | : | Not available. |
| Potential chronic health effe | ect | <u>s</u> |
| Not available. | | |
| General | : | Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. |
| Carcinogenicity | : | May cause cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : | No known significant effects or critical hazards. |
| Reproductive toxicity | : | No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

| Disposal methods | requirements of environments regional local authority require via a licensed waste disposal the sewer unless fully complia | Id be avoided or minimized whe any by-products should at all tim al protection and waste disposal ements. Dispose of surplus and contractor. Waste should not b ant with the requirements of all a ecycled. Incineration or landfill | nes comply with the legislation and any non-recyclable products e disposed of untreated to nuthorities with jurisdiction. |
|--------------------------------|---|--|---|
| Date of issue/Date of revision | : 1/27/2023 | Version : 1 | |
| Date of previous issue | : No previous validation | 8/10 | AkzoNobel |

Section 13. Disposal considerations

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

| | DOT Classification | IMDG | IATA |
|-------------------------------|--------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

| Section 15. Regu | latory information | | |
|--------------------------|---|--|--|
| U.S. Federal regulations | : United States inventory (TSCA 8b): | All components are active or exempted. | |

| State regulations | |
|----------------------------|--|
| Massachusetts | The following components are listed: SILICA, CRYSTALLINE, QUARTZ; CALCIUM CARBONATE; MARBLE DUST |
| New York | : None of the components are listed. |
| New Jersey | The following components are listed: SILICA, QUARTZ; QUARTZ (SiO2); CALCIUM CARBONATE; LIMESTONE |
| Pennsylvania | : The following components are listed: QUARTZ DUST; QUARTZ; LIMESTONE |
| <u>California Prop. 65</u> | |
| | r - www.P65W/arnings.ca.gov |

WARNING: Cancer - www.P65Warnings.ca.gov.

Section 15. Regulatory information

| Ingredient name | No significant risk level | Maximum acceptable dosage level | Type of toxicity |
|---|------------------------------|---------------------------------------|------------------|
| crystalline silica 2-methylimidazole | - | - | Cancer Cancer |

Inventory list Canada

: All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

| Classification COMBUSTIBLE DUSTS CARCINOGENICITY - Category 1A | | JustificationOn basis of test dataCalculation method | |
|--|---|--|--|
| | | | |
| Date of printing | : 27 January 2023 | | |
| Date of issue/ Date of revision | : 27 January 2023 | | |
| Date of previous issue | : No previous validation | | |
| Version | : 1 | | |
| Unique ID | : | | |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classifica IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition MARPOL = International Convention for the Prev as modified by the Protocol of 1978. ("Marpol" = N/A = Not available SGG = Segregation Group UN = United Nations | sociation rous Goods ter partition coefficient for the Prevention of Pollution From Ships, 1973 | |

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.