

SAFETY DATA SHEET

EA107QF 40-1260 INTERPON 700 K175 OYSTER WHITE

Section 1. Identification

Product identifier: EA107QF 40-1260 INTERPON 700 K175 OYSTER WHITESDS code: 8131167EA107QF/25KG

Relevant identified uses of the substance or mixture and uses advised against

Recommended use			
Industrial use			
	Restrictions on use		
All other uses			
Product use :	Electrostatic coating for use in industrial plants		
Supplier's details			
Akzo Nobel Coatings In 150 Columbia Street Reading, PA 19601 US	110 Woodbine Downs Blvd.		
1-610-372-3600 Emergency telephone number (with hours of operation) : CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted) 24 hours			
Section 2. Hazard identification			
Classification of the : substance or mixture	COMBUSTIBLE DUSTS - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1		

GHS label elements

Hazard pictograms



Signal word	: Danger
Hazard statements	: May cause an allergic skin reaction.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	Suspected of causing cancer.
	Suspected of damaging fertility or the unborn child

CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

Suspected of damaging fertility or the unborn child. May form combustible dust concentrations in air.

Precautionary statements



Section 2. Hazard identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Avoid breathing dust or mist. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

% (w/w)	CAS number	
≥10 - ≤30	13463-67-7	
≥0.1 - ≤1	552-30-7	
≥0.1 - ≤1	77-99-6	
	≥10 - ≤30 ≥0.1 - ≤1	≥10 - ≤30 13463-67-7 ≥0.1 - ≤1 552-30-7

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First-aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effe	ts
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>toms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate mee	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Date of issue/Date of revision	: 9/6/2023	Version : 1.03	
Date of previous issue	: 8/17/2023	3/12	AkzoNobel

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures For non-emergency : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. **For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". : Avoid dispersal of spilled material and runoff and contact with soil, waterways, Environmental precautions drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Methods and materials for containment and cleaning up Small spill : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container.

Large spill: Move containers from spill area. Use spark-proof tools and explosion-proof
equipment. Approach release from upwind. Prevent entry into sewers, water
courses, basements or confined areas. Avoid dust generation. Do not dry sweep.
Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled
waste container. Avoid creating dusty conditions and prevent wind dispersal.
Dispose of via a licensed waste disposal contractor. Note: see Section 1 for
emergency contact information and Section 13 for waste disposal.

Place spilled material in a designated, labeled waste container. Dispose of via a



Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits	
titanium dioxide CA British Columbia Pr 3/2022). TWA: 10 mg/m³ 8 hours. TWA: 3 mg/m³ 8 hours. fraction CA Quebec Provincial (TWAEV: 10 mg/m³ 8 hours. CA Alberta Provincial (Skin sensitizer. 8 hrs OEL: 10 mg/m³ 8 CA Ontario Provincial (TWA: 10 mg/m³ 8 hours. CA Saskatchewan Prov 7/2013). STEL: 20 mg/m³ 15 min TWA: 10 mg/m³ 8 hours.		ours. Form: Total dust ars. Form: respirable al (Canada, 6/2021). b hours. Form: Total al (Canada, 6/2018). b hours. al (Canada, 6/2019). bours. Form: total dust rovincial (Canada, minutes.	
benzene-1,2,4-tricarboxylic acid 1,2-anhydride		CA Ontario Provincia Absorbed through sl	
ate of issue/Date of revision	: 9/6/2023	Version : 1.03	
ate of previous issue	: 8/17/2023	5/12	AkzoNobel

Section 8. Exposure controls/personal protection

STEL: 0.002 mg/m ³ 15 minutes. Form:
Inhalable fraction and vapour.
TWA: 0.0005 mg/m ³ 8 hours. Form:
Inhalable fraction and vapour.
CA British Columbia Provincial (Canada,
3/2022). Absorbed through skin. Skin
sensitizer. Inhalation sensitizer.
C: 0.04 mg/m ³ 15 minutes. Form: Inhalable
vapour and aerosol
CA Quebec Provincial (Canada, 6/2021).
Absorbed through skin. Skin sensitizer.
STEV: 0.002 mg/m ³ 15 minutes. Form:
inhalable dust and vapor fraction
TWAEV: 0.0005 mg/m ³ 8 hours. Form:
inhalable dust and vapor fraction
CA Alberta Provincial (Canada, 6/2018).
C: 0.04 mg/m^3 15 minutes.
CA Saskatchewan Provincial (Canada,
• •
7/2013).
CEIL: 0.04 mg/m ³

Appropriate engineering controls Environmental exposure controls		Use only with adequate ventilation. vapor or mist, use process enclosu controls to keep worker exposure t recommended or statutory limits. T vapor or dust concentrations below ventilation equipment. Emissions from ventilation or work they comply with the requirements cases, fume scrubbers, filters or er	rres, local exhaust ventilation or o o airborne contaminants below a The engineering controls also ne of any lower explosive limits. Use process equipment should be ch of environmental protection legis ngineering modifications to the pro-	other engineering iny ed to keep gas, explosion-proof necked to ensure slation. In some rocess
		equipment will be necessary to red	uce emissions to acceptable leve	els.
Individual protection measure	<u>es</u>			
Hygiene measures	:	Wash hands, forearms and face th eating, smoking and using the lava Appropriate techniques should be a Contaminated work clothing should contaminated clothing before reusi showers are close to the workstation	tory and at the end of the workin used to remove potentially contain I not be allowed out of the workp ng. Ensure that eyewash station	g period. minated clothing. lace. Wash
Eye/face protection	:	Safety eyewear complying with an a assessment indicates this is neces gases or dusts. If contact is possib unless the assessment indicates a side-shields. If operating condition use dust goggles.	sary to avoid exposure to liquid s ole, the following protection shou higher degree of protection: saf	splashes, mists, ld be worn, ety glasses with
Skin protection				
Hand protection	:	Chemical-resistant, impervious glo be worn at all times when handling this is necessary. Considering the check during use that the gloves ar should be noted that the time to bre different for different glove manufa- several substances, the protection estimated.	chemical products if a risk asset parameters specified by the glov re still retaining their protective p eakthrough for any glove materia cturers. In the case of mixtures,	ssment indicates /e manufacturer, roperties. It Il may be consisting of
Body protection	:	Personal protective equipment for the being performed and the risks involution before handling this product.		
Date of issue/Date of revision		: 9/6/2023	Version : 1.03	
Date of previous issue		: 8/17/2023	6/12	AkzoNobel

Section 8. Exposure controls/personal protection

	selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Media		Result
Solubility(ies)	:	
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]
Relative vapor density	:	Not applicable.
Vapor pressure	:	Not available.
Lower and upper explosion limit	:	20 - 70 g/m3
Flammability	:	Not available.
Melting point/freezing point	:	Not available.
рН	:	Not applicable. [DIN EN 1262]
Odor threshold	:	Not available.
Odor	:	Odorless.
Color	:	White.
Physical state	:	Solid. [Powder.]

	cold water		Not soluble [OESO (TG 105)]
	artition coefficient: n- ctanol/water	:	Not applicable.
Α	uto-ignition temperature	:	450 to 600°C (842 to 1112°F)
D	ecomposition temperature	:	Not available.
	inimum ignition energy ıJ)	:	5 to 20
V	scosity	:	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]
<u>P</u> a	article characteristics		
Ν	ledian particle size	:	Not available.
W	ercentage of particles ⁄ith aerodynamic diameter 10 μm	:	0

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date of revision	: 9/6/2023	Version : 1.03	
Date of previous issue	: 8/17/2023	7/12	AkzoNobel

Section 10. Stability and reactivity

Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	LD50 Oral	Mouse	1900 mg/kg	-
•	LD50 Oral	Rabbit	5600 mg/kg	-
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

<u>Mutagenicity</u>

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	IARC	NTP	ACGIH
titanium dioxide	2B	-	A4

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Date of issue/Date of revision	: 9/6/2023	Version : 1.03	
Date of previous issue	: 8/17/2023	8/12	AkzoNobel

Section 11. Toxicological information

Information on the likely routes of exposure	: N	ot available.
Potential acute health effects		
Eye contact		xposure to airborne concentrations above statutory or recommended exposure mits may cause irritation of the eyes.
Inhalation	lin	xposure to airborne concentrations above statutory or recommended exposure nits may cause irritation of the nose, throat and lungs. May cause allergy or sthma symptoms or breathing difficulties if inhaled.
Skin contact	: M	lay cause an allergic skin reaction.
Ingestion	: N	o known significant effects or critical hazards.
Symptoms related to the phy	sical	, chemical and toxicological characteristics
Eye contact	irr	dverse symptoms may include the following: ritation edness
Inhalation	re cc wl as re in	dverse symptoms may include the following: espiratory tract irritation oughing theezing and breathing difficulties sthma educed fetal weight icrease in fetal deaths keletal malformations
Skin contact	irr re re in	dverse symptoms may include the following: ritation edness educed fetal weight icrease in fetal deaths keletal malformations
Ingestion	re ine	dverse symptoms may include the following: educed fetal weight crease in fetal deaths keletal malformations
	ts and	d also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate	: N	ot available.

Date of issue/Date of revision		: 9/6/2023	Version : 1.03
Reproductive toxicity	:	Suspected of damaging fertility or t	he unborn child.
Mutagenicity		No known significant effects or critical hazards.	
Carcinogenicity		exposure.	c of cancer depends on duration and level of
General	:		of dust may lead to chronic respiratory irritation. reaction may occur when subsequently exposed
Not available.			
Potential chronic health eff	ect	<u>S</u>	
Potential delayed effects	:	Not available.	
Potential immediate effects	:	Not available.	
Long term exposure			
Potential delayed effects	:	Not available.	
effects			

Date of issue/Date of revision	: 9/6/2023	Version : 1.03	
Date of previous issue	: 8/17/2023	9/12	AkzoNobel

Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	0.06	-	low
	-0.47	<1	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.



Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Additional information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

<u>Canadian lists</u>	
Canadian NPRI	: None of the components are listed.
CEPA Toxic substances	: None of the components are listed.
Inventory list	
Canada	: All components are listed or exempted.
United States	: 🕅 components are active or exempted.



Section 16. Other information

<u>History</u>	
Date of printing	: 9/6/2023
Date of issue/ Date of revision	: 9/6/2023
Date of previous issue	: 8/17/2023
Version	: 1.03
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS - Category 1	On basis of test data
RESPIRATORY SENSITIZATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

✓ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

