

# **SAFETY DATA SHEET**

#### JA133QF 30-1550 INTERPON 600 WHITE

### Section 1. Identification

GHS product identifier SDS code

 : JA133QF 30-1550 INTERPON 600 WHITE
 : 8131886 JA133QF/25KG

#### Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Industrial use	
	Uses advised against
All other uses	
Product use	: Electrostatic coating for use in industrial plants
Supplier's details	
Akzo Nobel Coatir 150 Columbia Stre Reading, PA 1960	eet
1-610-372-3600	
Emergency telephone number (with hours of operation)	<ul> <li>CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)</li> <li>Domestic Poison Control Center Customer Service +1 (800) 854-6813</li> </ul>
Section 2. Hazar	ds identification
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Danger



### Section 2. Hazards identification

Hazard statements	<ul> <li>Harmful if swallowed.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>May cause genetic defects.</li> <li>May cause cancer.</li> <li>Suspected of damaging fertility or the unborn child.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> <li>May form combustible dust concentrations in air.</li> </ul>
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
Manium dioxide	≥25 - ≤50	13463-67-7
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	≤5	2451-62-9
propylidynetrimethanol	≤0.3	77-99-6
Crystalline Silica as quartz not respirable,>10µm	≤0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

- Eye contact

- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.



# Section 4. First aid measures

Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye damage.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision	: 6/14/2023	Version : 2.01	
Date of previous issue	: 5/31/2023	3/13	AkzoNobel

# Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

#### See toxicological information (Section 11)

Section 5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Date of issue/Date of revision	: 6/14/2023	Version : 2.01	
Date of previous issue	: 5/31/2023	4/13	AkzoNobel

# Section 6. Accidental release measures

Small spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name		Exposure limits		
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione		OSHA PEL (United Sta TWA: 15 mg/m <sup>3</sup> 8 hou OSHA PEL 1989 (Unite TWA: 10 mg/m <sup>3</sup> 8 hou ACGIH TLV (United St TWA: 2.5 mg/m <sup>3</sup> 8 hou fraction, finescale partic ACGIH TLV (United St	rs. Form: Total dust ed States, 3/1989). rs. Form: Total dust ates, 1/2022). urs. Form: respirable les	
Date of issue/Date of revision	: 6/14/2023	Version : 2.01		
Date of previous issue	: 5/31/2023	5/13	AkzoNobel	

# Section 8. Exposure controls/personal protection

	[1,3,5-Triglycidyl-s-triazinetrione]
	TWA: 0.05 mg/m <sup>3</sup> 8 hours.
propylidynetrimethanol	None.
Crystalline Silica as quartz not respirable,>10µm	OSHA PEL Z3 (United States, 6/2016).
	TWA: 250 mppcf / (%SiO2+5) 8 hours. Form:
	Respirable
	TWA: 10 mg/m <sup>3</sup> / (%SiO2+2) 8 hours. Form:
	Respirable
	OSHA PEL (United States, 5/2018).
	TWA: 50 µg/m³ 8 hours. Form: Respirable
	dust
	OSHA PEL 1989 (United States, 3/1989).
	Notes: as quartz
	TWA: 0.1 mg/m³, (as quartz) 8 hours. Form:
	Respirable dust
	ACGIH TLV (United States, 3/2018). Notes:
	Respirable fraction; see Appendix C,
	paragraph C.
	TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form:
	Respirable fraction
	NIOSH REL (United States, 10/2016).
	Notes: See Appendix A - NIOSH Potential
	Occupational Carcinogen
	TWA: 0.05 mg/m <sup>3</sup> 10 hours. Form: respirable
	dust

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of issue/Date of revision	: 6/14/2023	Version : 2.01	
Date of previous issue	: 5/31/2023	6/13	AkzoNobel

**Appearance** 

# Section 8. Exposure controls/personal protection

protective equipment for the body should be selected based on the task being d and the risks involved and should be approved by a specialist before this product. ate footwear and any additional skin protection measures should be selected the task being performed and the risks involved and should be approved by a before handling this product.
the task being performed and the risks involved and should be approved by a
the hazard and potential for exposure, select a respirator that meets the te standard or certification. Respirators must be used according to a y protection program to ensure proper fitting, training, and other important of use.

# characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>nppoulanoo</u>		
Physical state	: 8	Solid. [Powder.]
Color	: V	Vhite.
Odor	: (	Ddorless.
Odor threshold	: N	lot available.
рН	: N	lot applicable. [DIN EN 1262]
Melting point/freezing point	: N	lot available.
Flammability	: N	lot available.
Lower and upper explosion limit	: 2	20 - 70 g/m3
Vapor pressure	: N	lot available.
Relative vapor density	: N	lot applicable.
Relative density	: 1	.2 to 1.9 [ISO 8130-2/-3]
Solubility(ies)	:	
Media		Result
cold water		Not soluble [OESO (TG 105)]
Partition coefficient: n- octanol/water	: N	lot applicable.
Auto-ignition temperature	: 4	50 to 600°C (842 to 1112°F)
Decomposition temperature	: N	lot available.
Minimum ignition energy (mJ)	: 5	to 20
Viscosity		(inematic (room temperature): Not applicable. [DIN EN ISO 3219] (inematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]
Particle characteristics		
Median particle size	: N	lot available.
Percentage of particles with aerodynamic diameter ≤ 10 μm	: 0	

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
7,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	LC50 Inhalation Dusts and mists	Mouse	2000 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Dusts and mists	Rat	650 mg/m³	4 hours
	LD50 Oral	Rat	188 mg/kg	-
	LD50 Oral	Rat	222 mg/kg	-
	LD50 Oral	Rat	138 mg/kg	-
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
7,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	Eyes - Severe irritant	Rabbit	-	100 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
iffanium dioxide Crystalline Silica as quartz not respirable,>10μm	-	2B 1	- Known to be a human carcinogen.
ate of issue/Date of revision	• 6/14/20	23	Version · 201

# Section 11. Toxicological information

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione	Category 2	-	-

#### Aspiration hazard

Not available.

effects

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye damage.
Inhalation	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	:	May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	ts	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate	:	Not available.

Date of issue/Date of revision	: 6/14/2023	Version : 2.01	
Date of previous issue	: 5/31/2023	9/13	AkzoNobel

### Section 11. Toxicological information

		0
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
General	:	May cause dam prolonged inhal

General	: May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: May cause genetic defects.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
₱5/JA133QF/USA 30-1550 INT 600 WHITE/BAS 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	1978.6 100	N/A N/A	N/A N/A	N/A N/A	9.9 0.5

# Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
propylidynetrimethanol	Acute LC50 >1000000 μg/l Marine water Acute LC50 >1000 mg/l Fresh water Acute EC50 13000000 μg/l Fresh water	Fish - Fundulus heteroclitus Fish - Pimephales promelas Daphnia - Daphnia magna	96 hours 96 hours 48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

#### Persistence and degradability

Not available.

Date of issue/Date of revision	: 6/14/2023	Version : 2.01	
Date of previous issue	: 5/31/2023	10/13	AkzoNobel

# Section 12. Ecological information

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
	-0.8	-	low
5H)-trione propylidynetrimethanol	-0.47	<1	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

### **Section 14. Transport information**

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA			
UN number	UN3077	Not regulated.	Not regulated.			
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (benzothiazole- 2-thiol)	-	-			
Transport hazard class(es)	9	-	-			
Packing group	111	-	-			
Environmental hazards	No.	No.	No.			
Additional information						
<b>DOT Classification</b> : <b>Reportable quantity</b> 2234.2 lbs / 1014.3 kg. The classification of the product is due						

: **Reportable quantity** 2234.2 lbs / 1014.3 kg. The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

### **Section 14. Transport information**

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

### Section 15. Regulatory information

U.S. Federal regulations	: United States inventory (TSCA 8b):	Not determined.
	chemicals which are not listed on the l another product for commercial purpos qualified individual. This material's che	This is a new product solely for research and development use. It contains J.S. EPA TSCA Inventory and cannot be distributed by itself or as a part of ses. It is to be used only by/ under the direct supervision of a technically emical, physical, and toxicological properties have not been fully be hazardous. Caution must be exercised through the use of protective o minimize exposure.
State regulations		
Massachusetts	: The following components are	e listed: TITANIUM DIOXIDE; BARIUM SULFATE
New York	: None of the components are I	isted.
New Jersey	: The following components are 1,3,5-TRIGLYCIDYL-s-TRIAZ	e listed: TITANIUM DIOXIDE; BARIUM SULFATE; INETRIONE
Pennsylvania	: The following components are	e listed: TITANIUM OXIDE; BARIUM SULFATE

#### California Prop. 65

**WARNING**: Cancer - www.P65Warnings.ca.gov.

No significant risk level	Maximum acceptable dosage level	Type of toxicity
-	-	Cancer
	•	level acceptable dosage

#### Inventory list

Canada

: Not determined.

### Section 16. Other information

#### Procedure used to derive the classification

Classification			Justification	
COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1				On basis of test data Calculation method Calculation method Calculation method
GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2			Calculation method Calculation method Calculation method Calculation method	
<u>History</u>				
Date of printing	: 14 June 2023			
Date of issue/ Date of revision	: 14 June 2023			
Date of previous issue	: 31 May 2023			
Version	: 2.01			
Date of issue/Date of revision	: 6/14/2023	Version	: 2.01	
Date of previous issue	: 5/31/2023	12/13		AkzoNobel

### Section 16. Other information

Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

