

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# SAFETY DATA SHEET

YL357F/20KG Interpon D2525 GREY Matt

## **SECTION 1: Identification of the substance/mixture and of the company/** undertaking

1.1 Product identifier	
Product name	:

SDS code

 YL357F/20KG Interpon D2525 GREY Matt
 8136781 YL357F/20KG

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Industrial use		
	Uses advised against	
All other uses		
	— · · · · · · · · · · · · · · · ·	

Product use

: Electrostatic coating for use in industrial plants

#### 1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. NE10 0JY United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS <u>National contact</u> 01 8092566 or 01 8379964 1.4 Emergency telephone number <u>National advisory body/Poison Centre</u>

Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111
Hours of operation	:

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	1/14	AkzoNobel

## **SECTION 2: Hazards identification**

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	en	ts
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form combustible dust concentrations in air.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

#### : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	EC: 247-952-5 CAS: 26741-53-7	≤1	Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Туре</u>

[1] Substance classified with a health or environmental hazard

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	2/14	AkzoNobel

## **SECTION 3: Composition/information on ingredients**

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

#### **Over-exposure signs/symptoms**

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

#### 5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	3/14	AkzoNobel

SECTION 5: Firefighting measures			
Hazards from the substance or mixture	: May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides		
5.3 Advice for firefighters			
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.		
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

information on hygiene measures.

: Not available.
: Not available.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

<u>Occu</u>	pational	exposure	<u>limits</u>

No exposure limit value know	'n.		
Recommended monitoring procedures	atmosphere or biologica of the ventilation or othe protective equipment. F the following: European the assessment of expo limit values and measur atmospheres - Guide for of exposure to chemical (Workplace atmosphere for the measurement of	ngredients with exposure limits, perso I monitoring may be required to deter r control measures and/or the necess Reference should be made to monitori Standard EN 689 (Workplace atmos sure by inhalation to chemical agents ement strategy) European Standard the application and use of procedure and biological agents) European Sta s - General requirements for the perforce chemical agents) Reference to natio for the determination of hazardous su	mine the effectiveness sity to use respiratory ing standards, such as pheres - Guidance for for comparison with EN 14042 (Workplace es for the assessment andard EN 482 ormance of procedures nal guidance
Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	5/14	AkzoNobel

## **SECTION 8: Exposure controls/personal protection**

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
3,9-bis(2,4-di-tert-butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5]undecane	DNEL	Long term Oral	0.39 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.39 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.68 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.78 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.75 mg/m <sup>3</sup>	Workers	Systemic

#### PNECs

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering controls	vapour or mist, use proce engineering controls to ke recommended or statutor vapour or dust concentra proof ventilation equipme	entilation. If user operations gener ess enclosures, local exhaust ventil eep worker exposure to airborne co y limits. The engineering controls tions below any lower explosive lim nt.	lation or other ontaminants below any also need to keep gas,	
Individual protection meas				
Hygiene measures	before eating, smoking a Appropriate techniques s Wash contaminated cloth	nd face thoroughly after handling c nd using the lavatory and at the en- hould be used to remove potentiall ing before reusing. Ensure that ey to the workstation location.	d of the working period. y contaminated clothing.	
Eye/face protection	assessment indicates this gases or dusts. If contac unless the assessment in	g with an approved standard shoul s is necessary to avoid exposure to t is possible, the following protection dicates a higher degree of protection conditions cause high dust concert	o liquid splashes, mists, on should be worn, on: safety glasses with	
Skin protection				
Hand protection	be worn at all times when this is necessary. Consid check during use that the should be noted that the different for different glov	: Chemical-resistant, impervious gloves complying with an approved standard shoul be worn at all times when handling chemical products if a risk assessment indicate this is necessary. Considering the parameters specified by the glove manufacture check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
	protection class of 6 (brea recommended. Recomm When only brief contact is (breakthrough time >30 n Recommended gloves: N	ently repeated contact may occur, akthrough time >480 minutes acco- lended gloves: Viton ® or Nitrile, th s expected, a glove with protection ninutes according to EN374) is rec- litrile, thickness $\geq 0.12$ mm. Ind regularly and if there is any sign	rding to EN374) is lickness ≥ 0.38 mm. class of 2 or higher ommended.	
	The performance or effect chemical damage and po	tiveness of the glove may be reduced or maintenance.	ced by physical/	
Date of issue/Date of revision	: 18-4-2023	Version : 2.01		
Date of previous issue	: 31-1-2023	6/14	AkzoNobel	

## **SECTION 8: Exposure controls/personal protection**

	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Solid. [Powder.]
Colour	: Grey.
Odour	: Odourless.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: 20 - 70 g/m3
Flash point	: Closed cup: Not applicable. [Pensky-Martens]
Auto-ignition temperature	: 450 to 600°C (842 to 1112°F)
Decomposition temperature	: Not available.
рН	: Not applicable. [DIN EN 1262]
Viscosity	: Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
- · · · · · · · ·	

#### Solubility(ies)

Solubility(ies) :			
Media	Result		
cold water	Not soluble [OESO (TG 105)]		
Partition coefficient: n-octanol/ : water	Not applicable.		
Vapour pressure	Not available.		
Relative density	1.2 to 1.9 [ISO 8130-2/-3]		
Vapour density	Not applicable.		

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	7/14	AkzoNobel

SECTION 9: Physical and chemical properties		
Particle characteristics		
Median particle size		: Not available.
9.2 Other information		
Minimum ignition energy (m	J)	: 5 to 20
SECTION 10: Stability	y a	and reactivity
10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.
10.5 Incompatible materials	:	Reactive or incompatible with the following materials: oxidising materials
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

2.0 bia/2.4 di tart				-
3,9-bis(2,4-di-tert- butylphenoxy)LD50-2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecaneLD50	i0 Oral	Rat	5580 mg/kg	-

#### Conclusion/Summary

#### Acute toxicity estimates

N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	Skin - Severe irritant	Rabbit	-	0.5 gm	-
Conclusion/Summary	: Not available.	·			
<u>Sensitisation</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Data of issue/Data of rovision	. 18 4 2022	Vors	ion : 2.01		

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	8/14	AkzoNobel

# **SECTION 11: Toxicological information**

SECTION IT. TOXICO	biogical informatio	11	
Conclusion/Summary	: Not available.		
Carcinogenicity			
Conclusion/Summary	: Not available.		
Reproductive toxicity	- NI-6		
Conclusion/Summary	: Not available.		
Teratogenicity	. Net evellette		
Conclusion/Summary	: Not available.		
Specific target organ toxic Not available.	<u>aty (single exposure)</u>		
Specific target organ toxic Not available.	<u>ity (repeated exposure)</u>		
Aspiration hazard			
Not available.			
Information on likely routes	: Not available.		
of exposure	· Not available.		
Potential acute health effect	ts		
Eye contact	<ul> <li>Exposure to airborne of limits may cause irritat</li> </ul>	concentrations above statutory or reco	mmended exposure
Inhalation	•	concentrations above statutory or reco	mmended exposure
initiation		ion of the nose, throat and lungs.	
Skin contact	: No known significant e	ffects or critical hazards.	
Ingestion	: No known significant e	ffects or critical hazards.	
Symptoms related to the ph	ysical, chemical and toxic	ological characteristics	
Eye contact	: Adverse symptoms ma irritation redness	ay include the following:	
Inhalation	: Adverse symptoms ma	ay include the following:	
	respiratory tract irritation		
	coughing		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate effe	ects as well as chronic effe	ects from short and long-term expo	SURA
Short term exposure			
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health ef			
Not available.			
Conclusion/Summary	: Not available.		
General		d inhalation of dust may lead to chron	ic respiratory irritation
		-	
Date of issue/Date of revision	: 18-4-2023	<b>Version</b> : 2.01	Altzahlaha
Date of previous issue	: 31-1-2023	9/14	AkzoNobe

## **SECTION 11: Toxicological information**

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### 11.2 Information on other hazards

**11.2.1 Endocrine disrupting properties** 

Not available.

11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	EC50 97 mg/l	Algae	72 hours
	LC50 70.7 mg/l	Fish	96 hours

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

#### 12.3 Bioaccumulative potential

Not available.

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	10/14	AkzoNobel

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	<ul> <li>Do not allow to enter drains or watercourses.</li> <li>Dispose of according to all federal, state and local applicable regulations.</li> <li>If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.</li> <li>For further information, contact your local waste authority.</li> </ul>

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 02 01	waste coating powders	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	<ul> <li>Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.</li> </ul>	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

## **SECTION 14: Transport information**

14.7 Maritime transport in : Not applicable. bulk according to IMO instruments

Date of previous issue

:31-1-2023

## **SECTION 15: Regulatory information**

15.1 Safety, health and envir <u>UK (GB) /REACH</u>	onmental regulations/le	gislation specific for the	substance or mixture
Annex XIV - List of substa	nces subiect to authoris	ation	
Annex XIV None of the components a			
Substances of very high None of the components a			
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Other EU regulations			
VOC	: Not applicable.		
VOC for Ready-for-Use Mixture	: Not applicable.		
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed		
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed		
Ozone depleting substance Not listed.	<u>es (1005/2009/EU)</u>		
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)		
Persistent Organic Polluta Not listed.	<u>ints</u>		
Seveso Directive This product is not controller National regulations	d under the Seveso Direc	ive.	
Industrial use	own assessment of w	orkplace risks, as required sions of the national health	eet does not constitute the user's d by other health and safety and safety at work regulations apply
Date of issue/Date of revision	: 18-4-2023	Version	: 2.01
Date of previous issue	: 31-1-2023	12/14	AkzoNobel

12/14

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

YL357F/20KG Interpon D2525 GREY Matt

## **SECTION 15: Regulatory information**

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## 15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration</li> </ul>
	PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

	Classification		Justifi	ication
Aquatic Chronic 3, H412			Calculation method	
Full text of abbreviated H	statements			
<b>⊮</b> 372		Causes damage to o exposure.	organs through prolonge	d or repeated
H410			life with long lasting effe	ects.
H412			fe with long lasting effec	
Full text of classifications	[CLP/GHS]			
Aquatic Chronic 1 Aquatic Chronic 3 STOT RE 1		LONG-TERM (CHR	ONIC) AQUATIC HAZA ONIC) AQUATIC HAZA ORGAN TOXICITY - R Jory 1	RD - Category 3
Date of printing	: 18 April 2023	·		
Date of issue/ Date of revision	: 18 April 2023			
Date of previous issue	: 31 January 20	23		
Version	: 2.01			
Unique ID	:			
Date of issue/Date of revision	: 18-4-2023		Version : 2.01	
Date of previous issue	: 31-1-2023		13/14	AkzoNobel

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

YL357F/20KG Interpon D2525 GREY Matt

## **SECTION 16: Other information**

#### Notice to reader

#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision	: 18-4-2023	Version : 2.01	
Date of previous issue	: 31-1-2023	14/14	AkzoNobel