

SAFETY DATA SHEET

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SDS code : 8197713

YF651F/20KG

UFI : 4DSC-201W-N00V-YS0T

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Industrial use				
	Uses advised against			
Consumer use				

Product use : Electrostatic coating for use in industrial plants

1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited

Stoneygate Lane,

Felling, Gateshead. NE10 0JY United Kingdom

e-mail address of person : s

: sdsfellinguk@akzonobel.com

National contact

01 8092566 or 01 8379964

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : +44 (0)344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361f

Aquatic Chronic 3, H412

Date of issue/Date of revision: 21-11-2025Version: 6Date of previous issue: 7-5-20251/16AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage. H361f - Suspected of damaging fertility.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

or hearing protection.

P273 - Avoid release to the environment. P261 - Avoid breathing dust or mist.

Response : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal**

national or international regulations.

: Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) **Hazardous ingredients**

benzene-1,2,4-tricarboxylate

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvR

Date of issue/Date of revision : 21-11-2025 Version: 6

AkzoNobel Date of previous issue : 7-5-2025 2/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 2: Hazards identification

Other hazards which do not result in classification

May form combustible dust concentrations in air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	REACH #: 01-2120065788-39 EC: 940-592-6	≤5	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361f (oral) STOT RE 2, H373 (central nervous system (CNS)) (oral) Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1000 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention. If necessary, call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation occurs.

Date of issue/Date of revision: 21-11-2025Version: 6Date of previous issue: 7-5-20253/16AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 4: First aid measures

Ingestion

: Get medical attention. If necessary, call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

: Use dry chemical powder.

Unsuitable extinguishing

media

media

: Avoid high pressure media which could cause the formation of a potentially

explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision : 21-11-2025 Version : 6

Date of previous issue : 7-5-2025 4/16 AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 5: Firefighting measures

Hazards from the substance or mixture

: May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 21-11-2025 Version : 6

Date of previous issue :7-5-2025 5/16 AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

solutions

Recommendations : Not available. **Industrial sector specific** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance

AkzoNobel

: 21-11-2025 Date of issue/Date of revision Version: 6 Date of previous issue : 7-5-2025 6/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 8: Exposure controls/personal protection

documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	DNEL	Long term Inhalation	0.025 mg/ m³	Workers	Systemic
,	DNEL	Long term Dermal	0.05 mg/ kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	Fresh water	0.003 mg/l	Assessment Factors
	Marine water	0 mg/l	Assessment Factors
	Sewage Treatment Plant	32 mg/l	Assessment Factors
	Fresh water sediment	0.044 mg/kg dwt	Equilibrium Partitioning
		0.004 mg/kg dwt 0.007 mg/kg dwt	Equilibrium Partitioning Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of issue/Date of revision: 21-11-2025Version: 6Date of previous issue: 7-5-20257/16AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 8: Exposure controls/personal protection

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation,

suitable respiratory protective equipment should be used.

Environmental exposure controls

Body protection

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid.

Colour : Orange.

Odour : Odourless.

Odour threshold : Not available.

Melting point/freezing point : Not available.

Flammability : Not available.

Lower and upper explosion : 20 - 70 g/m3

limit

Auto-ignition temperature : 450 to 600°C (842 to 1112°F)

Decomposition temperature: Not available.

pH : Not applicable. [DIN EN 1262]

Viscosity : Kinematic (room temperature): Not applicable. [DIN EN ISO 3219]

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Date of issue/Date of revision : 21-11-2025 Version : 6

Date of previous issue : 7-5-2025 8/16 AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 9: Physical and chemical properties

Solubility(ies)

Media Result Not soluble [OECD (TG 105)] cold water

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

: Not available.

Relative density

: 1.2 to 1.9 [ISO 8130-2/-3]

Vapour density

: Not applicable.

Particle characteristics

Median particle size

: Not available.

Percentage of particles with

aerodynamic diameter ≤ 10

9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

Fundamental burning velocity

: Not applicable.

SADT Heat of combustion : Not available. : Not available.

Aerosol product

Type of aerosol

: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust

accumulation.

10.5 Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision : 21-11-2025 Version: 6

AkzoNobel Date of previous issue : 7-5-2025 9/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	LD50 Oral	Rat	1000 mg/kg	-

Conclusion/Summary

: Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene- 1,2,4-tricarboxylate	21739.1	N/A	N/A	N/A	N/A
	1000	N/A	N/A	N/A	N/A

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitisation

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	-	Positive	-	Rat - Male, Female	Oral: 3 mg/kg	-

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available. **Specific target organ toxicity (single exposure)**

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	Category 2		central nervous system (CNS)

Aspiration hazard

Date of issue/Date of revision : 21-11-2025 Version : 6

Date of previous issue : 7-5-2025 10/16 AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 11: Toxicological information

Not available.

Information on likely routes: Not available.

of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contact : May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

: Adverse symptoms may include the following: Ingestion

stomach pains

reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Date of issue/Date of revision : 21-11-2025 Version: 6

AkzoNobel Date of previous issue : 7-5-2025 11/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 11: Toxicological information

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity: Suspected of damaging fertility.

11.2 Information on other hazards

11.2.1Endocrine disrupting properties

Not available.

11.2.20ther information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Date of issue/Date of revision: 21-11-2025Version: 6Date of previous issue: 7-5-202512/16AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 13: Disposal considerations

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision : 21-11-2025 Version: 6 **AkzoNobel** Date of previous issue : 7-5-2025 13/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

14.7 Transport in bulk according to IMO instruments

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Synthetic polymer microparticles - Designation 78

Generic identity of

: Refer to Product Data Sheet.

polymer(s)

Total percentage of

: 100%

synthetic polymer microparticles

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Other EU regulations

VOC : Not applicable. : Not applicable.

VOC for Ready-for-Use Mixture

: Not listed Industrial emissions

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

Active substances

Date of issue/Date of revision : 21-11-2025 Version: 6

AkzoNobel Date of previous issue : 7-5-2025 14/16

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 15: Regulatory information

Ingredient name

calcium oxide

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361f	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 21-11-2025	Version : 6	
Date of previous issue	: 7-5-2025	15/16	AkzoNobel

YF651F INTERPON ACE2010 LOW-E R2002 SN92 20KG

SECTION 16: Other information

Acute Tox. 4
Aquatic Chronic 2
Aquatic Chronic 3
Eye Dam. 1
Repr. 2
Skin Irrit. 2
Skin Sens. 1

ACUTE TOXICITY - Category 4

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2

SKIN SENSITISATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 2

Date of printing

Date of issue/Date of

revision

STOT RE 2

: 21-11-2025: 21-11-2025

Date of previous issue : 7-5-2025

Version : 6 Unique ID :

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 21-11-2025 Version : 6

Date of previous issue : 7-5-2025 16/16 AkzoNobel