

SAFETY DATA SHEET

JM071QF INT 600 RAL 8004 COPPER BROWN U1578-1

Section 1. Identification

Product identifier SDS code

 : JM071QF INT 600 RAL 8004 COPPER BROWN U1578-1
 : 8205521 JM071QF/25KG

Relevant identified uses of the substance or mixture and uses advised against

	Recommended use	
Restrictions on use		
Product use	: Electrostatic coating for use in industrial plants	
Supplier's details		
Akzo Nobel Coat 150 Columbia Sti Reading, PA 196 1-610-372-3600	reet 110 Woodbine Downs Blvd.	
Emergency telephone number (with hours of operation)	: CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted) Domestic Poison Control Center Customer Service +1 (800) 854-6813 24 hours	
Section 2. Haza	rd identification	
Classification of the substance or mixture	: COMBUSTIBLE DUSTS - Category 1 ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	
<u>GHS label elements</u> Hazard pictograms		

Signal word

: Danger



Section 2. Hazard identification

Hazard statements	: 📕 armful if swallowed.
	May cause an allergic skin reaction.
	Causes serious eye damage.
	May cause genetic defects.
	Suspected of causing cancer. May damage fertility or the unborn child.
	May cause damage to organs through prolonged or repeated exposure.
	May form combustible dust concentrations in air.
Precautionary statements	
Prevention	: Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	% (w/w)	CAS number
7,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	≥5 - ≤10	2451-62-9
titanium dioxide	≥0.1 - ≤1	13463-67-7
strontium sulphate	≥0.1 - ≤1	7759-02-6

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact	flush eyes with plenty of Check for and remove a	mediately. Call a poison center or ph water, occasionally lifting the upper a iny contact lenses. Continue to rinse treated promptly by a physician.	and lower eyelids.
Inhalation	victim to fresh air and ke suspected that fumes ar or self-contained breath respiratory arrest occurs It may be dangerous to resuscitation. If uncons	mediately. Call a poison center or pheep at rest in a position comfortable for re still present, the rescuer should we ing apparatus. If not breathing, if brea s, provide artificial respiration or oxyge the person providing aid to give mouth cious, place in recovery position and g an open airway. Loosen tight clothing	or breathing. If it is ar an appropriate mask athing is irregular or if en by trained personnel. h-to-mouth get medical attention
Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	2/13	AkzoNobel

Section 4. First-aid measures

	belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact :	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion :	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health eff	ects		
Eye contact	: Causes serious eye da	amage.	
Inhalation		concentrations above statutory or rec ion of the nose, throat and lungs.	commended exposure
Skin contact	: May cause an allergic	skin reaction.	
Ingestion	: Harmful if swallowed.		
<u>Over-exposure signs/sym</u>	nptoms		
Eye contact	: Adverse symptoms ma pain watering redness	ay include the following:	
Inhalation	: Adverse symptoms ma respiratory tract irritatio coughing reduced fetal weight increase in fetal deaths skeletal malformations	s	
Skin contact	: Adverse symptoms ma pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations	5	
Ingestion	: Adverse symptoms ma stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	5	
Indication of immediate me	edical attention and special	treatment needed, if necessary	
Notes to physician		decomposition products in a fire, sy nay need to be kept under medical s	
Specific treatments	: No specific treatment.		
Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	3/13	AkzoNobel

Section 4. First-aid measures

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it
is suspected that fumes are still present, the rescuer should wear an appropriate
mask or self-contained breathing apparatus. It may be dangerous to the person
providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing
thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill		Move containers from spill area. Use spark-proof tools and explosion-proof

Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof
	equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with
	equipment fitted with a HEPA filter and place in a closed, labeled waste container.
	Place spilled material in a designated, labeled waste container. Dispose of via a
	licensed waste disposal contractor.

Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	4/13	AkzoNobel

Section 6. Accidental release measures

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits	
1,3,5-tris(oxiranylmethyl)-1,3	,5-triazine-2,4,6(1H,3H,5H)-trione	8 hrs OEL: 0.05 mg, CA British Columbia 3/2022). [1,3,5-Trigly Skin sensitizer. TWA: 0.05 mg/m ³ 8 CA Ontario Provinci [1,3,5-Triglycidyl-s-1 TWA: 0.05 mg/m ³ 8	a Provincial (Canada, /cidyl-s-triazinetrione] hours. ial (Canada, 6/2019). triazinetrione] hours. ial (Canada, 6/2021). urate]
Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	5/13	AkzoNobel

Section 8. Exposure controls/personal protection

	CA Saskatchewan Provincial (Canada, 7/2013). STEL: 0.15 mg/m ³ 15 minutes. TWA: 0.05 mg/m ³ 8 hours.
titanium dioxide	 CA British Columbia Provincial (Canada, 3/2022). TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 6/2021). TWAEV: 10 mg/m³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). Skin sensitizer. 8 hrs OEL: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. Form: total dust CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.

controls	vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Section 0 Dhysic	al and chamical properties and safety

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

: Solid. [Powder.]
: Brown.
: Odorless.
: Not available.
: Not applicable. [DIN EN 1262]
: Not available.
: Not available.
: Closed cup: Not applicable. [Pensky-Martens]
: Not available.
: 20 - 70 g/m3
: Not available.
: Not applicable.
: 1.2 to 1.9 [ISO 8130-2/-3]
:

Media		Result	
cold water		Not soluble [OESO (TG 105)]	
Partition coefficient: n- octanol/water	: Not	applicable.	
Auto-ignition temperature	: 450	to 600°C (842 to 1112°F)	
Decomposition temperature	: Not	available.	
Minimum ignition energy (mJ)	: 5 to	20	
Viscosity		ematic (room temperature): Not applicable. [DIN EN ISO 3219] ematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]	
Particle characteristics Median particle size	: Not	available.	



Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	LC50 Inhalation Dusts and mists	Mouse	2000 mg/m³	4 hours
	LC50 Inhalation Dusts and mists	Rat	650 mg/m³	4 hours
	LD50 Oral	Rat	188 mg/kg	-
	LD50 Oral	Rat	222 mg/kg	-
	LD50 Oral	Rat	138 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	Eyes - Severe irritant	Rabbit	-	100 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	IARC	NTP	ACGIH
titanium dioxide	2B	-	A4

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	8/13	AkzoNobel

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name			Category	Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione		Category 2	-	-	
Aspiration hazard Not available.				<u>.</u>	
Information on the likely routes of exposure	:	Not available.			
Potential acute health effects	2				
Eye contact	:	Causes serious eye dama	ge.		
Inhalation	:	Exposure to airborne conc limits may cause irritation			mmended exposure
Skin contact	:	May cause an allergic skir	reaction.		
Ingestion	:	Harmful if swallowed.			
Symptoms related to the phy	sic	cal, chemical and toxicolo	gical character	<u>istics</u>	
Eye contact		Adverse symptoms may ir pain watering redness	-		
Inhalation	:	Adverse symptoms may in respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations	iclude the follow	ing:	
Skin contact	:	Adverse symptoms may in pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations	clude the follow	ing:	
Ingestion	:	Adverse symptoms may in stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	clude the follow	ing:	
Delayed and immediate effec	ts	and also chronic effects f	rom short and	long term expos	ure
Short term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Long term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Date of issue/Date of revision		: 2/7/2023	Ve	rsion :2	
Date of previous issue		: 12/12/2022	9/1	13	AkzoNobe

Section 11. Toxicological information

Potential chronic health effects

Not available.	
General	: May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: May cause genetic defects.
Reproductive toxicity	: May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
₱5/JM071QF/USA RAL8004 COPRBRN U1578-1/B 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	1890.7 100	N/A N/A	N/A N/A	N/A N/A	9.5 0.5

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential



Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	-0.8	-	low

<u>Mobility in soil</u>

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible.
Disposal of this product, solutions and any by-products should at all times comply
with the requirements of environmental protection and waste disposal legislation and
any regional local authority requirements. Dispose of surplus and non-recyclable
products via a licensed waste disposal contractor. Waste should not be disposed of
untreated to the sewer unless fully compliant with the requirements of all authorities
with jurisdiction. Waste packaging should be recycled. Incineration or landfill
should only be considered when recycling is not feasible. This material and its
container must be disposed of in a safe way. Care should be taken when handling
emptied containers that have not been cleaned or rinsed out. Empty containers or
liners may retain some product residues. Avoid dispersal of spilled material and
runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments



Section 15. Regulatory information

Canadian NPRI: None of the components are listed.CEPA Toxic substances: None of the components are listed.Inventory list: At least one component is not listed.Canada: At least one component is not listed.United States: All components are active or exempted.	Canadian lists	
Inventory listCanada: At least one component is not listed.	Canadian NPRI	: None of the components are listed.
Canada : At least one component is not listed.	CEPA Toxic substances	: None of the components are listed.
	Inventory list	
United States : All components are active or exempted.	Canada	: At least one component is not listed.
	United States	: All components are active or exempted.

Section 16. Other information

<u>History</u>	
Date of printing	: 7 February 2023
Date of issue/ Date of revision	: 7 February 2023
Date of previous issue	: 12 December 2022
Version	: 2
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS - Category 1	On basis of test data
ACUTE TOXICITY (oral) - Category 4	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

✓ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Date of issue/Date of revision	: 2/7/2023	Version : 2	
Date of previous issue	: 12/12/2022	12/13	AkzoNobel

JM071QF INT 600 RAL 8004 COPPER BROWN U1578-1

Section 16. Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

