

SAFETY DATA SHEET

ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

N100GF C
208179

LAAS Schwarz Satin Smooth Interpon 620 ON100GF /20KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
ndustrial use		
	Uses advised against	
Al other uses		
Product use	: Electrostatic coating for use in industrial plants	

: Electrostatic coating for use in industrial plants

1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. **NE10 0JY** United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS National contact 01 8092566 or 01 8379964 1.4 Emergency telephone number National advisory body/Poison Centre Telephone number : +44 (0)344 892 0111

: +44 0191 469 6111
:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

: Mixture **Product definition** Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Eve Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361f Aquatic Chronic 3, H412 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	1/15	AkzoNobel

ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Øbtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment. Avoid breathing dust or mist.
Response	:	F exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	Sispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
not result in classification	•	· · · · · · · · · · · · · · · · · · ·



SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene- 1,2,4-tricarboxylate	REACH #: 01-2120065788-39 EC: 940-592-6	≥3 - ≤5	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361f STOT RE 2, H373 (central nervous system (CNS)) (oral) Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

.

Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation: Set medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.Skin contact: Set medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.Ingestion: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or wai	Eye contact	flush eyes with plenty of v Check for and remove ar	Set medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.	
Ingestion: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting 	Inhalation	victim to fresh air and kee suspected that fumes are or self-contained breathir respiratory arrest occurs, It may be dangerous to th resuscitation. If unconsc immediately. Maintain ar	ep at rest in a position comfortable for b still present, the rescuer should wear a ng apparatus. If not breathing, if breathin provide artificial respiration or oxygen b ne person providing aid to give mouth-to ious, place in recovery position and get	reathing. If it is an appropriate mask ng is irregular or if by trained personnel. p-mouth medical attention
mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.Date of issue/Date of revision:16-12-2022Version:2	Skin contact	plenty of soap and water. contaminated clothing the Continue to rinse for at le by a physician. In the eve	Remove contaminated clothing and sh proughly with water before removing it, ast 10 minutes. Chemical burns must ent of any complaints or symptoms, avo	noes. Wash or wear gloves. oe treated promptly id further exposure.
AlveNebel	Ingestion	mouth with water. Remo exposed person is consc exposed person feels sic unless directed to do so l be kept low so that vomit promptly by a physician. If unconscious, place in r Maintain an open airway.	ve dentures if any. If material has been ious, give small quantities of water to du k as vomiting may be dangerous. Do n by medical personnel. If vomiting occur does not enter the lungs. Chemical bu Never give anything by mouth to an un- ecovery position and get medical attent	a swallowed and the rink. Stop if the ot induce vomiting s, the head should rns must be treated conscious person. ion immediately.
Date of previous issue: 15-12-20223/15AkzoNobel	Date of issue/Date of revision	: 16-12-2022	Version : 2	
	Date of previous issue	: 15-12-2022	3/15	AkzoNobel

SECTION 4: First aid measures Protection of first-aiders * No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include the following: pain watering redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Freat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

-	-
5.1 Extinguishing media	
Suitable extinguishing media	: 🗾 Se dry chemical powder.
Unsuitable extinguishing media	: Kooid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	4/15	AkzoNobel

ting measures
: May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
: Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
: Fre-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ntective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: Fspecialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	containment and cleaning up
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	Let on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Fating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupationa	<u>l exposure</u>	<u>limits</u>
No experies	limit volue l	00110

Recommended monitoring		ngredients with exposure limits, perso	nal, workplace
procedures	of the ventilation or othe protective equipment. R the following: European the assessment of expo- limit values and measure atmospheres - Guide for of exposure to chemical	I monitoring may be required to detern r control measures and/or the necessive ference should be made to monitorin Standard EN 689 (Workplace atmosp sure by inhalation to chemical agents ement strategy) European Standard E the application and use of procedures and biological agents) European Stat s - General requirements for the performance of the performance of the perfo	ity to use respiratory ng standards, such as oheres - Guidance for for comparison with EN 14042 (Workplace s for the assessment ndard EN 482
Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	6/15	AkzoNobel

SECTION 8: Exposure controls/personal protection

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Repropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



SECTION 9: Physical and chemical properties

÷

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Solid. [Powder.]
Colour	: Black.
Odour	: Ødourless.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: Not applicable.
Flash point	: Йosed cup: Not applicable. [Pensky-Martens]
Auto-ignition temperature	: ₩50 to 600°C (842 to 1112°F)
Decomposition temperature	: Not available.
рН	: Not applicable. [DIN EN 1262]
Viscosity	: K inematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies)

Media	Result
old water	Not soluble [OESO (TG 105)]
Partition coefficient: n-octawater	nol/ : Not applicable.
/apour pressure	: Not available.
Relative density	: 7.2 to 1.9 [ISO 8130-2/-3]
/apour density	: Not applicable.
Particle characteristics	
Median particle size	: Not available.

9.2 Other information

Minimum ignition energy (mJ) : 57 to 20

SECTION 10: Stabili	ty and reactivity		
10.1 Reactivity	: No specific test data re	lated to reactivity availabl	e for this product or its ingredients.
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Moder normal condition	s of storage and use, ha	zardous reactions will not occur.
10.4 Conditions to avoid	(spark or flame). Take To avoid fire or explosi	precautionary measures on, dissipate static electri	oid all possible sources of ignition against electrostatic discharges. city during transfer by earthing and erring material. Prevent dust
Date of issue/Date of revision	: 16-12-2022	Version	
Date of previous issue	: 15-12-2022	8/15	AkzoNobel

ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 10: Stability and reactivity

10.5 Incompatible materials	eactive or incompatible with the following materials: idising materials	
10.6 Hazardous decomposition products	nder normal conditions of storage and use, hazardous do ould not be produced.	ecomposition products

SECTION 11: Toxicological information

11.1 Information on toxicol	ogical effects
Acute toxicity	
Conclusion/Summary	: Not available.
Irritation/Corrosion	
Conclusion/Summary	: Not available.
Sensitisation	
Conclusion/Summary	: Not available.
<u>Mutagenicity</u>	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Poproductivo toxicity	

Reproductive toxicity

Reaction mass of bis -					
(2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene- 1,2,4-tricarboxylate	-	Positive	Rat - Male, Female	Oral: 3 mg/kg	-

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of bis (2,3-epoxypropyl) terepthalate and tris (oxiranylmethyl) benzene-1,2,4-tricarboxylate	Category 2		central nervous system (CNS)

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact	: 🗭 auses serious eye damage.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: May cause an allergic skin reaction.

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	9/15	AkzoNobel

	ON100GF CLAAS Schwarz Satin Smooth Interpon 620
SECTION 11: Toxico	logical information
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	 Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
-	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff Not available.	ects
Conclusion/Summary	: Not available.
General	 Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility.
11.2 Information on other ha 11.2.1 Endocrine disrupting	

Not available.

11.2.2 Other information

Not available.



ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: $\overline{\mathbf{r}}$ he classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	11/15	AkzoNobel

SECTION 13: Disposal considerations

	Waste code	Waste designation
	E WC 08 02 01	waste coating powders
<u>P</u>	ackaging	
	Methods of disposal	Phe generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
	Disposal considerations	 Ising information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
S	pecial precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name			
14.3 Transport hazard class(es)			
14.4 Packing group		F	
14.5 Environmental hazards	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not applicable. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	:15-12-2022	12/15	AkzoNobel

SECTION 15: Regulatory information

SECTION 15: Regula	tory information
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: Not available.
VOC for Ready-for-Use Mixture	: Not applicable.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substance Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P Not listed.	I <u>C) (649/2012/EU)</u>
Persistent Organic Polluta Not listed.	<u>nts</u>
Seveso Directive This product is not controlled National regulations Industrial use	 I under the Seveso Directive. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations Chemical Weapon Conventi Not listed.	on List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on F Not listed.	Persistent Organic Pollutants
Rotterdam Convention on P Not listed.	rior Informed Consent (PIC)
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
Inventory list Eurasian Economic Union	: Russian Federation inventory : Not determined.

Date of issue/Date of revision	: 16-12-2022	Version : 2	
Date of previous issue	: 15-12-2022	13/15	AkzoNobel

ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 15: Regulatory information

15.2 Chemical safety assessment

y : N

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information	that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
E ye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361f	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

⊮ 302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Repr. 2 Skin Irrit. 2 Skin Sens. 1 STOT RE 2	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of printing	: 16 December 2022
Date of issue/ Date of revision	: 16 December 2022
Date of previous issue	: 15 December 2022

Version	
Unique ID	
Notice to reader	

: 2 :



ON100GF CLAAS Schwarz Satin Smooth Interpon 620

SECTION 16: Other information

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

