

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

SK720JR INTD1036 SATXPRO R6020 SN70 20KG

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: SK720JR INTD1036 SATXPRO R6020 SN70 20KG
SDS code	: 8218153 SK720JR/20KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Industrial use		
Uses advised against		
All other uses		
Product use	: Electrostatic coating for use in industrial plants	

1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. NE10 0JY United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS <u>National contact</u> 01 8092566 or 01 8379964 1.4 Emergency telephone number <u>National advisory body/Poison Centre</u>

Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111
Hours of operation	:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	1/14	AkzoNobel

SECTION 2: Hazards identification

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form combustible dust concentrations in air.

SECTION 3: Composition/information on ingredients

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	EC: 247-952-5 CAS: 26741-53-7	≤1	Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Туре</u>

[1] Substance classified with a health or environmental hazard

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	2/14	AkzoNobel

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use dry chemical powder.
Unsuitable extinguishing media	:	Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	3/14	AkzoNobel

SECTION 5: Firefighting measures			
Hazards from the substance or mixture	: May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides		
5.3 Advice for firefighters			
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.		
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)Recommendations: Not available.Industrial sector specific: Not available.solutions

SECTION 8: Exposure controls/personal protection

: 20-2-2023

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Date of previous issue

.

Occupational exposure limits

No exposure limit value knowr	1.	
Recommended monitoring procedures	atmosphere or bid of the ventilation of protective equipm the following: Eur the assessment of limit values and m atmospheres - Gu of exposure to ch (Workplace atmos for the measurem	tains ingredients with exposure limits, personal, workplace ological monitoring may be required to determine the effectiveness or other control measures and/or the necessity to use respiratory ent. Reference should be made to monitoring standards, such as ropean Standard EN 689 (Workplace atmospheres - Guidance for f exposure by inhalation to chemical agents for comparison with neasurement strategy) European Standard EN 14042 (Workplace uide for the application and use of procedures for the assessment emical and biological agents) European Standard EN 482 spheres - General requirements for the performance of procedures ent of chemical agents) Reference to national guidance ethods for the determination of hazardous substances will also be
Date of issue/Date of revision	: 22-8-2023	Version : 2.03
Date of issue/Date of revision	. 22-0-2023	

5/14

AkzoNobe

SECTION 8: Exposure controls/personal protection

<u></u>	1	i	t		i
Product/ingredient name	Туре	Exposure	Value	Population	Effects
3,9-bis(2,4-di-tert-butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5]undecane	DNEL	Long term Oral	0.39 mg/ kg bw/day	General population	Systemic
-,	DNEL	Long term Dermal	0.39 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.68 mg/m ³		Systemic
	DNEL	Long term Dermal	0.78 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.75 mg/m ³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls			
Appropriate engineering controls	vapour or mist, use proc engineering controls to recommended or statuto	ventilation. If user operations generate dust, fumes, gas, ess enclosures, local exhaust ventilation or other eep worker exposure to airborne contaminants below any ry limits. The engineering controls also need to keep gas ations below any lower explosive limits. Use explosion- ent.	
Individual protection meas	<u>sures</u>		
Hygiene measures	before eating, smoking a Appropriate techniques Wash contaminated clot	and face thoroughly after handling chemical products, and using the lavatory and at the end of the working period should be used to remove potentially contaminated clothin hing before reusing. Ensure that eyewash stations and a to the workstation location.	
Eye/face protection	assessment indicates th gases or dusts. If conta unless the assessment i	ng with an approved standard should be used when a risk is is necessary to avoid exposure to liquid splashes, mists ct is possible, the following protection should be worn, ndicates a higher degree of protection: safety glasses wit g conditions cause high dust concentrations to be produce	s, th
Skin protection			
Hand protection	be worn at all times whe this is necessary. Consi check during use that th should be noted that the different for different glo	ervious gloves complying with an approved standard shoul in handling chemical products if a risk assessment indicate dering the parameters specified by the glove manufacture e gloves are still retaining their protective properties. It time to breakthrough for any glove material may be we manufacturers. In the case of mixtures, consisting of protection time of the gloves cannot be accurately	es
	protection class of 6 (bre recommended. Recommended. Recommended When only brief contact (breakthrough time >30 Recommended gloves:	Lently repeated contact may occur, a glove with a eakthrough time >480 minutes according to EN374) is nended gloves: Viton $\textcircled{0}$ or Nitrile, thickness \geq 0.38 mm. is expected, a glove with protection class of 2 or higher minutes according to EN374) is recommended. Nitrile, thickness \geq 0.12 mm. ed regularly and if there is any sign of damage to the glove	e
	The performance or effe chemical damage and p	ctiveness of the glove may be reduced by physical/ por maintenance.	
Date of issue/Date of revision	: 22-8-2023	Version : 2.03	

SECTION 8: Exposure controls/personal protection

	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Solid. [Powder.]
Colour	:	Green.
Odour	:	Odourless.
Odour threshold	:	Not available.
Melting point/freezing point	:	Not available.
Flammability	:	Not available.
Lower and upper explosion limit	:	20 - 70 g/m3
Auto-ignition temperature	:	450 to 600°C (842 to 1112°F)
Decomposition temperature	:	Not available.
рН	:	Not applicable. [DIN EN 1262]
Viscosity	:	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
Solubility(ies)	:	
Media		Result
cold water		Not soluble [OESO (TG 105)]
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	:	Not available.
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]
Vapour density	:	Not applicable.
Particle characteristics		
		Net evellete
Median particle size	- 1	Not available.

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	7/14	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SK720JR INTD1036 SATXPRO R6020 SN70 20KG

SECTION 9: Physical and chemical properties 9.2 Other information Minimum ignition energy (mJ) : 5 to 20 SECTION 10: Stability and reactivity 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients. 10.2 Chemical stability : The product is stable. 10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation. 10.5 Incompatible materials : Reactive or incompatible with the following materials:

10.6 Hazardous : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

oxidising materials

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	LD50 Oral	Rat	5580 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3,9-bis(2,4-di-tert- butylphenoxy) -2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane	Skin - Severe irritant	Rabbit	-	0.5 gm	-
Conclusion/Summary	: Not available.				
Sensitisation					
Conclusion/Summary	: Not available.				
Mutagenicity					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Date of issue/Date of revision	: 22-8-2023	Vers	sion : 2.03	}	
Date of previous issue	: 20-2-2023	8/14	l		AkzoNobel

	SK720JR INTD1036 SA	1XPRO R6020 SN70 20KG	
SECTION 11: Toxico	logical information	l	
Reproductive toxicity			
Conclusion/Summary	: Not available.		
<u>Teratogenicity</u>			
Conclusion/Summary	: Not available.		
Specific target organ toxici			
Not available.	y territor entry		
Specific target organ toxici	<u>ty (repeated exposure)</u>		
Not available.			
Aspiration hazard			
Not available.			
Information on likely routes	. Not available		
of exposure	. NUL avaliable.		
Potential acute health effects	•		
	_	populations above statistical as a second	mondod ovrogers
Eye contact	limits may cause irritation	oncentrations above statutory or recom on of the eves.	menueu exposure
Inhalation	,	procentrations above statutory or recom	mended exposure
	•	on of the nose, throat and lungs.	
Skin contact	: No known significant ef		
Ingestion	: No known significant ef		
Symptoms related to the phy	sical, chemical and toxic	ological characteristics	
Eye contact	: Adverse symptoms ma		
	irritation	,	
	redness		
Inhalation	: Adverse symptoms ma		
	respiratory tract irritatio	1	
Skin contact	coughing		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delaved and immediate effect	cts as well as chronic effe	cts from short and long-term exposi	ıre
Short term exposure			<u></u>
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Potential chronic health eff			
Not available.	<u></u>		
Conclusion/Summary	: Not available.		
General		inhalation of dust may lead to chronic	respiratory irritation.
Carcinogenicity	: No known significant ef	fects or critical hazards.	
Mutagenicity	: No known significant ef	fects or critical hazards.	
Reproductive toxicity	: No known significant ef	fects or critical hazards.	
Data of ionus (Data of south to s			
Date of issue/Date of revision	: 22-8-2023	Version : 2.03	

Date of previous issue: 20-2-2023version: 2.03AkzoNobel

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

mg/l	Algae	72 hours
7 mg/l	Fish	96 hours
	7 mg/l	7 mg/l Fish

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	10/14	AkzoNobel

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

SECTION 14: Transport information

14.6 Special precautions for user		Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
-----------------------------------	--	---

14.7 Maritime transport in : Not applicable. bulk according to IMO instruments

Date of previous issue

:20-2-2023

SECTION 15: Regulatory information

•	ronmental regulations/legis	lation specific for the substance of	or mixture
UK (GB) /REACH	waaa ay biaat ta ay thaying t		
Annex XIV	inces subject to authorisat		
None of the components a	ara liatad		
Substances of very high			
None of the components a	are listed.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Other EU regulations			
VOC	: Not applicable.		
VOC for Ready-for-Use Mixture	: Not applicable.		
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed		
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed		
Ozone depleting substance Not listed.	<u>ces (1005/2009/EU)</u>		
Prior Informed Consent (P Not listed.	<u>PIC) (649/2012/EU)</u>		
Persistent Organic Polluta Not listed.	ants		
Seveso Directive			
This product is not controlle	d under the Seveso Directive	ð.	
National regulations			
International regulations			
Chemical Weapon Convent	tion List Schedules I, II & II	Chemicals	
Not listed.			
Montreal Protocol			
Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	12/14	AkzoNobel

12/14

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SK720JR INTD1036 SATXPRO R6020 SN70 20KG

SECTION 15: Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety : No Chemical Safety Asse	essment has been carried
--	--------------------------

assessment

out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H410 H412		Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.		
				Full text of classifications
Aquatic Chronic 1		LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1		
Aquatic Chronic 3		LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3		
Date of printing	: 22-8-2023			
Date of issue/ Date of revision	: 22-8-2023			
Date of previous issue	: 20-2-2023			
Version	: 2.03			
Unique ID	:			
Notice to reader				
FOR PROFESSIONAL USE	ONLY			

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality

Date of issue/Date of revision	: 22-8-2023	Version : 2.03	
Date of previous issue	: 20-2-2023	13/14	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SK720JR INTD1036 SATXPRO R6020 SN70 20KG

SECTION 16: Other information

or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

