

SAFETY DATA SHEET

HGF03R Resicoat R4-ES

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : HGF03R Resicoat R4-ES

SDS code : 8236212

HGF03R/25KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses			
ndustrial use				
	Uses advised against			
All other uses				

Product use : Electrostatic coating for use in industrial plants

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Powder Coatings GmbH

Site Reutlingen:

Akzo Nobel Powder Coatings GmbH

Markwiesenstr. 50 72770 Reutlingen

Germany

T: +49 7121 519-0 F: +49 7121 519-199 www.resicoat.com

e-mail address of person responsible for this SDS

: resicoat@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : +44 (0)344 892 0111

<u>Supplier</u>

Telephone number : Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

Hours of operation :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

HGF03R Resicoat R4-ES

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms







Signal word : Danger

Hazard statements : May cause an allergic skin reaction.

Causes serious eye damage.

May damage fertility.

Precautionary statements

Prevention : ∅btain special instructions before use. Wear protective gloves, protective clothing,

eye protection, face protection, or hearing protection. Avoid breathing dust or mist.

Response : IF exposed or concerned: Get medical advice or attention. Take off contaminated

clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazardous ingredients : Sphenol A

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: May form combustible dust concentrations in air. May cause endocrine disruption.

Date of issue/Date of revision : 26-5-2023 Version : 2

Date of previous issue : 25-11-2022 2/18 AkzoNobel

HGF03R Resicoat R4-ES

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
sphenol A	EC: 201-245-8 CAS: 80-05-7	≤5	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335	-	[1] [2] [3]
2-methylimidazole	EC: 211-765-7 CAS: 693-98-1	<0.3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Carc. 2, H351 Repr. 1B, H360Df See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Det medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

 Date of issue/Date of revision
 : 26-5-2023
 Version
 : 2

 Date of previous issue
 : 25-11-2022
 3/18

AkzoNobel

HGF03R Resicoat R4-ES

SECTION 4: First aid measures

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains 4,4'-isopropylidenediphenol. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

: Use dry chemical powder.

Unsuitable extinguishing

media

media

: Avoid high pressure media which could cause the formation of a potentially

explosible dust-air mixture.

Date of issue/Date of revision : 26-5-2023 Version : 2

Date of previous issue : 25-11-2022 4/18 AkzoNobel

HGF03R Resicoat R4-ES

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : May form explosible dust-air mixture if dispersed.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other

: See Section 1 for emergency contact information.

sections

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 26-5-2023 Version : 2

AkzoNobel Date of previous issue : 25-11-2022 5/18

HGF03R Resicoat R4-ES

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

solutions

Recommendations : Not available.

Industrial sector specific : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 2 mg/m³ 8 hours. Form: inhalable dust

AkzoNobel

Date of issue/Date of revision: 26-5-2023Version: 2Date of previous issue: 25-11-20226/18

HGF03R Resicoat R4-ES

SECTION 8: Exposure controls/personal protection

procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
ĭsphenol A	DNEL	Short term Dermal	0.0019 mg/	General	Systemic
			kg bw/day	population	-
	DNEL	Long term Dermal	0.0019 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Oral	0.004 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Oral	0.004 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Dermal	0.031 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term Dermal	0.031 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Short term	1 mg/m³	General	Local
		Inhalation		population	
	DNEL	Long term	1 mg/m³	General	Local
		Inhalation		population	
	DNEL	Short term	1 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term	1 mg/m³	General	Systemic
		Inhalation	_ , ,	population	
	DNEL	Short term	2 mg/m³	Workers	Local
		Inhalation	_ , ,		
	DNEL	Long term	2 mg/m³	Workers	Local
	5	Inhalation			
	DNEL	Short term	2 mg/m³	Workers	Systemic
	DATE	Inhalation	0 / 3	\A/ I	
	DNEL	Long term	2 mg/m³	Workers	Systemic
	5	Inhalation			
2-methylimidazole	DNEL	Long term Oral	0.02 mg/	General	Systemic
	DAIE	 	kg bw/day	population	01
	DNEL	Long term Dermal	0.04 mg/	Workers	Systemic
	DAIE	1	kg bw/day	107	01
	DNEL	Long term	0.3 mg/m ³	Workers	Systemic
		Inhalation			

PNECs

No PNECs available

8.2 Exposure controls

Date of issue/Date of revision : 26-5-2023 Version : 2 **AkzoNobel** Date of previous issue : 25-11-2022 7/18

HGF03R Resicoat R4-ES

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 26-5-2023 Version : 2

Date of previous issue : 25-11-2022 8/18 AkzoNobel

HGF03R Resicoat R4-ES

SECTION 8: Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid. [Powder.]

Colour : Red. Odour : Odourless. **Odour threshold** : Not available. : Not available. Melting point/freezing point Initial boiling point and : Not available.

boiling range

Flammability Lower and upper explosion

limit

: Not available. : 20 - 70 g/m3

: Closed cup: Not applicable. [Pensky-Martens] Flash point

: 450 to 600°C (842 to 1112°F) **Auto-ignition temperature**

Decomposition temperature : Not available.

рΗ : Not applicable. [DIN EN 1262]

: Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] **Viscosity**

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies)

Media	Result
<mark>ø</mark> old water	Not soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

: Not available. Vapour pressure

Relative density : 1.2 to 1.9 [ISO 8130-2/-3]

: 0

Vapour density : Not applicable.

Particle characteristics

Median particle size : Not available.

Percentage of particles with

aerodynamic diameter ≤ 10

μm

9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

Date of issue/Date of revision : 26-5-2023 Version : 2

AkzoNobel Date of previous issue : 25-11-2022 9/18

HGF03R Resicoat R4-ES

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.

10.5 Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
písphenol A	LD50 Dermal	Rabbit	3 mL/kg	-
	LD50 Intraperitoneal	Mouse	150 mg/kg	-
	LD50 Intraperitoneal	Rat	200 mg/kg	-
	LD50 Oral	Guinea pig	4 g/kg	-
	LD50 Oral	Guinea pig	4000 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
	LD50 Oral	Mouse	2500 mg/kg	-
	LD50 Oral	Mouse	2500 mg/kg	-
	LD50 Oral	Rabbit	2230 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Oral	Rat	4240 mg/kg	-
	LD50 Oral	Rat	3250 mg/kg	-
	LD50 Subcutaneous	Rabbit	3000 mg/kg	-
2-methylimidazole	LD50 Intraperitoneal	Mouse	480 mg/kg	-
	LD50 Oral	Mouse	1400 mg/kg	-

Conclusion/Summary

: Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2 -methylimidazole	500	N/A	N/A	N/A	N/A

Irritation/Corrosion

Date of issue/Date of revision: 26-5-2023Version: 2Date of previous issue: 25-11-202210/18AkzoNobel

HGF03R Resicoat R4-ES

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
<mark>b</mark> ísphenol A	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
	Skin - Mild irritant	Rabbit	-	ug 250 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	

Conclusion/Summary

: Not available.

Sensitisation

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
sphenol A	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced foetal weight increase in foetal deaths skeletal malformations

Date of issue/Date of revision : 26-5-2023 Version : 2

Date of previous issue : 25-11-2022 11/18 AkzoNobel

HGF03R Resicoat R4-ES

SECTION 11: Toxicological information

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains

reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity: May damage fertility.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Date of issue/Date of revision : 26-5-2023 Version : 2

Date of previous issue : 25-11-2022 12/18 AkzoNobel

HGF03R Resicoat R4-ES

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
sphenol A	Acute EC50 1.506 mg/l Marine water	Algae - Prorocentrum minimum	72 hours
		- Exponential growth phase	
	Acute EC50 1.51 mg/l Marine water	Algae - Prorocentrum minimum	72 hours
		- Exponential growth phase	
	Acute EC50 2700 μg/l Fresh water	Algae - Pseudokirchneriella	96 hours
		subcapitata	
	Acute EC50 1000 μg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 1800 μg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 7.75 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 20.5 mg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute EC50 10200 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 9940 µg/l Fresh water	Daphnia - Daphnia magna - Young	48 hours
	Acute EC50 5.246 mg/l Fresh water	Fish - Danio rerio - Embryo	96 hours
	Acute LC50 3.881 mg/l Marine water	Crustaceans - Acartia tonsa - Copepodid	48 hours
	Acute LC50 4.04371 mg/l Marine water		48 hours
	Acute LC50 1.34 mg/l Marine water	Crustaceans - Americamysis bahia - Larvae	48 hours
	Acute LC50 1600 μg/l Marine water	Crustaceans - Americamysis bahia	48 hours
	Acute LC50 50.4 µg/l Marine water	Crustaceans - Artemia sinica	48 hours
	Acute LC50 12.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 4.2 mg/l Fresh water	Fish - Pimephales promelas - Larvae	96 hours
	Acute LC50 4700 μg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 4600 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 3.5 mg/l Marine water	Fish - Rivulus marmoratus - Embryo	96 hours
	Chronic NOEC 5 mg/l Fresh water	Algae - Chlorella pyrenoidosa	72 hours
	Chronic NOEC 4 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 4 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 2 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 0.1 mg/l Fresh water	Crustaceans - Asellus aquaticus - Juvenile (Fledgling,	21 days
		Hatchling, Weanling)	
	Chronic NOEC 0.05 mg/l Fresh water	Crustaceans - Asellus	21 days
		aquaticus - Juvenile (Fledgling, Hatchling, Weanling)	
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 0.8 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.86 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.86 mg/l Fresh water	Daphnia - Daphnia magna -	21 days

AkzoNobel

Date of issue/Date of revision: 26-5-2023Version: 2Date of previous issue: 25-11-202213/18

Acute LC50 286000 µg/l Fresh water

HGF03R Resicoat R4-ES

SECTION 12: Ecological information Neonate Daphnia - Daphnia magna -Chronic NOEC 30 µg/l Fresh water 21 days Neonate Fish - Carassius auratus - Adult Chronic NOEC 0.2 µg/I Fresh water 30 days Chronic NOEC 0.2 µg/l Fresh water Fish - Carassius auratus - Adult 60 days Chronic NOEC 0.2 µg/I Fresh water Fish - Carassius auratus - Adult 90 days Chronic NOEC 0.2 µg/l Fresh water Fish - Carassius auratus - Adult 90 days Fish - Oryzias latipes - Embryo Chronic NOEC 6 µg/l Fresh water 44 days

Fish - Pimephales promelas

96 hours

AkzoNobel

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
prisphenol A	3.4	20 to 67	low
2-methylimidazole	0.24	-	low

12.4 Mobility in soil

2-methylimidazole

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Date of issue/Date of revision: 26-5-2023Version: 2Date of previous issue: 25-11-202214/18

HGF03R Resicoat R4-ES

SECTION 13: Disposal considerations

Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable.

: 26-5-2023 Date of issue/Date of revision Version : 2

AkzoNobel Date of previous issue : 25-11-2022 15/18

HGF03R Resicoat R4-ES

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Poxic to reproduction	bisphenol A 2-methylimidazole	Recommended Candidate	ED/01/2018 D(2020) 4578-DC	10/1/2019 6/25/2020
Endocrine disrupting properties for human health	bisphenol A	Recommended	ED/01/2018	10/1/2019
Endocrine disrupting properties for environment	bisphenol A	Recommended	ED/01/2018	10/1/2019

Annex XVII - Restrictions

: Restricted to professional users.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : Not applicable. : Not applicable.

VOC for Ready-for-Use Mixture

Industrial emissions

: Not listed

(integrated pollution

prevention and control) -

Air

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety

legislation. The provisions of the national health and safety at work regulations apply

to the use of this product at work.

International regulations

Date of issue/Date of revision : 26-5-2023 Version : 2

AkzoNobel Date of previous issue : 25-11-2022 16/18

HGF03R Resicoat R4-ES

SECTION 15: Regulatory information

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
E ye Dam. 1, H318	Calculation method	
Skin Sens. 1, H317	Calculation method	
Repr. 1B, H360F	Calculation method	

Full text of abbreviated H statements

⊮ 302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated
	exposure.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision: 26-5-2023Version: 2Date of previous issue: 25-11-202217/18AkzoNobel

HGF03R Resicoat R4-ES

SECTION 16: Other information

Acute Tox. 4 ACUTE TOXICITY - Category 4 Carc. 2 **CARCINOGENICITY - Category 2**

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Repr. 1B REPRODUCTIVE TOXICITY - Category 1B Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C Skin Sens. 1

SKIN SENSITISATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 1

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -

Category 3

Date of printing : 26 May 2023 Date of issue/ Date of : 26 May 2023

revision

STOT RF 1

STOT SE 3

Date of previous issue : 25 November 2022

Version : 2 **Unique ID**

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 26-5-2023 Version : 2

AkzoNobel Date of previous issue : 25-11-2022 18/18