

SAFETY DATA SHEET

NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)
SDS code	: 8237891

NL061F/25KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Industrial use		
	Uses advised against	
All other uses		
Descharteres		

Product use

: Electrostatic coating for use in industrial plants

1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited Stoneygate Lane, Felling, Gateshead. NE10 0JY United Kingdom e-mail address of person : sdsfellinguk@akzonobel.com responsible for this SDS <u>National contact</u> 01 8092566 or 01 8379964 1.4 Emergency telephone number <u>National advisory body/Poison Centre</u>

Telephone number	: +44 (0)344 892 0111
<u>Supplier</u>	
Telephone number	: +44 0191 469 6111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	1/14	AkzoNobel

		NEUGIF/25KG Interport 610LB GREY 7001 GLOSS AGI (85)
SECTION 2: Hazards	i	dentification
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Safety data sheet available on request. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Special packaging requirem	ner	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form combustible dust concentrations in air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤15	Carc. 2, H351 (inhalation)	-	[1] [*]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	2/14	AkzoNobel

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

Hazards from the	: May form explosible dust-air mixture if dispersed.
substance or mixture	

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	3/14	AkzoNobel

SECTION 5: Firefighting measures		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling



SECTION 7: Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)		
Recommendations	: Not available	÷.
Industrial sector specific	: Not available	÷.
solutions		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
titanium dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 4 mg/m ³ 8 hours. Form: respirable TWA: 10 mg/m ³ 8 hours. Form: total inhalable
procedures atmosphe of the ver protective the follow the asses limit value atmosphe of exposu (Workplay for the me	duct contains ingredients with exposure limits, personal, workplace ere or biological monitoring may be required to determine the effectiveness intilation or other control measures and/or the necessity to use respiratory e equipment. Reference should be made to monitoring standards, such as ving: European Standard EN 689 (Workplace atmospheres - Guidance for ssment of exposure by inhalation to chemical agents for comparison with es and measurement strategy) European Standard EN 14042 (Workplace eres - Guide for the application and use of procedures for the assessment ure to chemical and biological agents) European Standard EN 482 ce atmospheres - General requirements for the performance of procedures easurement of chemical agents) Reference to national guidance ts for methods for the determination of hazardous substances will also be
DNELS/DMELS	

DNELs/DMELs

No DNELs/DMELs available.

PNECs

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	5/14	AkzoNobel

SECTION 8: Exposure controls/personal protection

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection meas	ires
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	Solid. [Powder.]	
Colour	Grey.	
Odour	Odourless.	
Odour threshold	Not available.	
Melting point/freezing point	Not available.	
Flammability	Not available.	
Lower and upper explosion limit	20 - 70 g/m3	
Auto-ignition temperature	450 to 600°C (842 to 1112°F)	
Decomposition temperature	Not available.	
рН	Not applicable. [DIN EN 1262]	
Viscosity	Kinematic (room temperature): Not applicable. [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219]	
Solubility(ies)		

So	lub	ility	(ies)
----	-----	-------	-------

Media		Result	
cold water		Not soluble [OESO (TG 105)]	
Partition coefficient: n-octanol/ water	:	Not applicable.	
Vapour pressure	: 1	Not available.	
Relative density	: '	1.2 to 1.9 [ISO 8130-2/-3]	
Vapour density	: 1	Not applicable.	
Particle characteristics			
Median particle size	:	Not available.	
Percentage of particles with aerodynamic diameter ≤ 10 μm	: (0	

9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.		
Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	7/14	AkzoNobel

NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)

SECTION 10: Stability and reactivity		
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	
SECTION 11: Toxicological information		
11.1 Information on hazard c Acute toxicity	lasses as defined in Regulation (EC) No 1272/2008	
Conclusion/Summary Acute toxicity estimates	: Not available.	

Irritation/Corrosion		
Conclusion/Summary	:	Not available.
<u>Sensitisation</u>		
Conclusion/Summary	:	Not available.
Mutagenicity		
Conclusion/Summary	:	Not available.
Carcinogenicity		
Conclusion/Summary	:	Not available.
Reproductive toxicity		
Conclusion/Summary	:	Not available.
Teratogenicity		
Conclusion/Summary	:	Not available.
Specific target organ toxicity	<u>y (</u>	<u>single exposure)</u>

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following:
	irritation
	redness

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	8/14	AkzoNobel

NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)

SECTION 11: Toxicological information		
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
<u>Long term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health effe	<u>ects</u>	
Not available.		
Conclusion/Summary	: Not available.	
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive toxicity	: No known significant effects or critical hazards.	

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNo additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	9/14	AkzoNobel

NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)

SECTION 12: Ecological information

	dubia - Neonate	
Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex -	48 hours
	Neonate	
Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

Date of issue/Date of revision	: 18-9-2023	Version : 4	
Date of previous issue	: 7-6-2023	10/14	AkzoNobel

SECTION 13: Disposal considerations

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB) /REACH</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision	: 18-9-2023
Date of previous issue	: 7-6-2023



SECTION 15: Regulatory information

SECTION 15: Regula	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations	: Not applicable.
VOC	: Not applicable.
VOC for Ready-for-Use	: Not applicable.
Mixture	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substance Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)
Persistent Organic Polluta Not listed.	<u>nts</u>
National regulations Biocidal products regulation	l under the Seveso Directive. on on List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on F Not listed.	Persistent Organic Pollutants
Rotterdam Convention on P Not listed.	rior Informed Consent (PIC)
UNECE Aarhus Protocol on Not listed.	POPs and Heavy Metals
15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried out.



NL061F/25KG Interpon 610LB GREY 7001 GLOSS AGI (85)

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

H351		Suspected of causing cancer.	
Full text of classifications	[CLP/GHS]		
Carc. 2		CARCINOGENICITY - Category 2	
Date of printing	: 18-9-2023		
Date of issue/ Date of revision	: 18-9-2023		
Date of previous issue	: 7-6-2023		
Version	: 4		

Unique ID

Notice to reader

FOR PROFESSIONAL USE ONLY

5

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.



Date of issue/Date of revision
Date of previous issue

