

## SAFETY DATA SHEET

GA218QF INT D1010 SGN WHITE INTENSE RAL9003 25KG

#### Section 1. Identification

GHS product identifier : GA218QF INT D1010 SGN WHITE INTENSE RAL9003 25KG

**SDS code** : 8239589

GA218QF/25KG

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Powder coating. Industrial use

Uses advised against

All other uses

Product use : Electrostatic coating for use in industrial plants

Supplier's details

Akzo Nobel Coatings Inc. 150 Columbia Street Reading, PA 19601 USA

1-610-372-3600

Emergency telephone

number (with hours of operation)

: CHEMTREC +1 (800) 424-9300 (Inside the US)

CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls

accepted)

## Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : COMBUSTIBLE DUSTS

substance or mixture CARCINOGENICITY - Category 2

**TOXIC TO REPRODUCTION - Category 2** 

**GHS** label elements

Hazard pictograms



Signal word : Warning

**Hazard statements** : Suspected of causing cancer.

Suspected of damaging fertility or the unborn child. May form combustible dust concentrations in air.

**Precautionary statements** 

**Prevention**: Obtain special instructions before use. Wear protective gloves, protective clothing and

eye or face protection.

**Response**: IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Date of issue/Date of revision : 9/8/2023 Version : 1.01

Date of previous issue :11/23/2022 1/12 AkzoNobel

## Section 2. Hazards identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.

Hazards not otherwise classified

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

## Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact**: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

**Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

irritation redness

Date of issue/Date of revision : 9/8/2023 Version : 1.01

Date of previous issue :11/23/2022 2/12 AkzoNobel

#### Section 4. First aid measures

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a potentially explosible

dust-air mixture.

Specific hazards arising

from the chemical

Hazardous thermal decomposition products

: May form explosible dust-air mixture if dispersed.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Date of issue/Date of revision : 9/8/2023 Version : 1.01

Date of previous issue :11/23/2022 3/12 AkzoNobel

#### Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

#### Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## including any incompatibilities

**Conditions for safe storage,** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 9/8/2023 Version: 1.01

**AkzoNobel** Date of previous issue : 11/23/2022 4/12

## Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits	
titanium dioxide	OSHA PEL (United States, 5/2018).  TWA: 15 mg/m³ 8 hours. Form: Total dust OSHA PEL 1989 (United States, 3/1989).  TWA: 10 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124):36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A Carcinogens.	
aluminium hydroxide cobalt chromite green spinel	A Carcinogens.  TWA: 10 mg/m³ 8 hours.  None.  OSHA PEL 1989 (United States, 3/1989).  TWA: 0.5 mg/m³, (as Cr) 8 hours.  NIOSH REL (United States, 10/2016).  TWA: 0.5 mg/m³, (as CR) 8 hours.  ACGIH TLV (United States, 3/2020).  TWA: 0.5 mg/m³, (measured as Cr) 8 hours.  Form: Inhalable fraction  TWA: 0.02 mg/m³, (as Co) 8 hours.  OSHA PEL (United States, 5/2018).  TWA: 0.5 mg/m³, (as Cr) 8 hours.	
propylidynetrimethanol	None.	

## Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

#### **Skin protection**

Date of issue/Date of revision: 9/8/2023Version: 1.01Date of previous issue: 11/23/20225/12AkzoNobel

## Section 8. Exposure controls/personal protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Solid. [Powder.]

Color : White.

Odor : Odorless.

Odor threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Flammability : Not available.

Lower and upper explosion : Not available.

limit

Vapor pressure : Relative vapor density :

**Relative density** : 1.2 to 1.9 [ISO 8130-2/-3]

Solubility(ies)

Not available.

Partition coefficient: n-

: Not available.

octanol/water

: 450 to 600°C (842 to 1112°F)

**Decomposition temperature** : Not available.

Minimum ignition energy (mJ)

**Auto-ignition temperature** 

: 5 to 20

**Viscosity** 

: Kinematic (room temperature): Not applicable. Kinematic (40°C (104°F)): Not applicable.

**Particle characteristics** 

Median particle size :

Date of issue/Date of revision: 9/8/2023Version: 1.01

Date of previous issue :11/23/2022 6/12 AkzoNobel

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid the creation of dust when handling and avoid all possible sources of ignition

(spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust

accumulation.

**Incompatible materials**: Reactive or incompatible with the following materials:

oxidizing materials

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

## **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

#### **Irritation/Corrosion**

Not available.

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### **Classification**

Product/ingredient name	OSHA IARC	NTP
titanium dioxide	- 2B	- Peasanably anticipated to be a human carsinogen
cobalt chromite green spinel	- 2B - 2B	Reasonably anticipated to be a human ca

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Date of issue/Date of revision: 9/8/2023Version: 1.01Date of previous issue: 11/23/20227/12AkzoNobel

## **Section 11. Toxicological information**

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

**Eye contact**: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

**Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**General**: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

N/A

Date of issue/Date of revision : 9/8/2023 Version : 1.01

Date of previous issue :11/23/2022 8/12 AkzoNobel

## **Section 11. Toxicological information**

## **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	<1	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision: 9/8/2023Version: 1.01Date of previous issue: 11/23/20229/12AkzoNobel

## **Section 14. Transport information**

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

## **Section 15. Regulatory information**

U.S. Federal regulations

: United States inventory (TSCA 8b):

Not determined.

#### **SARA 302/304**

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : COMBUSTIBLE DUSTS

**CARCINOGENICITY - Category 2** 

TOXIC TO REPRODUCTION - Category 2

#### Composition/information on ingredients

Name	%	Classification
titanium dioxide	≥25 - ≤50	CARCINOGENICITY - Category 2
cobalt chromite green spinel	≤0.3	CARCINOGENICITY - Category 2
propylidynetrimethanol	≤0.3	TOXIC TO REPRODUCTION - Category 2

#### **SARA 313**

Date of issue/Date of revision : 9/8/2023 Version: 1.01 **AkzoNobel** 10/12 Date of previous issue : 11/23/2022

GA218QF INT D1010 SGN WHITE INTENSE RAL9003 25KG

## **Section 15. Regulatory information**

	Product name	CAS number	%
Form R - Reporting requirements	cobalt chromite green spinel	68187-49-5	≤0.3
Supplier notification	cobalt chromite green spinel	68187-49-5	≤0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

**Massachusetts** : The following components are listed: TITANIUM DIOXIDE; TIN DIOXIDE DUST;

**BARIUM SULFATE** 

**New York** : None of the components are listed.

: The following components are listed: TITANIUM DIOXIDE; TITANIUM OXIDE (TiO2); **New Jersey** 

BARIUM SULFATE; SULFURIC ACID, BARIUM SALT (1:1); CHROMIUM

**COMPOUNDS** 

Pennsylvania : The following components are listed: TITANIUM OXIDE; BARIUM SULFATE;

CHROMIUM COMPOUNDS

#### California Prop. 65

**WARNING**: Cancer - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
titanium dioxide	-	-	Cancer
crystalline silica	-	-	Cancer
2,2'-iminodiethanol	-	-	Cancer
crystalline silica, respirable powder	-	-	Cancer

#### **Inventory list**

Canada : All components are listed or exempted.

## Section 16. Other information

#### Procedure used to derive the classification

ustification
test data method method
I

#### <u>History</u>

**Date of printing** : 9/8/2023 Date of issue/ Date of : 9/8/2023

revision

Date of previous issue : 11/23/2022

Version : 1.01 **Unique ID** 

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

Date of issue/Date of revision Version: 1.01 : 9/8/2023

**AkzoNobel** Date of previous issue :11/23/2022 11/12

GA218QF INT D1010 SGN WHITE INTENSE RAL9003 25KG

#### Section 16. Other information

UN = United Nations

**▼** Indicates information that has changed from previously issued version.

#### Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 9/8/2023 Version : 1.01

Date of previous issue :11/23/2022 12/12 AkzoNobel