

# SAFETY DATA SHEET

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Product name : NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

**SDS code** : 8248166

NFB06I/20KG

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Industrial use		
	Uses advised against	
All other uses		

Product use : Electrostatic coating for use in industrial plants

### 1.3 Details of the supplier of the safety data sheet

AkzoNobel Powder Coatings Limited

Stoneygate Lane,

Felling, Gateshead. NE10 0JY

United Kingdom e-mail address of person

: sdsfellinguk@akzonobel.com

responsible for this SDS

**National contact** 

01 8092566 or 01 8379964

### 1.4 Emergency telephone number

### National advisory body/Poison Centre

**Telephone number** : +44 (0)344 892 0111

<u>Supplier</u>

**Telephone number** : +44 0191 469 6111

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Date of issue/Date of revision	: 20-9-2023	Version : 2	
Date of previous issue	: 4-5-2023	1/14	AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

### SECTION 2: Hazards identification

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention: Not applicable.Response: Not applicable.Storage: Not applicable.Disposal: Not applicable.

**Supplemental label**: Contains 1,2,2,6,6-pentamethylpiperidin-4-ol. May produce an allergic reaction.

Safety data sheet available on request. Warning! Hazardous respirable dust may

be formed when used. Do not breathe dust.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

**Special packaging requirements** 

Containers to be fitted with child-resistant

fastenings

elements

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: May form combustible dust concentrations in air.

# SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤3	Carc. 2, H351 (inhalation)	-	[1] [*]
1,2,2,6,6-pentamethylpiperidin- 4-ol	EC: 219-292-8 CAS: 2403-89-6	<1	Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Date of issue/Date of revision : 20-9-2023 Version : 2

Date of previous issue :4-5-2023 2/14 AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 3: Composition/information on ingredients**

Type

[1] Substance classified with a health or environmental hazard

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation**: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains 1,2,2,6,6-pentamethylpiperidin-4-ol. May produce an allergic reaction.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision: 20-9-2023Version: 2

Date of previous issue : 4-5-2023 3/14 AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

# SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical powder.

Unsuitable extinguishing

media

: Avoid high pressure media which could cause the formation of a potentially

explosible dust-air mixture.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : May form explosible dust-air mixture if dispersed.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective

equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for

chemical incidents.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 20-9-2023 Version : 2

**AkzoNobel** Date of previous issue : 4-5-2023 4/14

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

### SECTION 6: Accidental release measures

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations : Not available. Industrial sector specific : Not available.

solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### Occupational exposure limits

Product/ingredient name	Exposure limit values
Manium dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020).  TWA: 4 mg/m³ 8 hours. Form: respirable  TWA: 10 mg/m³ 8 hours. Form: total inhalable

# procedures

**Recommended monitoring**: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482

: 20-9-2023 Date of issue/Date of revision Version :2 **AkzoNobel** Date of previous issue : 4-5-2023 5/14

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 8: Exposure controls/personal protection**

(Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
1,2,2,6,6-pentamethylpiperidin-4-ol	DNEL	Long term Oral	1.13 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.13 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.97 mg/m³	General population	Systemic
	DNEL	Long term Dermal	3.16 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	11.2 mg/m³	Workers	Systemic

### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2,6,6-pentamethylpiperidin-4-ol	Fresh water Marine water Sewage Treatment Plant	95.5 μg/l 9.55 μg/l 37.5 mg/l	Assessment Factors Assessment Factors Assessment Factors
	Fresh water sediment Marine water sediment Soil	0.46 mg/kg dwt 46 µg/kg dwt 35.9 µg/kg dwt	Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning

### 8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

### **Skin protection**

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Date of issue/Date of revision : 20-9-2023 Version : 2

Date of previous issue : 4-5-2023 6/14 AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 8: Exposure controls/personal protection**

For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck

and wrists through contact with the powder are avoided.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Environmental exposure

**Body protection** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Solid. [Powder.]

Colour : Orange.

Odour : Odourless.

Odour threshold : Not available.

Melting point/freezing point : Not available.

Flammability : Not available.

Lower and upper explosion : 20 - 70 g/m3

Lower and upper explosion limit

**Auto-ignition temperature** 

**Decomposition temperature** : Not available.

pH : Not applicable. [DIN EN 1262]

Viscosity : Kinematic (room temperature): Not applicable. [DIN EN ISO 3219]

: 450 to 600°C (842 to 1112°F)

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies) :

Media	Result
cold water	Not soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable. water

Date of issue/Date of revision : 20-9-2023 Version : 2

Date of previous issue :4-5-2023 7/14 AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 9: Physical and chemical properties**

Vapour pressure : Not available.

**Relative density** : 1.2 to 1.9 [ISO 8130-2/-3]

Vapour density : Not applicable.

**Particle characteristics** 

Median particle size : Not available.

Percentage of particles with aerodynamic diameter ≤ 10

μm

: 0

#### 9.2 Other information

Minimum ignition energy (mJ) : 5 to 20

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid the creation of dust when handling and avoid all possible sources of ignition

(spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust

accumulation.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:

oxidising materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

**Conclusion/Summary**: Not available.

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2,2,6,6-pentamethylpiperidin-4-ol	500	N/A	N/A	N/A	N/A

### **Irritation/Corrosion**

**Conclusion/Summary**: Not available.

<u>Sensitisation</u>

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

Carcinogenicity

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 11: Toxicological information**

: Not available. Conclusion/Summary

Reproductive toxicity

**Conclusion/Summary** : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data. Ingestion : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards.

Date of issue/Date of revision : 20-9-2023 Version : 2

**AkzoNobel** Date of previous issue : 4-5-2023 9/14

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 11: Toxicological information**

**Reproductive toxicity**: No known significant effects or critical hazards.

### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

No additional information.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

**Conclusion/Summary**: Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2,2,6,6-pentamethylpiperidin- 4-ol	1.15	-	low

### 12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Date of issue/Date of revision	: 20-9-2023	Version : 2	
Date of previous issue	: 4-5-2023	10/14	AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 12: Ecological information**

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

### **Product**

**Methods of disposal**: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as

hazardous waste, as defined by EU Directive 2008/98/EC.

**Disposal considerations**: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 02 01	waste coating powders

### **Packaging**

**Methods of disposal**: The generation of waste should be avoided or minimised wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

**Disposal considerations**: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

**Special precautions**: This material and its container must be disposed of in a safe way. Empty containers

or liners may retain some product residues. Avoid dispersal of spilt material and

runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 20-9-2023 Version : 2

Date of previous issue : 4-5-2023 11/14 AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

# **Section 14. Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not applicable.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

### Annex XIV - List of substances subject to authorisation

### **Annex XIV**

None of the components are listed.

### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC VOC for Ready-for-Use

**Mixture** 

: Not applicable.

: Not applicable.

: Not applicable.

Industrial emissions (integrated pollution : Not listed

prevention and control) -Air

Date of issue/Date of revision : 20-9-2023 Version : 2

**AkzoNobel** Date of previous issue : 4-5-2023 12/14

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

## **SECTION 15: Regulatory information**

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information** 

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

### Full text of abbreviated H statements

Date of issue/Date of revision: 20-9-2023Version: 2Date of previous issue: 4-5-202313/14AkzoNobel

NFB06I PFP 610LOW-E BUC ARANCIO 2010 HR

SECTION 16: Other information		
H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H351	Suspected of causing cancer.	
H411	Toxic to aquatic life with long lasting effects.	

### Full text of classifications [CLP/GHS]

ACUTE TOXICITY - Category 4
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
CARCINOGENICITY - Category 2
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
SKIN CORROSION/IRRITATION - Category 1
SKIN SENSITISATION - Category 1

Date of printing : 20-9-2023 Date of issue/ Date of : 20-9-2023

revision

Date of previous issue : 4-5-2023

Version : 2 Unique ID :

### **Notice to reader**

### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 20-9-2023 Version : 2

Date of previous issue : 4-5-2023 14/14 AkzoNobel