

# **SAFETY DATA SHEET**

#### HFD11QF RESICOAT® EL ECA-1283 SAFETY ORANGE

## **Section 1. Identification**

#### Product identifier SDS code

 HFD11QF RESICOAT® EL ECA-1283 SAFETY ORANGE
 8263811 HFD11QF/20KG

#### Relevant identified uses of the substance or mixture and uses advised against

	Recomm	ended use	
Powder coating. Professiona	l use Industrial use		
	Restriction	ons on use	
All other uses			
Product use	: Electrostatic coating for	use in industrial plants	
Supplier's details			
Akzo Nobel Coating 150 Columbia Stree Reading, PA 19601 1-610-372-3600	et	Akzo Nobel Coatings Ltd. 110 Woodbine Downs Blvd. Unit #4 Etobicoke, Ontario Canada M9W 5S6	
Emergency telephone number (with hours of operation)	: CHEMTREC +1 (800) 42 CHEMTREC Internation accepted) 24 hours	24-9300 (Inside the US) al +1 (703) 527-3887 (Outside the	US, collect calls
Section 2. Hazard	l identification		
Classification of the substance or mixture	: COMBUSTIBLE DUSTS SKIN SENSITIZATION - CARCINOGENICITY - C TOXIC TO REPRODUC	Category 1 ategory 2	
GHS label elements			
Hazard pictograms			
Signal word	: Danger		
Hazard statements	: May cause an allergic sk Suspected of causing ca May damage fertility or the May form combustible d	ncer. ne unborn child.	
Precautionary statements			
Prevention		ns before use. Wear protective glov n. Avoid breathing dust or mist.	es, protective clothing
Response	clothing and wash it befo	d: Get medical advice or attention. T are reuse. IF ON SKIN: Wash with p Get medical advice or attention.	
Date of issue/Date of revision	: 2/24/2023	Version : 1	
Date of previous issue	: No previous validation	1/13	AkzoNobel

## Section 2. Hazard identification

Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	: Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Section 3. Com	position/information on ingredients
Substance/mixture	: Mixture

Substance/mixture	: Mixte
Other means of	:
identification	

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

## **Section 4. First-aid measures**

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.		
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Most important symptoms/effects, acute and delayed			

Potential acute health effe			
Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.	•	
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.		
Skin contact	May cause an allergic skin reaction.		
Ingestion	No known significant effects or critical hazards.		
Over-exposure signs/sym	<u>IS</u>		
Eye contact	Adverse symptoms may include the following: irritation redness		
Date of issue/Date of revision	: 2/24/2023 Version : 1		
Date of previous issue	: No previous validation 2/13 AkzoNo	bel	

# Section 4. First-aid measures

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. For non-emergency Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". **Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Methods and materials for containment and cleaning up Small spill : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. : Move containers from spill area. Use spark-proof tools and explosion-proof Large spill equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

Dispose of via a licensed waste disposal contractor. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

information on hygiene measures.



# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
--	---

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
titanium dioxide	<ul> <li>CA British Columbia Provincial (Canada, 1/2020).</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> <li>CA Quebec Provincial (Canada, 7/2019).</li> <li>TWAEV: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust.</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>Skin sensitizer.</li> <li>8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours. Form: total dust</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 20 mg/m<sup>3</sup> 15 minutes.</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours.</li> </ul>

controls	vapor or mist, use process enclosures, controls to keep worker exposure to airly recommended or statutory limits. The e vapor or dust concentrations below any ventilation equipment.	engineering controls also need to keep gas, lower explosive limits. Use explosion-proof	f
Environmental exposure : controls			
Individual protection measures			
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.		
Date of issue/Date of revision	: 2/24/2023	Version :1	
Date of previous issue	: No previous validation	5/13 AkzoNobe	

# Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### Appearance

Date of previous issue		: 2/24/2023 : No previous validation	Version 6/13	: 1	AkzoNobel
Median particle size Date of issue/Date of revision	:	. 0/04/2022	Varaiar	. 1	
Particle characteristics					
Viscosity	:	Kinematic (room temperature): Not ap Kinematic (40°C (104°F)): Not applica			
(mJ)	-				
Minimum ignition energy		5 to 20			
Decomposition temperature		Not available.			
Auto-ignition temperature		450 to 600°C (842 to 1112°F)			
Partition coefficient: n- octanol/water	:	Not available.			
Not available.					
Solubility(ies)	:				
Relative density	:	1.2 to 1.9 [ISO 8130-2/-3]			
Relative vapor density	:				
Vapor pressure	:				
Lower and upper explosion limit/flammability limit	:	Not available.			
Flammability	:	Not available.			
Flash point		Closed cup: Not applicable.			
Boiling point, initial boiling point, and boiling range	:	Not available.			
Melting point/freezing point		Not available.			
рН	:	Not applicable.			
Odor threshold	:	Not available.			
Odor	:	Odorless.			
Color	:	Orange.			
Physical state	:	Solid. [Powder.]			
Appearance					

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Info

<u>formation on toxicological</u> Acute toxicity	effects			
Product/ingredient name	Result	Species	Dose	Exposur
bisphenol A	LD50 Dermal	Rabbit	3 mL/kg	-
•	LD50 Intraperitoneal	Mouse	150 mg/kg	-
	LD50 Intraperitoneal	Rat	200 mg/kg	-
	LD50 Oral	Guinea pig	4 g/kg	-
	LD50 Oral	Guinea pig	4000 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
	LD50 Oral	Mouse	2500 mg/kg	-
	LD50 Oral	Mouse	2500 mg/kg	-
	LD50 Oral	Rabbit	2230 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Oral	Rat	4240 mg/kg	-
	LD50 Oral	Rat	3250 mg/kg	-
	LD50 Subcutaneous	Rabbit	3000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Rabbit	-	24 hours 500 Ul	-
bisphenol A	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
	Skin - Mild irritant	Rabbit	-	ug 24 hours 500	-
	Skin - Mild irritant	Rabbit	-	mg 250 mg	-

### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.



# Section 11. Toxicological information

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name		Category	Route of exposure	Target organs
bisphenol A		Category 3	-	Respiratory tract irritation
Specific target organ toxic	<u>ity (repeated exposu</u>	<u>ire)</u>		
Not available.				
Aspiration hazard				
Not available.				
nformation on the likely outes of exposure	: Not available.			
Potential acute health effect	<u>ts</u>			
Eye contact		orne concentrations abov orritation of the eyes.	e statutory or reco	mmended exposure
Inhalation		orne concentrations abov irritation of the nose, thro		mmended exposure
Skin contact	: May cause an al	: May cause an allergic skin reaction.		
Ingestion Symptoms related to the pl	-	cant effects or critical haz		
Eye contact		ms may include the follow		
Inhalation	: Adverse symptol respiratory tract coughing reduced fetal we increase in fetal skeletal malform	ight deaths	/ing:	
Skin contact	: Adverse sympton irritation redness reduced fetal we increase in fetal skeletal malform	deaths	/ing:	
Ingestion	: Adverse sympton reduced fetal we increase in fetal skeletal malform	deaths	ing:	

#### Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure

# Section 11. Toxicological information

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
Not available.		
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
		May damage fertility or the unborn child.

#### Acute toxicity estimates

N/A

Section	12.	Ecological	information
Jection	14.	LCOIOgical	mormation

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
bisphenol A	Acute EC50 1000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 1800 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 1.506 mg/l Marine water	Algae - Prorocentrum minimum - Exponential growth phase	72 hours
	Acute EC50 1.51 mg/l Marine water	Algae - Prorocentrum minimum - Exponential growth phase	72 hours
	Acute EC50 2700 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
Date of issue/Date of revision	: 2/24/2023	Version :1	
Date of previous issue	: No previous validation	9/13 AI	czoNobe

# Section 12. Ecological information

Section 12. Ecolo	gical information		
	Acute EC50 7.75 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 20.5 mg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute EC50 10200 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 9940 µg/l Fresh water	Daphnia - Daphnia magna - Young	48 hours
	Acute EC50 5.246 mg/l Fresh water	Fish - Danio rerio - Embryo	96 hours
	Acute LC50 50.4 µg/l Marine water	Crustaceans - Artemia sinica	48 hours
	Acute LC50 3.881 mg/l Marine water	Crustaceans - Acartia tonsa - Copepodid	48 hours
	Acute LC50 4.04371 mg/l Marine water	Crustaceans - Acartia tonsa - Copepodid	48 hours
	Acute LC50 1.34 mg/l Marine water	Crustaceans - Americamysis bahia - Larvae	48 hours
	Acute LC50 1600 µg/l Marine water	Crustaceans - Americamysis bahia	48 hours
	Acute LC50 12.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 4.2 mg/l Fresh water	Fish - Pimephales promelas - Larvae	96 hours
	Acute LC50 4700 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 4600 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 3.5 mg/l Marine water	Fish - Rivulus marmoratus - Embryo	96 hours
	Chronic NOEC 4 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 4 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 2 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 5 mg/l Fresh water Chronic NOEC 0.1 mg/l Fresh water	Algae - Chlorella pyrenoidosa Crustaceans - Asellus aquaticus - Juvenile (Fledgling, Hatchling, Weanling)	72 hours 21 days
	Chronic NOEC 0.05 mg/l Fresh water	Crustaceans - Asellus aquaticus - Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 0.8 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.86 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.86 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 30 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	30 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	60 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	90 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	90 days
	Chronic NOEC 6 µg/l Fresh water	Fish - Oryzias latipes - Embryo	44 days
		,	-

#### Persistence and degradability



# Section 12. Ecological information

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	low
bisphenol A	3.4	20 to 67	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

#### **Additional information**

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision	: 2/24/2023	Version : 1	
Date of previous issue	: No previous validation	11/13	AkzoNobel

# Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

## Section 15. Regulatory information

<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: vanadium (and its compounds)
CEPA Toxic substances	<ul> <li>The following components are listed: phenol, 4,4' -(1-methylethylidene)bis-; bisphenol A</li> </ul>
Inventory list	
Canada	: All components are listed or exempted.
United States	: All components are active or exempted.

## Section 16. Other information

<u>History</u>	
Date of printing	: 24 February 2023
Date of issue/ Date of revision	: 24 February 2023
Date of previous issue	: No previous validation
Version	: 1
Unique ID	:
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>

#### Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS - Category 1 SKIN SENSITIZATION - Category 1	On basis of test data Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1	Calculation method

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is

Date of issue/Date of revision	: 2/24/2023	Version : 1	
Date of previous issue	: No previous validation	12/13	AkzoNobel

# Section 16. Other information

current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

